

PV204 Laboratory of security and applied cryptography II

Lecture: Reverse code engineering

Powerfull knowledge, lot of fun and legal for several purposes!

Basic information available in Wikipedia article on reverse engineering (IS copy REWiki.pdf)

- RE in general, example with B-29, synthetic chemistry/biology
- Legality
 - Own binary without documentation
 - Interoperability
 - Anti-virus research
 - Fair use, education
 - Problem with recent copyright laws (attempt to circumvent is illegal, not only selling circumvented content)
 - Forensics
- Disassembler vs. debugger
 - Static vs. dynamic code analysis
 - Debugger vs. Debugger with advanced modification tools (Visual Studio vs. OllyDbg)
- Assembler vs. bytecode
 - Instruction set (downloadable)
 - Register-based vs. stack-based execution
- Structured code vs. sequence of executed instructions
 - Structured code contains code for all branches (runable binary)
 - Sequence of executed instructions only from branches taken (power analysis of smart card)
- Example: Java Card bytecode
 - sspush, sspush, add, ifeq
- Example: Win32 binary
 - Lena tutorials 1 and 2
 - Name of the registers (EAX 32bit, AX 16bit, AH/AL 8bit)
 - Flags (Zero/Sign/Carry)

Java(Card) bytecode

Intermediate code interpreted by virtual machine (see JavaCard222_ops.pdf).

- Usually easier to understand than assembler code.
- Stack-based oriented execution, no registers are used (all operands at the top of the stack).
- Operation takes its operands from stack and return result there.
- JavaCard example selected because of lower number of opcodes.
- Same principle works for Java, .NET CLI ...

```
// ENCRYPT INCOMING BUFFER
void Encrypt(APDU apdu) {
    byte[]    apdubuf = apdu.getBuffer();
    short     dataLen = apdu.setIncomingAndReceive();
    short     i;

    // CHECK EXPECTED LENGTH (MULTIPLY OF 64 bites)
    if ((dataLen % 8) != 0)
        ISOException.throwIt(SW_CIPHER_DATA_LENGTH_BAD);

    // ENCRYPT INCOMING BUFFER
    m_encryptCipher.doFinal(apdubuf, ISO7816.OFFSET_CDATA, dataLen,
                           m_ramArray, (short) 0);

    // COPY ENCRYPTED DATA INTO OUTGOING BUFFER
    Util.arrayCopyNonAtomic(m_ramArray, (short) 0, apdubuf,
                           ISO7816.OFFSET_CDATA, dataLen);

    // SEND OUTGOING BUFFER
    apdu.setOutgoingAndSend(ISO7816.OFFSET_CDATA, dataLen);
}
```

Original JavaCard source code

```
.method Encrypt(Ljavacard/framework/APDU;)V 129 {
    .stack 6;
    .locals 3;
    .descriptor    Ljavacard/framework/APDU;    0.10;
        L0:    aload_1;
            invokevirtual 30;
            astore_2;
            aload_1;
            invokevirtual 42;
            sstore_3;
            sload_3;
            bspush 8;
            srem;
            ifeq L2;
        L1:    sspush 26384;
            invokestatic 41;
            goto L2;
        L2:    getfield_a_this 1;
            aload_2;
            sconst_5;
            sload_3;
            getfield_a_this 10;
            sconst_0;
            invokevirtual 43;
```

```

    pop;
    getfield_a_this 10;
    sconst_0;
    aload_2;
    sconst_5;
    sload_3;
    invokestatic 44;
    pop;
    aload_1;
    sconst_5;
    sload_3;
    invokevirtual 45;
    return;
}

```

Resulting JavaCard bytecode

Native binary code (assembler)

How to start quickly with assembler (mixed mode)

Most current IDE supports mixed source code/assembler instructions mode (Visual Studio, QT Creator...). Mode is usually available during a debugging.

1. Write simple code (e.g., if then else condition), insert breakpoint and start debugging
2. Switch to mixed mode
 - a. Visual Studio→RClick →Go to disassembly
 - b. QTcreator→Debug→Operate by Instruction
3. Learn how particular source code is translated into assembler code

```

#include <stdio.h>
int main() {
    FILE* file = NULL;
    file = fopen("values.txt", "r");

    if (file) {
        int value1 = 0;
        int value2 = 0;
        fscanf(file, "%d", &value1);
        fscanf(file, "%d", &value2);

        value1 = value1 + value2;

        printf("Result: %d", value1);
    }
    fclose(file);
}


```

Original C source code

00401340	90	NOP
00401341	90	NOP
00401342	90	NOP
00401343	55	PUSH EBP
00401344	89E5	MOV EBP,ESP
00401345	83E4 F0	AND ESP,FFFFFFF0
00401346	83EC 20	SUB ESP,20
00401347	E8 CE060000	CALL Test_C.00401A20
00401348	C74424 1C 000	MOV DWORD PTR SS:[ESP+1C],0
00401349	C74424 04 302	MOV DWORD PTR SS:[ESP+4],Test_C.00402030
0040134A	C70424 322040	MOV DWORD PTR SS:[ESP],Test_C.00402032
0040134B	E8 22090000	CALL <JMP.&msvcrt.fopen>
0040134C	894424 1C	MOV DWORD PTR SS:[ESP+1C],EAX
0040134D	837C24 1C 00	CMP DWORD PTR SS:[ESP+1C],0
0040134E	74 6B	JE SHORT Test_C.004013E4
0040134F	C74424 18 000	MOV DWORD PTR SS:[ESP+18],0
00401350	C74424 14 000	MOV DWORD PTR SS:[ESP+14],0
00401351	8D4424 18	LEA EAX,DWORD PTR SS:[ESP+18]
00401352	894424 08	MOV DWORD PTR SS:[ESP+8],EAX
00401353	C74424 04 302	MOV DWORD PTR SS:[ESP+4],Test_C.00402030
00401354	8B4424 1C	MOV EAX,DWORD PTR SS:[ESP+1C]
00401355	890424	MOV DWORD PTR SS:[ESP],EAX
00401356	E8 F3080000	CALL <JMP.&msvcrt.fscanf>
00401357	8D4424 14	LEA EAX,DWORD PTR SS:[ESP+14]
00401358	894424 08	MOV DWORD PTR SS:[ESP+8],EAX
00401359	C74424 04 302	MOV DWORD PTR SS:[ESP+4],Test_C.00402030
0040135A	8B4424 1C	MOV EAX,DWORD PTR SS:[ESP+1C]
0040135B	890424	MOV DWORD PTR SS:[ESP],EAX
0040135C	E8 D7080000	CALL <JMP.&msvcrt.fscanf>
0040135D	8B5424 18	MOV EDI,DWORD PTR SS:[ESP+18]
0040135E	8B4424 14	MOV EAX,DWORD PTR SS:[ESP+14]
0040135F	8D0402	LEA EAX,DWORD PTR DS:[EDI+EAX]
00401360	894424 18	MOV DWORD PTR SS:[ESP+18],EAX
00401361	8B4424 18	MOV EAX,DWORD PTR SS:[ESP+18]
00401362	894424 04	MOV DWORD PTR SS:[ESP+4],EAX
00401363	C70424 402040	MOV DWORD PTR SS:[ESP],Test_C.00402040
00401364	E8 BC080000	CALL <JMP.&msvcrt.printf>
00401365	8B4424 1C	MOV EAX,DWORD PTR SS:[ESP+1C]
00401366	890424	MOV DWORD PTR SS:[ESP],EAX
00401367	E8 B8080000	CALL <JMP.&msvcrt.fclose>
00401368	B8 00000000	MOV EAX,0
00401369	C9	LEAVE
0040136A	C3	RETN
0040136B	90	NOP
0040136C	00	DB 00
0040136D	00	DB 00
0040136E	00	DB 00
0040136F	00	DB 00

Relevant snapshot from executable binary

- value = value + value2;
1. Načtení hodnot z HDD do RAM paměti
 - fscanf("%d", &value);
 2. Přesun hodnot z RAM paměti do registru CPU
 - MOV 0x48(%esp),%eax
 3. Provedení instrukce procesoru (např. ADD)
 - ADD %edx,%eax
 4. Uložení výsledku registru CPU do RAM
 - MOV %eax, 0x48(%esp)
 5. Vypsání na standardní výstup
 - printf("%d", value);



```
Dump of assembler code for function main:
2      int main() {
0x00401344 <+0>:      push    %ebp
0x00401345 <+1>:      mov     %esp,%ebp
0x00401347 <+3>:      and     $0xffffffff,%esp
0x0040134a <+6>:      sub     $0x20,%esp
0x0040134d <+9>:      call    0x401a20 <__main>

3      FILE* file = NULL;
0x00401352 <+14>:     movl    $0x0,0x1c(%esp)

4      file = fopen("values.txt", "r");
0x0040135a <+22>:     movl    $0x402030,0x4(%esp)
0x00401362 <+30>:     movl    $0x402032,(%esp)
0x00401369 <+37>:     call    0x401c90 <fopen>
0x0040136e <+42>:     mov     %eax,0x1c(%esp)

5
6      if (file) {
0x00401372 <+46>:     cmpl    $0x0,0x1c(%esp)
0x00401377 <+51>:     je      0x4013e4 <main+160>

7      int value1 = 0;
0x00401379 <+53>:     movl    $0x0,0x18(%esp)

8      int value2 = 0;
0x00401381 <+61>:     movl    $0x0,0x14(%esp)

9      fscanf(file, "%d", &value1);
0x00401389 <+69>:     lea     0x18(%esp),%eax
0x0040138d <+73>:     mov     %eax,0x8(%esp)
0x00401391 <+77>:     movl    $0x40203d,0x4(%esp)
0x00401399 <+85>:     mov     0x1c(%esp),%eax
0x0040139d <+89>:     mov     %eax,(%esp)
0x004013a0 <+92>:     call    0x401c98 <fscanf>

10     fscanf(file, "%d", &value2);
0x004013a5 <+97>:     lea     0x14(%esp),%eax
0x004013a9 <+101>:    mov     %eax,0x8(%esp)
0x004013ad <+105>:    movl    $0x40203d,0x4(%esp)
0x004013b5 <+113>:    mov     0x1c(%esp),%eax
0x004013b9 <+117>:    mov     %eax,(%esp)
0x004013bc <+120>:    call    0x401c98 <fscanf>

11
12     value1 = value1 + value2;
0x004013c1 <+125>:    mov     0x18(%esp),%edx
0x004013c5 <+129>:    mov     0x14(%esp),%eax
0x004013c9 <+133>:    lea     (%edx,%eax,1),%eax
0x004013cc <+136>:    mov     %eax,0x18(%esp)

13
14     printf("Result: %d", value1);
0x004013d0 <+140>:    mov     0x18(%esp),%eax
0x004013d4 <+144>:    mov     %eax,0x4(%esp)
0x004013d8 <+148>:    movl    $0x402040,(%esp)
0x004013df <+155>:    call    0x401ca0 <printf>

15     }
16     fclose(file);
0x004013e4 <+160>:    mov     0x1c(%esp),%eax
0x004013e8 <+164>:    mov     %eax,(%esp)
0x004013eb <+167>:    call    0x401ca8 <fclose>
0x004013f0 <+172>:    mov     $0x0,%eax

17     }
0x004013f5 <+177>:    leave
0x004013f6 <+178>:    ret

End of assembler dump.
```

Display of mixed mode of source code and resulting assembler instructions

Disassembling binary code (OllyDbg)

In case when only binary code is available (no source code), other approach is required. We will work with OllyDbg (www.ollydbg.de) program that is easy-to-use disassembler and debugger.

- Download OllyDbg 1.10 (freeware) either from <http://www.ollydbg.de/> or (better) from IS (OllyDbg.zip).
- Download tutorials I and II. by Lena from IS (tut1.rar and tut2.rar). Additional tutorials can be obtained from <http://www.tuts4you.com>.
- Download Assembler basics from IS (BasicsOfAssembler.pdf)

00401341	90	NOP	
00401342	90	NOP	
00401343	90	NOP	
00401344	55	PUSH EBP	
00401345	89E5	MOV EBP,ESP	
00401347	83E4 F0	AND ESP,FFFFFFF0	
0040134A	83EC 20	SUB ESP,20	
0040134D	E8 CE060000	CALL Test_C.00401A20	
00401352	C74424 1C 0001	MOV DWORD PTR SS:[ESP+1C],0	
0040135A	C74424 04 3021	MOV DWORD PTR SS:[ESP+4],Test_C.00402031	
00401362	C70424 32204001	MOV DWORD PTR SS:[ESP],Test_C.00402032	
00401369	E8 22090000	CALL <JMP.&msvort.fopen>	ASCII "values.txt"
0040136A	894424 1C 00	MOV DWORD PTR SS:[ESP+1C],EAX	fopen
00401372	837C24 1C 00	CMF DWORD PTR SS:[ESP+1C],0	
00401377	74 6B	JE SHORT Test_C.004013E4	
00401379	C74424 18 0001	MOV DWORD PTR SS:[ESP+18],0	
00401381	C74424 14 0001	MOV DWORD PTR SS:[ESP+14],0	
00401389	8D4424 18	LEA EAX,DWORD PTR SS:[ESP+18]	
0040138D	894424 08	MOV DWORD PTR SS:[ESP+8],EAX	
00401391	C74424 04 3021	MOV DWORD PTR SS:[ESP+4],Test_C.00402031	ASCII "%d"
00401399	8B4424 1C	MOV EAX,DWORD PTR SS:[ESP+1C]	
0040139D	890424	MOV DWORD PTR SS:[ESP],EAX	fscanf
004013A0	E8 F3080000	CALL <JMP.&msvort.fscanf>	
004013A5	8D4424 14	LEA EAX,DWORD PTR SS:[ESP+14]	
004013A9	894424 08	MOV DWORD PTR SS:[ESP+8],EAX	
004013AD	C74424 04 3021	MOV DWORD PTR SS:[ESP+4],Test_C.00402031	ASCII "%d"
004013B5	8B4424 1C	MOV EAX,DWORD PTR SS:[ESP+1C]	
004013B9	890424	MOV DWORD PTR SS:[ESP],EAX	fscanf
004013BC	E8 D7080000	CALL <JMP.&msvort.fscanf>	
004013C1	8B5424 18	MOV EDX,DWORD PTR SS:[ESP+18]	
004013C5	8B4424 14	MOV EAX,DWORD PTR SS:[ESP+14]	
004013C9	8D0402	LEA EAX,DWORD PTR DS:[EDX+EAX]	
004013CC	894424 18	MOV DWORD PTR SS:[ESP+18],EAX	
004013D0	8B4424 18	MOV EAX,DWORD PTR SS:[ESP+18]	
004013D4	894424 04	MOV DWORD PTR SS:[ESP+4],EAX	
004013D8	C70424 40204001	MOV DWORD PTR SS:[ESP],Test_C.00402040	ASCII "Result: %d"
004013DF	E8 BC080000	CALL <JMP.&msvort.printf>	printf
004013E4	8B4424 1C	MOV EAX,DWORD PTR SS:[ESP+1C]	
004013E9	890424	MOV DWORD PTR SS:[ESP],EAX	
004013EB	E8 B8080000	CALL <JMP.&msvort.fclose>	fclose
004013F0	B8 00000000	MOV EAX,0	
004013F5	C9	LEAVE	
004013F6	C3	RETN	
004013F7	90	NOP	
004013F8	00	DB 00	
004013F9	00	DB 00	
004013FA	00	DB 00	

Disassembled information provided by OllyDbg

OllyDbg shortcuts & most important commands

F3 ... Open binary file

F2 ... Toggle breakpoint (on opcodes, or double click)

F9 ... Run debugged program

Ctrl+F2 ... Restart program, all temporary changes are lost!

F8 ... Step over

F7 ... Step into

Spacebar or double click ... allows to set new opcode. Use when you like to change program behaviour, e.g., replacing conditional jump (JGE) by unconditional jump (JMP) or to discard instruction (NOP).

Alt+BkSp ... Undo change

Rightclick->Search for->All referenced text strings ... Constant text strings referenced in code. Use to find strings like hardcoded passwords, important messages ("Wrong license"). Double click on string will takes you to referencing instruction. Helps you to build mind model quickly.

Rightclick->Find references to->Address constant ... will find references to particular memory elsewhere in the code – use when you like to know where in code the memory is set, changed or otherwise used.

Ctrl+F1 ... Help on Win32 API (WIN32 API help file already prepared in OllyDbg directory (WIN32.HLP)). Use to get meaning of the parameters pushed to stack just before the API function is called.

; ... add or edit your comment for specific code line. Use to write down things you already understand. Use classic paper as well (program mind model)

Rightclick->Copy to executable->All modifications (or Selection) ... make changes permanent. New window with modified code is opened. **Rightclick->Save file** to write patched binary to disk.

Registers (FPU):

Z – zero flag, C – carry flag, S – sign flag. Invert bit flag by double click.

EIP ... next address to execute (instruction pointer)

EBX ... usually loop counter

Some hints

- Assembler is not as difficult as it may seem at first sight. You are not required to write your own program in assembler – you are usually only required to understand existing code, where only very limited set of assembler operations is used.
 - Using mixed mode in IDE debugger will quickly provide you an insight, how common programming constructions (assignments, conditional branching, cycles...) are transformed from source code into executable. Usually, you will get only 5-15 instructions per line of the source code, with MOV instruction being the most common.
 - Conditional branching is usually realized by two consecutive operations:
 - Comparison operation setting Flags register
 - Conditional jumping operation to address based on Flags (Branch 1)
 - If not jumped then Branch 2 code is directly present on the next instruction, or unconditional jump JMP to Branch 2 is present.
 - Comparison operation
 - CMP EAX, -1 - will set flag(s) in Registers, Zero and Sign flags are usually of interest. If two values are same (EAX == -1), Zero flag is set to 1.
 - TEST A, B (usually TEST EAX, EAX) – logical AND operation, results not saved, Flags are set. TEST EAX, EAX will test if value in EAX is equal to 0. If EAX == 0 then Zero flag == 1, 0 otherwise.
 - Jump operation
 - Unconditional JMP – jump every time
 - Conditional - based on the current value of flag(s)
- | | | |
|-------|-----------------------------------|-----------------------------------|
| JA* | Jump if (unsigned) above | - CF=0 and ZF=0 |
| JB* | Jump if (unsigned) below | - CF=1 |
| JE** | Jump if equal | - ZF=1 |
| JG* | Jump if (signed) greater | - ZF=0 and SF=OF (SF = Sign Flag) |
| JGE* | Jump if (signed) greater or equal | - SF=OF |
| JL* | Jump if (signed) less | - SF != OF (!= is not) |
| JLE* | Jump if (signed) less or equal | - ZF=1 and OF != OF |
| JMP** | Jump | - Jumps always |
| JNE** | Jump if not equal | - ZF=0 |

Disassembling binary code (IDAPro freeware)

Interactive Disassembler is legendary fullfledged disassembler with ability to disassemble many different platforms.

- Free version available for non-commercial uses
- <http://www.hex-rays.com/idapro/idadownfreeware.htm>
- Free version disassemble only Windows binaries
- Very nice visualization and debugger feature (similar as OllyDbg)
- Try it!

Decompiling binary code

Decompiler is able to produce source code from binary code. Decompiler needs to do disassembling first and then try to create code that will in turn produce binary code you have at the beginning.

- Resulting code will NOT contain information removed during compilation (comments, function names, formatting...)
- Read <http://www.debugmode.com/dcompile/> for more info
- Still can be of great help!
- Problem to find well working free disassembler :(
- http://en.wikibooks.org/wiki/X86_Disassembly/Disassemblers_and_Decompile

Other resources

RE on Wikipedia: http://en.wikipedia.org/wiki/Reverse_engineering

The Reverse Code Engineering Community: <http://www.reverse-engineering.net/>

Tutorials for You: <http://www.tuts4you.com>

Disassembling tutorial <http://www.codeproject.com/KB/cpp/reversedisasm.aspx>

Homework

The goal of this assignment is to reverse engineer supplied crack me file (LabakCrackMe.exe), obtain information about its behavior and make program to continue successfully without error message by a) patching, b) creating valid license info. More principally different solutions for the same problem will be awarded by extra points.

Hints:

- You may use OllyDbg or any other disassembler.
- Function *fread* fail by null exception if invalid file handle is supplied.

Submit:

- Short description of program behavior in text form or as **annotated C** source code (not only output of some disassembler) (source code version will be awarded by 1 extra point).
- Patched crack me binary that let the program run every time successfully with no error **without** valid license info.
- Valid license info that let program run successfully **without binary modification**.