

IB031 Úvod do strojového učení

Tomáš Brázdil

Course Info

Resources:

- ▶ Lectures & tutorials (the **main** source)
- ▶ Many books, few perfect for introductory level
One relatively good, especially the first part:
A. Géron. Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow: Concepts, Tools, and Techniques to Build Intelligent Systems. O'Reilly Media; 3rd edition, 2022
- ▶ (Almost) infinitely many online courses, tutorials, materials, etc.

Evaluation

The evaluation is composed of three parts:

- ▶ Mid-term exam: Written exam from the material of the first half of the semester.
- ▶ End-term exam: The "big" one containing everything from the semester (with possibly more stress in the second half).
- ▶ Projects: During tutorials, you will work on larger projects (in pairs or triples).

Each part contributes the following number of points:

- ▶ Mid-term exam: 25
- ▶ End-term exam: 50
- ▶ Project: 25

To pass, you need to obtain at least 60 points.

Distinguishing Properties of the Course

- ▶ Introductory, prerequisites are held to a minimum
- ▶ Formal and precise: Be prepared for a complete and “mathematical” description of presented methods.

Distinguishing Properties of the Course

- ▶ Introductory, prerequisites are held to a minimum
- ▶ Formal and precise: Be prepared for a complete and “mathematical” description of presented methods.

I assume that you have basic knowledge of

- ▶ Elementary mathematical notation (operations on sets, logic, etc.)
- ▶ Linear algebra: Vectors in \mathbb{R}^n , operations on vectors (including the dot product). Geometric interpretation!
- ▶ Calculus: Functions of multiple real variables, partial derivatives, basic differential calculus.
- ▶ Probability: Notion of probability distribution, random variables/vectors, expectation.

What Is Machine Learning?

Machine learning is the science (and art) of programming computers so they can **learn from data**.

What Is Machine Learning?

Machine learning is the science (and art) of programming computers so they can **learn from data**.

Here is a slightly more general definition:

Arthur Samuel, 1959

Machine learning is the field of study that allows computers to learn without being explicitly programmed.

What Is Machine Learning?

Machine learning is the science (and art) of programming computers so they can **learn from data**.

Here is a slightly more general definition:

Arthur Samuel, 1959

Machine learning is the field of study that allows computers to learn without being explicitly programmed.

And a more engineering-oriented one:

Tom Mitchell, 1997

A computer program is said to learn from experience E concerning some task T and some performance measure P if its performance on T , as measured by P , improves with experience E .

Example

In the context of spam filtering:

- ▶ The task T is to flag spam in new emails.
- ▶ The experience E is represented by a set of emails labeled either spam or ham by hand (the training data).
- ▶ The performance measure P could be the accuracy, which is the ratio of the number of correctly classified emails and all emails.

There are many more performance measures; we will study the basic ones later.

Example

In the context of spam filtering:

- ▶ The task T is to flag spam in new emails.
- ▶ The experience E is represented by a set of emails labeled either spam or ham by hand (the training data).
- ▶ The performance measure P could be the accuracy, which is the ratio of the number of correctly classified emails and all emails.

There are many more performance measures; we will study the basic ones later.

In the context of housing price prediction:

- ▶ The task T is to predict prices of new houses based on their basic parameters (size, number of bathrooms, etc.)
- ▶ The experience E is represented by information about existing houses.
- ▶ The performance measure P could be, e.g., an absolute difference between the predicted and the real price.

Examples (cont.)

In the context of game playing:

- ▶ The task T is to play chess.
- ▶ The experience E is represented by a series of self-plays where the computer plays against itself.
- ▶ The performance measure P is winning/losing the game.

Here, the trick is to spread the delayed and limited feedback about the result of the game throughout the individual decisions in the game.

Examples (cont.)

In the context of game playing:

- ▶ The task T is to play chess.
- ▶ The experience E is represented by a series of self-plays where the computer plays against itself.
- ▶ The performance measure P is winning/losing the game.
Here, the trick is to spread the delayed and limited feedback about the result of the game throughout the individual decisions in the game.


In the context of customer behavior:

- ▶ The task T is to group customers with similar shopping habits in an e-shop.
- ▶ The experience E consists of lists of items individual customers bought in the shop.
- ▶ The performance measure P ?
Measure how "nicely" the customers are grouped.
(whether people with similar habits, as seen by humans, fall into the same group).

Comparison of Programming and Learning

How to code the spam filter?


- ▶ Examine what spam mails typically contain: Specific words ("Viagra"), sender's address, etc.
- ▶ Write down a rule-based system that detects specific features.
- ▶ Test the program on new emails and (most probably) go back to look for more spam features.



Comparison of Programming and Learning

The machine learning way:


- ▶ Study the problem and collect lots of emails, labeling them spam or ham.
- ▶ Train a machine learning model that reads an email and decides whether it's spam or ham.
- ▶ Test the model and (most probably) go back to collect more data and adjust the model.



ML Solutions are Adaptive

Spam filter: Authors of spam might and will adapt to your spam filter (possibly change the wording to pass through).


ML systems can be adjusted to new situations by retraining on new data (unless the data becomes ugly).



ML for Human Understanding

Spam filter: A trained system can be inspected for notorious spam features.

Some models allow direct inspection, such as decision trees or linear/logistic regression models.



Usage of Machine Learning

Machine learning suits various applications, especially where traditional methods fall short. Here are some areas where it excels:

- ▶ Solving complex problems where fine-tuning and rule-based solutions are inadequate.
- ▶ Tackling complex issues that resist traditional problem-solving approaches.
- ▶ Adapting to fluctuating environments through retraining on new data.
- ▶ Gaining insights from large and complex datasets.


In summary, machine learning offers innovative solutions and adaptability for today's complex and ever-changing problems, (sometimes) providing insights beyond the reach of traditional approaches.

Types of Learning

There are main categories based on information available during the training:


- ▶ Supervised learning
- ▶ Unsupervised learning
- ▶ Semi-supervised learning
- ▶ Self-supervised learning
- ▶ Reinforcement learning

Supervised Learning



Labels are available for all input data.

Supervised Learning





Labels are available for all input data.

Typical supervised learning tasks are



- ▶ *Classification* where the aim is to classify inputs into (typically few) classes
(e.g., the spam filter where the classes are spam/ham)
- ▶ *Regression* where a numerical value is output for a given input
(e.g., housing prices)

Unsupervised Learning



No labels are available for input data.

Unsupervised Learning




No labels are available for input data.

Typical unsupervised learning tasks are


- ▶ *Clustering* where inputs are grouped according to their features
(e.g., clients of a bank grouped according to their age, wealth, etc.)
- ▶ *Association* where interesting relations and rules are discovered among the features of inputs
(e.g., market basket mining where associations between various types of goods are being learned from the behavior of customers)
- ▶ *Dimensionality reduction* reduce high-dimensional data to few dimensions (e.g., images to few image features)

Semi-Supervised Learning



Labels for some data.

Semi-Supervised Learning



Labels for some data.

For example, Medical data, where elaborate diagnosis is available only for some patients.

Combines supervised and unsupervised learning: e.g., clusters all data and labels the unlabeled inputs with the most common labels in their clusters.

Self-Supervised Learning




Generate labels from (unlabeled) inputs.


The goal is to learn typical features of the data.

It can be later modified to generate images, classify, etc.


Reinforcement Learning



- 1 Observe
- 2 Select action using policy



- 3 Action!
- 4 Get reward or penalty



- 5 Update policy (learning step)
- 6 Iterate until an optimal policy is found

Learn from performing *actions* and getting feedback from *environment*.

ML Applications Highlights

- ▶ ChatGPT (and similar generative models)
 - ▶ The basis forms a generative language model, i.e., a text-generating model trained on texts in a self-supervised way
 - ▶ Recently extended to multimodal versions (text, image, sound)

ML Applications Highlights

- ▶ ChatGPT (and similar generative models)
 - ▶ The basis forms a generative language model, i.e., a text-generating model trained on texts in a self-supervised way
 - ▶ Recently extended to multimodal versions (text, image, sound)
- ▶ Machine translation, image captioning
 - ▶ Google translate, etc.
 - ▶ Typically (semi)-supervised learning,

ML Applications Highlights

- ▶ ChatGPT (and similar generative models)
 - ▶ The basis forms a generative language model, i.e., a text-generating model trained on texts in a self-supervised way
 - ▶ Recently extended to multimodal versions (text, image, sound)
- ▶ Machine translation, image captioning
 - ▶ Google translate, etc.
 - ▶ Typically (semi)-supervised learning,
- ▶ Various image recognition and processing tasks
 - ▶ In medicine, such systems are slowly making their way into hospitals as assistance tools
 - ▶ Automotive, quality control, advertising, etc., etc., etc.

ML Applications Highlights

- ▶ ChatGPT (and similar generative models)
 - ▶ The basis forms a generative language model, i.e., a text-generating model trained on texts in a self-supervised way
 - ▶ Recently extended to multimodal versions (text, image, sound)
- ▶ Machine translation, image captioning
 - ▶ Google translate, etc.
 - ▶ Typically (semi)-supervised learning,
- ▶ Various image recognition and processing tasks
 - ▶ In medicine, such systems are slowly making their way into hospitals as assistance tools
 - ▶ Automotive, quality control, advertising, etc., etc., etc.
- ▶ Science
 - ▶ Chemistry & biology: E.g., prediction of features of chemical compounds (Alpha-fold)


ML Applications Highlights

- ▶ ChatGPT (and similar generative models)
 - ▶ The basis forms a generative language model, i.e., a text-generating model trained on texts in a self-supervised way
 - ▶ Recently extended to multimodal versions (text, image, sound)
- ▶ Machine translation, image captioning
 - ▶ Google translate, etc.
 - ▶ Typically (semi)-supervised learning,
- ▶ Various image recognition and processing tasks
 - ▶ In medicine, such systems are slowly making their way into hospitals as assistance tools
 - ▶ Automotive, quality control, advertising, etc., etc., etc.
- ▶ Science
 - ▶ Chemistry & biology: E.g., prediction of features of chemical compounds (Alpha-fold)
- ▶ Various "table" data processing in finance, management, etc.
 - ▶ Often straightforward methods (linear/logistic regression)
 - ▶ Essential but not fancy

ML Applications Highlights

- ▶ ChatGPT (and similar generative models)
 - ▶ The basis forms a generative language model, i.e., a text-generating model trained on texts in a self-supervised way
 - ▶ Recently extended to multimodal versions (text, image, sound)
- ▶ Machine translation, image captioning
 - ▶ Google translate, etc.
 - ▶ Typically (semi)-supervised learning,
- ▶ Various image recognition and processing tasks
 - ▶ In medicine, such systems are slowly making their way into hospitals as assistance tools
 - ▶ Automotive, quality control, advertising, etc., etc., etc.
- ▶ Science
 - ▶ Chemistry & biology: E.g., prediction of features of chemical compounds (Alpha-fold)
- ▶ Various "table" data processing in finance, management, etc.
 - ▶ Often straightforward methods (linear/logistic regression)
 - ▶ Essential but not fancy
- ▶ Game playing: More fancy than useful, learning models beating humans in several difficult games.

ML in Context




Supervised Learning

Example - Fruit Recognition


The goal: Create an automatic system for fruit recognition, concretely apple, lemon, and mandarin.

Inputs: Measures of *height* and *width* of each fruit.

Suppose we have a dataset of dimensions of several fruits labeled with the correct class.



Data




	height	width	fruit
0	3.91	5.76	Mandarin
1	7.09	7.69	Apple
2	10.48	7.32	Lemon
3	9.21	7.20	Lemon
4	7.95	5.90	Lemon
5	7.62	7.51	Apple
6	7.95	5.32	Mandarin
7	4.69	6.19	Mandarin
8	7.50	5.99	Lemon
9	7.11	7.02	Apple
10	4.15	5.60	Mandarin
11	7.29	8.38	Apple
12	8.49	6.52	Lemon
13	7.44	7.89	Apple
14	7.86	7.60	Apple
15	3.93	6.12	Apple
16	4.40	5.90	Mandarin
17	5.50	4.50	Lemon
18	8.10	6.15	Lemon
19	8.69	5.82	Lemon

Use similarity to solve the problem.

KNN Classification

Given a new fruit.
What is it?

Find five closest
examples



Where is the machine learning?


KNN Classification

Given a new fruit.
What is it?

Find five closest
examples

Among the five closest:

- ▶ $M = 4$ mandarins
- ▶ $A = 1$ apples
- ▶ $L = 0$ lemons



Where is the machine learning?

KNN Classification


Given a new fruit.
What is it?

Find five closest
examples

Among the five closest:

- ▶ $M = 4$ mandarins
- ▶ $A = 1$ apples
- ▶ $L = 0$ lemons


It is a **mandarin!**




Where is the machine learning?

Learning in Fruit Classification with KNN

Learning:



Inference:



Fruit Classification Algorithm

Input: A fruit F with dimensions *height*, *width*

Output: *mandarin*, *lemon*, *apple*


- 1: Find K examples $\{E_1, \dots, E_K\}$ in the dataset whose dimensions are closest to the dimensions of the fruit F
- 2: Count the number of examples of each class in $\{E_1, \dots, E_K\}$
 - M mandarins in $\{E_1, \dots, E_K\}$
 - L lemons in $\{E_1, \dots, E_K\}$
 - A apples in $\{E_1, \dots, E_K\}$
- 3: **if** $M \geq L$ and $M \geq A$ **then return** *mandarin*
- 4: **else if** $L \geq A$ **then return** *lemon*
- 5: **else return** *apple*
- 6: **end if**

Does it work?

Testing the Model for Fruit Classification

Consider a test set of new instances ($K = 5$, d is Euclidean):

height	width	fruit
4.0	6.5	Mandarin
4.47	7.13	Mandarin
6.49	7.0	Apple
7.51	5.01	Lemon
8.34	4.23	Lemon



Perfect classification of new data! Just deploy and sell!!

K Nearest Neighbors


... on ideal data

Learning and Inference

Two crucial components of machine learning are the following:

Learning:

Creating model



Inference:

Using model



Training Data

Assume table training data, i.e., of the form

$$\begin{array}{cccc|c} x_{11} & x_{12} & \cdots & x_{1n} & C_1 \\ x_{21} & x_{22} & \cdots & x_{2n} & C_2 \\ \vdots & \vdots & \ddots & \vdots & \vdots \\ x_{p1} & x_{p2} & \cdots & x_{pn} & C_p \end{array}$$

height	width	fruit
4.0	6.5	Mandarin
4.47	7.13	Mandarin
6.49	7.0	Apple
7.51	5.01	Lemon
8.34	4.23	Lemon

Formally, we define **training dataset**

$$\mathcal{T} = \{(\vec{x}_k, c_k) \mid k = 1, \dots, p\}$$

Here each $\vec{x}_k \in \mathbb{R}^n$ is an input vector and $c_k \in C$ is the correct class.

$$\mathcal{T} = \{(4.0, 6.5), M), \\ (4.47, 7.13), M), \\ (6.49, 7.0), A), \\ \dots\}$$

KNN: Learning

Consider the training set:

$$\mathcal{T} = \{(\vec{x}_k, c_k) \mid k = 1, \dots, p\}$$

and *memorize it* exactly as it is.

Store in a table.

Possibly use a clever representation allowing fast computation of nearest neighbors such as KDTrees (out of the scope of this lecture).

Also,

- ▶ determine the number of neighbors $K \in \mathbb{N}$,
- ▶ and the distance measure d .

Inference in KNN

Assume a KNN "trained" by memorizing

$\mathcal{T} = \{(\vec{x}_k, c_k) \in \mathbb{R}^n \times C \mid k = 1, \dots, p\}$, a constant $K \in \mathbb{N}$ and a distance measure d .

For d , consider Euclidean distance, but different norms may also be used to define different distance measures.

Inference in KNN

Assume a KNN "trained" by memorizing

$\mathcal{T} = \{(\vec{x}_k, c_k) \in \mathbb{R}^n \times \mathcal{C} \mid k = 1, \dots, p\}$, a constant $K \in \mathbb{N}$ and a distance measure d .

For d , consider Euclidean distance, but different norms may also be used to define different distance measures.

Input: A vector $\vec{z} = (z_1, \dots, z_n) \in \mathbb{R}^n$

Output: A class from \mathcal{C}

- 1: Find K indices of examples $X = \{i_1, \dots, i_K\} \subseteq \{1, \dots, p\}$ with minimum distance to \vec{z} , i.e., satisfying

$$\max\{d(\vec{z}, \vec{x}_\ell) \mid \ell \in X\} \leq \min\{d(\vec{z}, \vec{x}_\ell) \mid \ell \in \{1, \dots, p\} \setminus X\}$$

- 2: For every $c \in \mathcal{C}$ count the number $\#c$ of elements ℓ in X such that $c_\ell = c$
- 3: Return some

$$c_{max} \in \arg \max_{c \in \mathcal{C}} \#c$$

A class $c_{max} \in \mathcal{C}$ which maximizes $\#c$.

The resulting model

What exactly constitutes the model? The *model* consists of


- ▶ The *trained parameters*: In this case the memorized training data.
- ▶ The *hyperparameters* set “from the outside”: In this case, the number of neighbors K and the distance measure d .

The resulting model

What exactly constitutes the model? The *model* consists of

- ▶ The *trained parameters*: In this case the memorized training data.
- ▶ The *hyperparameters* set “from the outside”: In this case, the number of neighbors K and the distance measure d .

Note that different settings of K lead to different classifiers (for the same d):



In Practice

... to get an efficient solution:

In Practice

... to get an efficient solution:

- ▶ Deal with issues in the data
 - ▶ Data almost always comes in weird formats, with inconsistencies, missing values, wrong values, etc.
 - ▶ Data rarely have the ideal form for a given learning model.

We need to ingest, validate, and preprocess the data.

In Practice

... to get an efficient solution:

- ▶ Deal with issues in the data

- ▶ Data almost always comes in weird formats, with inconsistencies, missing values, wrong values, etc.
- ▶ Data rarely have the ideal form for a given learning model.

We need to ingest, validate, and preprocess the data.

- ▶ Deal with issues in the model

- ▶ In KNN, the training memorizes the example, but at least the K can be tuned.

We need to tune the model.

In Practice

... to get an efficient solution:

- ▶ Deal with issues in the data
 - ▶ Data almost always comes in weird formats, with inconsistencies, missing values, wrong values, etc.
 - ▶ Data rarely have the ideal form for a given learning model.

We need to ingest, validate, and preprocess the data.

- ▶ Deal with issues in the model
 - ▶ In KNN, the training memorizes the example, but at least the K can be tuned.

We need to tune the model.

- ▶ Deal with the wrong model by testing and validation in as realistic conditions as possible.

In Practice

... to get an efficient solution:

- ▶ Deal with issues in the data
 - ▶ Data almost always comes in weird formats, with inconsistencies, missing values, wrong values, etc.
 - ▶ Data rarely have the ideal form for a given learning model.

We need to ingest, validate, and preprocess the data.

- ▶ Deal with issues in the model
 - ▶ In KNN, the training memorizes the example, but at least the K can be tuned.

We need to tune the model.

- ▶ Deal with the wrong model by testing and validation in as realistic conditions as possible.
- ▶ Deal with deployment - real-world application issues involving, e.g., implementation in embedded devices with limited resources.

Models Considered in This Course

Throughout this course, we will meet the following models:

- ▶ KNN (already did)
- ▶ Decision trees
- ▶ (Naive) Bayes classifier
- ▶ Clustering: K-means and hierarchical
- ▶ Linear and logistic regression
- ▶ Support Vector Machines (SVM)
- ▶ Kernel linear models
- ▶ Neural networks (light intro to feed-forward networks)
- ▶ Ensemble methods + random forests
- ▶ (maybe some reinforcement learning)


Models Considered in This Course

Throughout this course, we will meet the following models:

- ▶ KNN (already did)
- ▶ Decision trees
- ▶ (Naive) Bayes classifier
- ▶ Clustering: K-means and hierarchical
- ▶ Linear and logistic regression
- ▶ Support Vector Machines (SVM)
- ▶ Kernel linear models
- ▶ Neural networks (light intro to feed-forward networks)
- ▶ Ensemble methods + random forests
- ▶ (maybe some reinforcement learning)

... but first, let us see the whole machine-learning pipeline.

Machine Learning Pipeline



Fetch Data

Always start with

Fetch Data

Always start with

- ▶ The problem formulation & understanding.

For example, diagnosis of diabetes from medical records. What info is (possibly) sufficient for such a diagnosis?

Fetch Data

Always start with

- ▶ The problem formulation & understanding.

For example, diagnosis of diabetes from medical records. What info is (possibly) sufficient for such a diagnosis?

- ▶ Find data sources.

In our example, the sources are hospitals. It would be best to persuade them to give you the data and sign a contract.

Fetch Data

Always start with

- ▶ The problem formulation & understanding.

For example, diagnosis of diabetes from medical records. What info is (possibly) sufficient for such a diagnosis?

- ▶ Find data sources.

In our example, the sources are hospitals. It would be best to persuade them to give you the data and sign a contract.

- ▶ Collect the data.

In our example, the data is possibly small (just tables with results of tests). But for other diagnoses, you may include huge amounts of data from MRI, CT, etc. Then, the collection itself might be a serious technical problem.

Fetch Data

Always start with

- ▶ The problem formulation & understanding.

For example, diagnosis of diabetes from medical records. What info is (possibly) sufficient for such a diagnosis?

- ▶ Find data sources.

In our example, the sources are hospitals. It would be best to persuade them to give you the data and sign a contract.

- ▶ Collect the data.

In our example, the data is possibly small (just tables with results of tests). But for other diagnoses, you may include huge amounts of data from MRI, CT, etc. Then, the collection itself might be a serious technical problem.

- ▶ Integrate data from various sources.

A serious diagnostic system must be trained/tested on data from many hospitals. You must blend the data from various sources (different formats, etc.).

Fetch Data

For simple “toy” machine learning projects, you may fetch prepared datasets from various databases on the internet.

Fetch Data

For simple “toy” machine learning projects, you may fetch prepared datasets from various databases on the internet.

The data should be stored in an identified location and versioned. You will probably keep adding data and training models on the ever-changing datasets. You have to be able to keep track of the changes and map training data to particular models.

Tools such as ML Flow or Weights & Biases might be helpful.

Fetch Data

For simple “toy” machine learning projects, you may fetch prepared datasets from various databases on the internet.

The data should be stored in an identified location and versioned. You will probably keep adding data and training models on the ever-changing datasets. You have to be able to keep track of the changes and map training data to particular models.

Tools such as ML Flow or Weights & Biases might be helpful.

Data Separation

At this point, you should randomize the ordering of the data and select a test set to be used in model evaluation!

The test data are supposed to simulate the actual conditions, i.e., they should be “unseen”.

Fetch Data

For simple “toy” machine learning projects, you may fetch prepared datasets from various databases on the internet.

The data should be stored in an identified location and versioned. You will probably keep adding data and training models on the ever-changing datasets. You have to be able to keep track of the changes and map training data to particular models.

Tools such as ML Flow or Weights & Biases might be helpful.

Data Separation

At this point, you should randomize the ordering of the data and select a test set to be used in model evaluation!

The test data are supposed to simulate the actual conditions, i.e., they should be “unseen”.

Data Exploration

Compute basic statistics to identify missing values, outliers, etc.

Clean Data

The cleaning usually comprises the following steps:

- ▶ Fix or remove incorrect or corrupted values.
- ▶ Identify outliers and decide what to do with them.
Outliers may harm some training methods and are not “representative”. However, sometimes, they naturally belong to the dataset, and expert insight is needed.
- ▶ Fix formatting.
For example, the Date may be expressed in many ways, and a simple Yes/No answer.
- ▶ Resolve missing values (by either removing the whole examples or imputing)
Many methods have been developed for missing values imputation. It is a susceptible issue because new values may strongly bias the model.
- ▶ Remove duplicates.

The above steps often affect the training and need expertise in the application domain.

Later in this course, we will discuss techniques for data cleaning.

ID	Age	Income	Gender	Customer_Satisfaction
1	38	46641.356413713	nan	Unsatisfied
2	42	49129.0615585107	female	Neutral
3	18	119965.049731014	Male	nan
4	18	66828.0762224329	nan	very unsatisfied
5	58	57422.2721106762	female	very unsatisfied
6	28	59502.8174855665	Other	Satisfied
7	18	42659.6675768587	Other	Neutral
8	18	54019.1173206374	Other	Satisfied
9	40	25429.1604541137	female	Unsatisfied
10	21	15595.5862129548	Other	Satisfied
11	18	58094.2328460069	Other	very unsatisfied
12	18	39097.3278583155	female	Very Satisfied
13	30		Other	Satisfied
14	50	30617.3914472273	Female	Very Satisfied
15	18		nan	Neutral
16	34	39902.4430953214	male	nan
17	49	68381.6997683133	Female	Very Satisfied
18	33	44796.0962271524	Other	Very Satisfied
19	47	39218.9560738814	Female	very unsatisfied
20		14544.9226784447	Other	Satisfied

Prepare Data

Unlike cleaning, which is application-dependent, data preparation/transformation is model-dependent. This usually subsumes:

- ▶ **Scaling:** Settings values of inputs to a similar range.

Some models, especially those utilizing distance, are sensitive to large differences between input sizes.

- ▶ **Encoding:** Encode non-numeric data using real-valued vectors.

Many models, especially those based on geometry, work only with numeric data. Non-numeric data such as Yes/No, Short/Medium/Long must be encoded appropriately.

- ▶ **Binning or Discretization** Convert continuous features into discrete bins to capture patterns in ranges.

Comment: Sometimes **Normalization**, that is changing the distribution of inputs to resemble the normal distribution, is mentioned. However, this step is typically not essential for machine learning itself. However, it is important to use statistical inference to test the significance of learned parameters.

Prepare Data

- ▶ **Feature selection** Throw out input features that are too “similar” to other features.

For example, if the temperature is measured both in Celsius and in Kelvin, keep one of them. The relationship can, of course, be a more complex (non-linear) correlation.

Prepare Data

- ▶ **Feature selection** Throw out input features that are too “similar” to other features.

For example, if the temperature is measured both in Celsius and in Kelvin, keep one of them. The relationship can, of course, be a more complex (non-linear) correlation.

- ▶ **Dimensionality reduction** Transforming data from \mathbb{R}^n to \mathbb{R}^m where $m \ll n$.

Growing dimension means growing difficulty of training for all models. Some models cease to work for high-dimensional data. The reduction typically searches for a few important characteristic features of inputs.

Prepare Data

- ▶ **Feature selection** Throw out input features that are too “similar” to other features.

For example, if the temperature is measured both in Celsius and in Kelvin, keep one of them. The relationship can, of course, be a more complex (non-linear) correlation.

- ▶ **Dimensionality reduction** Transforming data from \mathbb{R}^n to \mathbb{R}^m where $m \ll n$.

Growing dimension means growing difficulty of training for all models. Some models cease to work for high-dimensional data. The reduction typically searches for a few important characteristic features of inputs.

- ▶ **Feature aggregation** Introducing new features using operations on the original ones.

We will see kernel transformations later in this course, allowing simple models to solve complex problems.

Train Model


Now the dataset has been cleaned; we may train a model.

Train Model

Now the dataset has been cleaned; we may train a model.

Before training, we should split the dataset into

- ▶ *training* dataset on which the model will learn
- ▶ *validation* dataset on which we fine-tune hyperparameters



The resulting model is obtained after several iterations of the above process.

Evaluate Model

Here, we use the test set that we separated during data fetching.

In some cases, a brand new test set can be generated.

patients are examined regularly, creating new records continuously.

In some cases, it is tough to obtain new data.

For example, new expensive and difficult measurements are needed to obtain new data.

Evaluate Model

Here, we use the test set that we separated during data fetching.

In some cases, a brand new test set can be generated.

patients are examined regularly, creating new records continuously.

In some cases, it is tough to obtain new data.

For example, new expensive and difficult measurements are needed to obtain new data.

Critical issue: Make sure that you are truly testing
exactly the whole inference process.

Often, just a model is tested, and the testing and production inference engines are separated. This leads to truly nasty errors in the production!

We will discuss various generic metrics helpful in measuring the quality of the resulting model.

Deploy to Production

Deployment of machine learning models is a complex question, application dependent.

The recently emerging area of MLOps is concerned with the engineering side of the model deployment.

Deploy to Production

Deployment of machine learning models is a complex question, application dependent.

The recently emerging area of MLOps is concerned with the engineering side of the model deployment.

From the technical point of view, the typical issues solved by ML Ops teams are

- ▶ how to extract/process data in real-time
- ▶ how much storage is required
- ▶ how to store/collect model (and data) artifacts/predictions
- ▶ how to set up APIs, tools, and software environments
- ▶ What the period of predictions (instantaneous or batch predictions) should be
- ▶ how to set up hardware requirements (or cloud requirements for on-cloud environments) by the computational resources required
- ▶ how to set up a pipeline for continuous training and parameter tuning

Deploy to Production

From the user's point of view:

- ▶ How to get a sensible and valuable user output?
 - ▶ AI researchers will be satisfied with tons of running text in terminals.
 - ▶ “Normal” people need a graphical interface with understandable output.
 - ▶ Experts working in other domains typically demand speed and clarity at the extreme.

Deploy to Production

From the user's point of view:

- ▶ How to get a sensible and valuable user output?
 - ▶ AI researchers will be satisfied with tons of running text in terminals.
 - ▶ “Normal” people need a graphical interface with understandable output.
 - ▶ Experts working in other domains typically demand speed and clarity at the extreme.
- ▶ How do you persuade users that the AI is working for them?
 - ▶ Especially if safety is at stake, you need to have outstanding arguments and explanations ready for end-users.
 - ▶ In many areas, the devices need to be certified (medicine, automotive) for ML-based systems.

This complex subject will be only touched on in this course.

Monitor, collect Data

Deployed machine learning models must be constantly monitored.

Because of the influx of new data, ML models work in highly dynamic environments.

For example, an image-processing medical diagnostic model suddenly misdiagnosed a patient because a nurse marked the sample with a marker pen.

Every customer has a different infrastructure and may produce data slightly differently.

Data for retraining and improvement should be stored.

Also, many areas allow the *active learning* where users provide feedback for (continuous) retraining of the models.

Data

Data Science Example

You receive data from a medical researcher concerning a project that you are eager to work on.

Data Science Example

You receive data from a medical researcher concerning a project that you are eager to work on.

The data consists of a 1000 lines table with five columns:

012	232	33.5	0	10.7
020	121	16.9	2	210.1
027	165	24.0	0	427.6
		...		

The aim is to predict the last field given the others.

Data Science Example

You receive data from a medical researcher concerning a project that you are eager to work on.

The data consists of a 1000 lines table with five columns:

012	232	33.5	0	10.7
020	121	16.9	2	210.1
027	165	24.0	0	427.6
		...		

The aim is to predict the last field given the others.

The medical researcher does not elaborate further on the data, but they seem to be pretty easy to work with, right?

Data Science Example

You receive data from a medical researcher concerning a project that you are eager to work on.

The data consists of a 1000 lines table with five columns:

012	232	33.5	0	10.7
020	121	16.9	2	210.1
027	165	24.0	0	427.6
		...		

The aim is to predict the last field given the others.

The medical researcher does not elaborate further on the data, but they seem to be pretty easy to work with, right?

After a few days, you have trained a model that predicts numbers resembling the ones in the table.

You contact the medical researcher and discuss the results.

Model Discussion

Researcher: So, you got the data for all the patients?

Model Discussion

Researcher: So, you got the data for all the patients?

Data Miner: Yes. I haven't had much time for analysis, but I do have a few interesting results.

Model Discussion

Researcher: So, you got the data for all the patients?

Data Miner: Yes. I haven't had much time for analysis, but I do have a few interesting results.

Researcher: Amazing. There were so many data issues with this set of patients that I couldn't do much.

Model Discussion

Researcher: So, you got the data for all the patients?

Data Miner: Yes. I haven't had much time for analysis, but I do have a few interesting results.

Researcher: Amazing. There were so many data issues with this set of patients that I couldn't do much.

Data Miner: Oh? I didn't hear about any possible problems.

Model Discussion

Researcher: So, you got the data for all the patients?

Data Miner: Yes. I haven't had much time for analysis, but I do have a few interesting results.

Researcher: Amazing. There were so many data issues with this set of patients that I couldn't do much.

Data Miner: Oh? I didn't hear about any possible problems.

Researcher: Well, first, there is field 5, the variable we want to predict. It's common knowledge among people who analyze this type of data that results are better if you work with the log of the values, but I didn't discover this until later. Was it mentioned to you?

Model Discussion

Researcher: So, you got the data for all the patients?

Data Miner: Yes. I haven't had much time for analysis, but I do have a few interesting results.

Researcher: Amazing. There were so many data issues with this set of patients that I couldn't do much.

Data Miner: Oh? I didn't hear about any possible problems.

Researcher: Well, first, there is field 5, the variable we want to predict. It's common knowledge among people who analyze this type of data that results are better if you work with the log of the values, but I didn't discover this until later. Was it mentioned to you?

Data Miner: No.

Model Dicsuccion

Researcher: But surely you heard about what happened to field 4? It's supposed to be measured on a scale from 1 to 10, with 0 indicating a missing value, but because of a data entry error, all 10's were changed into 0's. Unfortunately, since some of the patients have missing values for this field, it's impossible to say whether a 0 in this field is a real 0 or a 10. Quite a few of the records have that problem.

Model Dicsuccion

Researcher: But surely you heard about what happened to field 4? It's supposed to be measured on a scale from 1 to 10, with 0 indicating a missing value, but because of a data entry error, all 10's were changed into 0's. Unfortunately, since some of the patients have missing values for this field, it's impossible to say whether a 0 in this field is a real 0 or a 10. Quite a few of the records have that problem.

Data Miner: Interesting. Were there any other problems?

Model Dicsuccion

Researcher: But surely you heard about what happened to field 4? It's supposed to be measured on a scale from 1 to 10, with 0 indicating a missing value, but because of a data entry error, all 10's were changed into 0's. Unfortunately, since some of the patients have missing values for this field, it's impossible to say whether a 0 in this field is a real 0 or a 10. Quite a few of the records have that problem.

Data Miner: Interesting. Were there any other problems?

Researcher: Yes, fields 2 and 3 are basically the same, but I assume that you probably noticed that.

Model Dicsuccion

Researcher: But surely you heard about what happened to field 4? It's supposed to be measured on a scale from 1 to 10, with 0 indicating a missing value, but because of a data entry error, all 10's were changed into 0's. Unfortunately, since some of the patients have missing values for this field, it's impossible to say whether a 0 in this field is a real 0 or a 10. Quite a few of the records have that problem.

Data Miner: Interesting. Were there any other problems?

Researcher: Yes, fields 2 and 3 are basically the same, but I assume that you probably noticed that.

Data Miner: Yes, but these fields were only weak predictors of field 5.

Model Discussion

Researcher: Anyway, given all those problems, I'm surprised you were able to accomplish anything.

Data Miner: True, but my results are really quite good. Field 1 is a very strong predictor of field 5. I'm surprised that this wasn't noticed before.

Researcher: What? Field 1 is just an identification number.

Data Miner: Nonetheless, my results speak for themselves.

Researcher: Oh, no! I just remembered. We assigned ID numbers after we sorted the records based on field 5. There is a strong connection, but it isn't very sensible. Sorry.

Model Discussion

Researcher: Anyway, given all those problems, I'm surprised you were able to accomplish anything.

Data Miner: True, but my results are really quite good. Field 1 is a very strong predictor of field 5. I'm surprised that this wasn't noticed before.

Researcher: What? Field 1 is just an identification number.

Data Miner: Nonetheless, my results speak for themselves.

Researcher: Oh, no! I just remembered. We assigned ID numbers after we sorted the records based on field 5. There is a strong connection, but it isn't very sensible. Sorry.

OK, what's the point?

You have to

Understand the task you want to solve and the data!

Data Objects

Data objects represent entities we work with (e.g., classify them).

For example, in cancer prediction, the data objects are patients. In fruit classification, the data objects are individual fruits.

Data Objects

Data objects represent entities we work with (e.g., classify them).

For example, in cancer prediction, the data objects are patients. In fruit classification, the data objects are individual fruits.

Data objects are described by *attributes* (or *features* or *variables*).

For example, the age, weight, genetic profile, and other patient characteristics. Or the width and height of a fruit.

Attributes vs Features vs Variables

The name differs from field to field.

Attributes vs Features vs Variables

The name differs from field to field.

So, the following names are usually used as synonyms:

- ▶ *Attributes* - used mostly by database and data mining experts.
- ▶ *Features* - used mostly by machine learning experts.
- ▶ *Variables* - used mostly by statisticians.

Attributes vs Features vs Variables

The name differs from field to field.

So, the following names are usually used as synonyms:

- ▶ *Attributes* - used mostly by database and data mining experts.
- ▶ *Features* - used mostly by machine learning experts.
- ▶ *Variables* - used mostly by statisticians.

One may make some distinctions

- ▶ *Attributes* represent information about the object without any additional assumptions.
- ▶ *Features* assume that their values are somewhat characteristic of the object.
- ▶ *Variables* assume that there is some process behind them (typically a random process in the case of statistics).

Data Types - Categorical Attributes

Categorical attributes (nominal attributes) are symbols or names of things.

- ▶ Each value represents some kind of category, code, or state.
- ▶ Values are not ordered and should not be used quantitatively (in computer science, the values are known as enumerations).

Data Types - Categorical Attributes

Categorical attributes (nominal attributes) are symbols or names of things.

- ▶ Each value represents some kind of category, code, or state.
- ▶ Values are not ordered and should not be used quantitatively (in computer science, the values are known as enumerations).
- ▶ **Examples:**

$\text{hair_color} \in \{\text{black, brown, blond, red, auburn, gray, white}\}$

$\text{marital_status} \in \{\text{single, married, divorced, widowed}\}$

$\text{customer_ID} \in \{0, 1, 2, \dots\}$

Even though the last one is usually expressed using numbers, it should not be used quantitatively.

Data Types - Categorical Attributes

Categorical attributes (nominal attributes) are symbols or names of things.

- ▶ Each value represents some kind of category, code, or state.
- ▶ Values are not ordered and should not be used quantitatively (in computer science, the values are known as enumerations).
- ▶ **Examples:**

hair_color \in {black, brown, blond, red, auburn, gray, white}

marital_status \in {single, married, divorced, widowed}

customer_ID \in {0, 1, 2, ...}

Even though the last one is usually expressed using numbers, it should not be used quantitatively.

Binary attributes are categorical attributes with only two values.

DataTypes - Ordinal Attributes

Ordinal attribute is an attribute with values that have a meaningful order or ranking among them.

DataTypes - Ordinal Attributes

Ordinal attribute is an attribute with values that have a meaningful order or ranking among them.

Examples:

$\text{drink_size} \in \{\text{small, medium, large}\}$

$\text{grades} \in \{\text{A, B, C, D, E, F}\}$

It can also be obtained by discretizing numeric quantities into series of intervals.

Ordinal attributes do not allow arithmetic operations.

DataTypes - Ordinal Attributes

Ordinal attribute is an attribute with values that have a meaningful order or ranking among them.

Examples:

$\text{drink_size} \in \{\text{small, medium, large}\}$

$\text{grades} \in \{\text{A, B, C, D, E, F}\}$

It can also be obtained by discretizing numeric quantities into series of intervals.

Ordinal attributes do not allow arithmetic operations.

Categorical and ordinal attributes are called *qualitative* attributes.

Next, we look at numeric, i.e., *quantitative* attributes.

Data Types - Numeric Attributes

Numeric attributes are quantities represented by numbers.

Data Types - Numeric Attributes

Numeric attributes are quantities represented by numbers.

Distinguish two types: *Interval-scale* and *ratio-scale*.

	INTERVAL SCALE	RATIO SCALE
Measurement interval	Equal intervals between consecutive points.	Equal intervals with the presence of a true zero.
Absolute zero	Lacks a true zero point.	Possesses a true zero point.
Statistical analysis	Limited to addition and subtraction	Allows for meaningful multiplication and division.
Meaningful ratios	Ratios are not meaningful due to the lack of zero.	Ratios are meaningful due to the presence of zero.
Examples	Celsius temperature (20 degrees not twice as hot as 10 degrees)	Height, duration, etc. (20 meters is twice as large as 10 meters)

Discrete vs Continuous Attributes

Often, two kinds of numeric attributes are distinguished:

Discrete vs Continuous Attributes

Often, two kinds of numeric attributes are distinguished:

- ▶ *Discrete*

A finite or countably infinite range of values, i.e., integers may represent the values.

Some (but not all) authors count the qualitative (categorical, ordinal) attributes among the discrete attributes.

Discrete vs Continuous Attributes

Often, two kinds of numeric attributes are distinguished:

- ▶ *Discrete*

A finite or countably infinite range of values, i.e., integers may represent the values.

Some (but not all) authors count the qualitative (categorical, ordinal) attributes among the discrete attributes.

- ▶ *Continuous*

A continuous range of values, an interval.

There are several more or less formal definitions of continuous attributes in the literature. For example:

- ▶ All non-discrete variables.
- ▶ Have an infinite number of values between any two values.
- ▶ Their values are measured (??).

Deeper characteristics of data (statistical properties, etc.) will be examined at tutorials.

Decision Trees


Decision Trees

- ▶ One of the widely used methods for machine learning.
- ▶ Intuitively simple, directly explainable.
- ▶ Basis for random forests (a powerful model).


Decision Trees

- ▶ One of the widely used methods for machine learning.
- ▶ Intuitively simple, directly explainable.
- ▶ Basis for random forests (a powerful model).
- ▶ We will consider the ID3 algorithm.
Quinlan, 1979
- ▶ Various adjustments that appear in C4.5, CART, etc.

Consider the weather forecast for tennis playing. How would you decide whether to play today?



Consider the weather forecast for tennis playing. How would you decide whether to play today?



How do we obtain such a tree based on experience/data?

Learning Decision Trees

Consider data represented as follows:

- ▶ A finite set of *attributes* $\mathcal{A} = \{A_1, \dots, A_n\}$.
- ▶ Each attribute $A \in \mathcal{A}$ has its *set of values* $V(A)$.

We start with trees on discrete datasets, that is, assume $V(A)$ finite for all $A \in \mathcal{A}$.

Learning Decision Trees

Consider data represented as follows:

- ▶ A finite set of *attributes* $\mathcal{A} = \{A_1, \dots, A_n\}$.
- ▶ Each attribute $A \in \mathcal{A}$ has its *set of values* $V(A)$.

We start with trees on discrete datasets, that is, assume $V(A)$ finite for all $A \in \mathcal{A}$.

Objects to be classified are described by vectors of values of all attributes:

$$\vec{x} = (x_1, \dots, x_n) \in V(A_1) \times \dots \times V(A_n)$$

Given \vec{x} and an attribute A_k we denote by $A_k(\vec{x})$ the value x_k of the attribute A_k in \vec{x} .

Learning Decision Trees

Consider data represented as follows:

- ▶ A finite set of *attributes* $\mathcal{A} = \{A_1, \dots, A_n\}$.
- ▶ Each attribute $A \in \mathcal{A}$ has its *set of values* $V(A)$.

We start with trees on discrete datasets, that is, assume $V(A)$ finite for all $A \in \mathcal{A}$.

Objects to be classified are described by vectors of values of all attributes:

$$\vec{x} = (x_1, \dots, x_n) \in V(A_1) \times \dots \times V(A_n)$$

Given \vec{x} and an attribute A_k we denote by $A_k(\vec{x})$ the value x_k of the attribute A_k in \vec{x} .

Consider a set C of *classes*.

We consider a multiclass classification in general, i.e., C is an arbitrary finite set.

Example

The tennis problem:

- ▶ The attributes are:

$$A_1 = \textit{Outlook}, A_2 = \textit{Temperature}, A_3 = \textit{Humidity}, A_4 = \textit{Wind}$$

Example

The tennis problem:

- ▶ The attributes are:

$A_1 = \textit{Outlook}$, $A_2 = \textit{Temperature}$, $A_3 = \textit{Humidity}$, $A_4 = \textit{Wind}$

- ▶ The sets of values of the attributes:

- ▶ $V(A_1) = \{\textit{Sunny}, \textit{Overcast}, \textit{Rain}\}$

- ▶ $V(A_2) = \{\textit{Hot}, \textit{Mild}, \textit{Cool}\}$

- ▶ $V(A_3) = \{\textit{High}, \textit{Normal}\}$

- ▶ $V(A_4) = \{\textit{Strong}, \textit{Weak}\}$

Example

The tennis problem:

- ▶ The attributes are:

$$A_1 = \textit{Outlook}, A_2 = \textit{Temperature}, A_3 = \textit{Humidity}, A_4 = \textit{Wind}$$

- ▶ The sets of values of the attributes:

- ▶ $V(A_1) = \{\textit{Sunny}, \textit{Overcast}, \textit{Rain}\}$

- ▶ $V(A_2) = \{\textit{Hot}, \textit{Mild}, \textit{Cool}\}$

- ▶ $V(A_3) = \{\textit{High}, \textit{Normal}\}$

- ▶ $V(A_4) = \{\textit{Strong}, \textit{Weak}\}$

- ▶ Consider

$$\vec{x} = (\textit{Overcast}, \textit{Hot}, \textit{Normal}, \textit{Weak})$$

$$\in V(A_1) \times V(A_2) \times V(A_3) \times V(A_4)$$

Example

The tennis problem:

- ▶ The attributes are:

$$A_1 = \textit{Outlook}, A_2 = \textit{Temperature}, A_3 = \textit{Humidity}, A_4 = \textit{Wind}$$

- ▶ The sets of values of the attributes:

- ▶ $V(A_1) = \{\textit{Sunny}, \textit{Overcast}, \textit{Rain}\}$

- ▶ $V(A_2) = \{\textit{Hot}, \textit{Mild}, \textit{Cool}\}$

- ▶ $V(A_3) = \{\textit{High}, \textit{Normal}\}$

- ▶ $V(A_4) = \{\textit{Strong}, \textit{Weak}\}$

- ▶ Consider

$$\vec{x} = (\textit{Overcast}, \textit{Hot}, \textit{Normal}, \textit{Weak})$$

$$\in V(A_1) \times V(A_2) \times V(A_3) \times V(A_4)$$

Then

$$A_3(\vec{x}) = \textit{Humidity}(\vec{x}) = \textit{Normal}$$

$$A_4(\vec{x}) = \textit{Wind}(\vec{x}) = \textit{Weak}$$

Example

The tennis problem:

- ▶ The attributes are:

$$A_1 = \textit{Outlook}, A_2 = \textit{Temperature}, A_3 = \textit{Humidity}, A_4 = \textit{Wind}$$

- ▶ The sets of values of the attributes:

- ▶ $V(A_1) = \{\textit{Sunny}, \textit{Overcast}, \textit{Rain}\}$

- ▶ $V(A_2) = \{\textit{Hot}, \textit{Mild}, \textit{Cool}\}$

- ▶ $V(A_3) = \{\textit{High}, \textit{Normal}\}$

- ▶ $V(A_4) = \{\textit{Strong}, \textit{Weak}\}$

- ▶ Consider

$$\vec{x} = (\textit{Overcast}, \textit{Hot}, \textit{Normal}, \textit{Weak})$$

$$\in V(A_1) \times V(A_2) \times V(A_3) \times V(A_4)$$

Then

$$A_3(\vec{x}) = \textit{Humidity}(\vec{x}) = \textit{Normal}$$

$$A_4(\vec{x}) = \textit{Wind}(\vec{x}) = \textit{Weak}$$

- ▶ $C = \{\textit{Yes}, \textit{No}\}$

Decision Trees

Consider (directed, rooted) *trees* $\mathcal{T} = (T, E)$ where T is a set of nodes and $E \subseteq T \times T$ is a set of directed edges.

Decision Trees

Consider (directed, rooted) *trees* $\mathcal{T} = (T, E)$ where T is a set of nodes and $E \subseteq T \times T$ is a set of directed edges.

Denote by $T_{leaf} \subseteq T$ the set of all *leaves* of the tree and by T_{int} the set $T \setminus T_{leaf}$ of *internal nodes*.

Decision Trees

Consider (directed, rooted) *trees* $\mathcal{T} = (T, E)$ where T is a set of nodes and $E \subseteq T \times T$ is a set of directed edges.

Denote by $T_{leaf} \subseteq T$ the set of all *leaves* of the tree and by T_{int} the set $T \setminus T_{leaf}$ of *internal nodes*.

A *decision tree* is

- ▶ a tree $\mathcal{T} = (T, E)$ where
- ▶ each leaf $\tau \in T_{leaf}$ is assigned a class $C(\tau) \in C$,
- ▶ each internal node $\tau \in T_{int}$ is assigned an attribute $A(\tau) \in \mathcal{A}$,
- ▶ and there is a bijection between edges from τ and values of the attribute $A(\tau)$. Given an edge $(\tau, \tau') \in E$ we write $V(\tau, \tau')$ to denote the value of the attribute $A(\tau)$ assigned to the edge.

Decision Trees

Consider (directed, rooted) *trees* $\mathcal{T} = (T, E)$ where T is a set of nodes and $E \subseteq T \times T$ is a set of directed edges.

Denote by $T_{leaf} \subseteq T$ the set of all *leaves* of the tree and by T_{int} the set $T \setminus T_{leaf}$ of *internal nodes*.

A *decision tree* is

- ▶ a tree $\mathcal{T} = (T, E)$ where
- ▶ each leaf $\tau \in T_{leaf}$ is assigned a class $C(\tau) \in C$,
- ▶ each internal node $\tau \in T_{int}$ is assigned an attribute $A(\tau) \in \mathcal{A}$,
- ▶ and there is a bijection between edges from τ and values of the attribute $A(\tau)$. Given an edge $(\tau, \tau') \in E$ we write $V(\tau, \tau')$ to denote the value of the attribute $A(\tau)$ assigned to the edge.

Inference: Given an input \vec{x} , we traverse the tree from the root to a leaf, always choosing edges labeled with values of attributes from \vec{x} . The output is the class labeling the leaf.

Example

$$T = \{O, H, W, z_1, z_2, z_3, z_4, z_5\}$$

$$T_{leaf} = \{z_1, z_2, z_3, z_4, z_5\}, T_{int} = \{O, H, W\}$$

$$E = \{(O, H), (O, W), (H, z_1), (H, z_2), \\ (O, z_3), (W, z_4), (W, z_5)\}$$

$$C(z_1) = C(z_3) = \text{No}, C(z_2) = C(z_4) = \text{Yes}$$


$$A(O) = \text{Outlook}, A(H) = \text{Humidity}, A(W) = \text{Wind}$$

$$V(O, H) = \text{Sunny}, V(O, z_3) = \text{Overcast}, V(O, W) = \text{Rain}$$

$$V(H, z_1) = \text{High}, V(H, z_2) = \text{Normal}$$

$$V(W, z_4) = \text{Strong}, V(W, z_5) = \text{Weak}$$

Inference: For (*Rain, Hot, High, Strong*) we reach z_4 , yielding *No*.



Training Dataset

Consider a *training dataset*

$$\mathcal{D} = \{(\vec{x}_k, c_k) \mid k = 1, \dots, p\}$$

Here $\vec{x}_k \in V(A_1) \times \dots \times V(A_k)$ and $c_k \in C$ for every k .

Technically \mathcal{D} can be a multiset containing several occurrences of the same vector.

Index	Outlook	Temperature	Humidity	Wind	PlayTennis
1	Sunny	Hot	High	Weak	No
2	Sunny	Hot	High	Strong	No
3	Overcast	Hot	High	Weak	Yes
4	Rain	Mild	High	Weak	Yes
5	Rain	Cool	Normal	Weak	Yes
6	Rain	Cool	Normal	Strong	No
7	Overcast	Cool	Normal	Strong	Yes
8	Sunny	Mild	High	Weak	No
9	Sunny	Cool	Normal	Weak	Yes
10	Rain	Mild	Normal	Weak	Yes
11	Sunny	Mild	Normal	Strong	Yes
12	Overcast	Mild	High	Strong	Yes
13	Overcast	Hot	Normal	Weak	Yes
14	Rain	Mild	High	Strong	No

$$\begin{aligned}
\mathcal{D} = \{ & ((\text{Sunny}, \text{Hot}, \text{High}, \text{Weak}), \text{No}), \\
& ((\text{Sunny}, \text{Hot}, \text{High}, \text{Strong}), \text{No}) \\
& \dots \\
& ((\text{Rain}, \text{Mild}, \text{High}, \text{Strong}), \text{No}) \}
\end{aligned}$$

Learning Decision Trees

The learning algorithm ID3 works as follows:

- ▶ Start with the whole training dataset \mathcal{D} .

Learning Decision Trees

The learning algorithm ID3 works as follows:

- ▶ Start with the whole training dataset \mathcal{D} .
- ▶ If there is just a single class in \mathcal{D} , create a single node decision tree that returns the class.

Learning Decision Trees

The learning algorithm ID3 works as follows:

- ▶ Start with the whole training dataset \mathcal{D} .
- ▶ If there is just a single class in \mathcal{D} , create a single node decision tree that returns the class.
- ▶ Otherwise, identify an attribute $A \in \mathcal{A}$ which *best classifies* the examples in \mathcal{D} . For every $v \in V(A)$ we obtain

$$\mathcal{D}_v = \{\vec{x} \mid \vec{x} \in \mathcal{D}, A(\vec{x}) = v\}$$

We aim to have each \mathcal{D}_v as pure as possible, that is, ideally, to contain examples of just a single class.

Learning Decision Trees

The learning algorithm ID3 works as follows:

- ▶ Start with the whole training dataset \mathcal{D} .
- ▶ If there is just a single class in \mathcal{D} , create a single node decision tree that returns the class.
- ▶ Otherwise, identify an attribute $A \in \mathcal{A}$ which *best classifies* the examples in \mathcal{D} . For every $v \in V(A)$ we obtain

$$\mathcal{D}_v = \{\vec{x} \mid \vec{x} \in \mathcal{D}, A(\vec{x}) = v\}$$

We aim to have each \mathcal{D}_v as pure as possible, that is, ideally, to contain examples of just a single class.

- ▶ Finally,
 - ▶ create a root node τ of a decision tree,

Learning Decision Trees

The learning algorithm ID3 works as follows:

- ▶ Start with the whole training dataset \mathcal{D} .
- ▶ If there is just a single class in \mathcal{D} , create a single node decision tree that returns the class.
- ▶ Otherwise, identify an attribute $A \in \mathcal{A}$ which *best classifies* the examples in \mathcal{D} . For every $v \in V(A)$ we obtain

$$\mathcal{D}_v = \{\vec{x} \mid \vec{x} \in \mathcal{D}, A(\vec{x}) = v\}$$

We aim to have each \mathcal{D}_v as pure as possible, that is, ideally, to contain examples of just a single class.

- ▶ Finally,
 - ▶ create a root node τ of a decision tree,
 - ▶ assign the attribute A to τ ,

Learning Decision Trees

The learning algorithm ID3 works as follows:

- ▶ Start with the whole training dataset \mathcal{D} .
- ▶ If there is just a single class in \mathcal{D} , create a single node decision tree that returns the class.
- ▶ Otherwise, identify an attribute $A \in \mathcal{A}$ which *best classifies* the examples in \mathcal{D} . For every $v \in V(A)$ we obtain

$$\mathcal{D}_v = \{\vec{x} \mid \vec{x} \in \mathcal{D}, A(\vec{x}) = v\}$$

We aim to have each \mathcal{D}_v as pure as possible, that is, ideally, to contain examples of just a single class.

- ▶ Finally,
 - ▶ create a root node τ of a decision tree,
 - ▶ assign the attribute A to τ ,
 - ▶ for every $v \in V(A)$, recursively construct a decision tree with a root τ_v using \mathcal{D}_v ,

Learning Decision Trees

The learning algorithm ID3 works as follows:

- ▶ Start with the whole training dataset \mathcal{D} .
- ▶ If there is just a single class in \mathcal{D} , create a single node decision tree that returns the class.
- ▶ Otherwise, identify an attribute $A \in \mathcal{A}$ which *best classifies* the examples in \mathcal{D} . For every $v \in V(A)$ we obtain

$$\mathcal{D}_v = \{\vec{x} \mid \vec{x} \in \mathcal{D}, A(\vec{x}) = v\}$$

We aim to have each \mathcal{D}_v as pure as possible, that is, ideally, to contain examples of just a single class.

- ▶ Finally,
 - ▶ create a root node τ of a decision tree,
 - ▶ assign the attribute A to τ ,
 - ▶ for every $v \in V(A)$, recursively construct a decision tree with a root τ_v using \mathcal{D}_v ,
 - ▶ for every $v \in V(A)$ introduce an edge (τ, τ_v) assigned v .

```

1: function ID3(dataset  $\mathcal{D}$ , attribute set  $\mathcal{A}$ )
2:   Create a root node  $\tau$  for the tree
3:   if  $\mathcal{D} = \emptyset$  then
4:     Return the single node  $\tau$  assigned with a default class.
5:   else if all examples in  $\mathcal{D}$  are of the same class  $c$  then
6:     Return the single-node tree, where  $\tau$  is assigned  $c$ 
7:   else if set of attributes  $\mathcal{A}$  is empty then
8:     Return the single-node tree where  $\tau$  is assigned
       the most common class in  $\mathcal{D}$ 
9:   else
10:    Choose attribute  $A \in \mathcal{A}$  best classifying examples in  $\mathcal{D}$ .
11:    Set the decision attribute for  $\tau$  to  $A$ 
12:    for each value  $v \in D(A)$  do
13:      Compute a decision tree  $\text{ID3}(\mathcal{D}_v, \mathcal{A} \setminus \{A\})$  with root  $\tau_v$ ,
14:      add a new edge  $(\tau, \tau_v)$  assigned  $v$ .
15:    end for
16:  end if
17: return  $\tau$ 
18: end function

```

Best Classifying Attribute

We aim to choose an attribute that best informs us about the class.
As a result, we would possibly use as few attributes as possible and obtain a small tree containing only class-relevant decisions.

How to choose an attribute that best classifies examples in \mathcal{D} ?

There are several measures used in practice.

The most common are

- ▶ *information gain*
- ▶ *Gini impurity decrease*

Information Gain

The information gain is based on the notion of entropy.

Information Gain

The information gain is based on the notion of entropy.

We need some notation:

- ▶ Given a training dataset \mathcal{D} and a class $c \in C$ we denote by p_c the proportion of examples with class c in \mathcal{D} .

Information Gain

The information gain is based on the notion of entropy.

We need some notation:

- ▶ Given a training dataset \mathcal{D} and a class $c \in \mathcal{C}$ we denote by p_c the proportion of examples with class c in \mathcal{D} .
- ▶ We define the *entropy* of \mathcal{D} by

$$Entropy(\mathcal{D}) = \sum_{c \in \mathcal{C}} -p_c \log_2 p_c$$

Information Gain

The information gain is based on the notion of entropy.

We need some notation:

- ▶ Given a training dataset \mathcal{D} and a class $c \in \mathcal{C}$ we denote by p_c the proportion of examples with class c in \mathcal{D} .
- ▶ We define the *entropy* of \mathcal{D} by

$$\text{Entropy}(\mathcal{D}) = \sum_{c \in \mathcal{C}} -p_c \log_2 p_c$$

- ▶ The *information gain* of an attribute A is then defined by


$$\text{Gain}(\mathcal{D}, A) = \text{Entropy}(\mathcal{D}) - \sum_{v \in \mathcal{V}(A)} \frac{|\mathcal{D}_v|}{|\mathcal{D}|} \text{Entropy}(\mathcal{D}_v)$$

In every step of the ID3 algorithm, we choose an attribute *maximizing* the information gain for the current dataset \mathcal{D} .

Information Gain

The intuition behind information gain:


- ▶ Consider $C = \{0, 1\}$ and p the proportion of examples of class 1. p measures the “uncertainty” of the class:



Information Gain

The intuition behind information gain:

- ▶ Consider $C = \{0, 1\}$ and p the proportion of examples of class 1. p measures the “uncertainty” of the class:




- ▶ $\sum_{v \in V(A)} \frac{|\mathcal{D}_v|}{|\mathcal{D}|} Entropy(\mathcal{D}_v)$ is weighted uncertainty of classes in each \mathcal{D}_v (weighted by the relative size of \mathcal{D}_v).

Information Gain

The intuition behind information gain:

- ▶ Consider $C = \{0, 1\}$ and p the proportion of examples of class 1. p measures the “uncertainty” of the class:



- ▶ $\sum_{v \in V(A)} \frac{|\mathcal{D}_v|}{|\mathcal{D}|} Entropy(\mathcal{D}_v)$ is weighted uncertainty of classes in each \mathcal{D}_v (weighted by the relative size of \mathcal{D}_v).
- ▶ $Gain(\mathcal{D}, A)$ measures reduction in uncertainty of classes by splitting \mathcal{D} according to A .

Gini Impurity

- ▶ We define *Gini impurity* of \mathcal{D} by

$$Gini(\mathcal{D}) = 1 - \sum_{c \in C} p_c^2$$

Gini Impurity

- ▶ We define *Gini impurity* of \mathcal{D} by

$$Gini(\mathcal{D}) = 1 - \sum_{c \in C} p_c^2$$

- ▶ The *impurity decrease* of an attribute A is then defined similarly to the gain in the entropy case

$$ImpDec(\mathcal{D}, A) = Gini(\mathcal{D}) - \sum_{v \in V(A)} \frac{|\mathcal{D}_v|}{|\mathcal{D}|} Gini(\mathcal{D}_v)$$

In every step of the ID3 algorithm, we choose an attribute *maximizing* the impurity decrease for the current dataset \mathcal{D} .

Gini Impurity

What is the intuition behind $Gini(\mathcal{D})$?

Gini Impurity

What is the intuition behind $Gini(\mathcal{D})$?

Assume we randomly independently choose objects from \mathcal{D} .

$1 - \sum_{c \in C} p_c^2$ is the probability of choosing two objects of different classes in two consecutive independent trials.

Indeed, p_c is the probability of choosing an object of class c , p_c^2 the probability of choosing objects of the class c twice, and $\sum_{c \in C} p_c^2$ the probability of choosing two objects of the same class.

In what follows (and at the exam), we will work only with the Gini impurity as it is easier to compute.

Example

Consider our tennis example (see the table).

- ▶ Consider the whole dataset \mathcal{D} .
 - ▶ $p_{Yes} = 9/14$
 - ▶ $p_{No} = 5/14$
 - ▶ $Gini(\mathcal{D}) = 1 - (9/14)^2 - (5/14)^2 = 0.45918$

Example

Consider our tennis example (see the table).

- ▶ Consider the whole dataset \mathcal{D} .
 - ▶ $p_{Yes} = 9/14$
 - ▶ $p_{No} = 5/14$
 - ▶ $Gini(\mathcal{D}) = 1 - (9/14)^2 - (5/14)^2 = 0.45918$
- ▶ For $A = Outlook$ we get
 - ▶ $Gini(\mathcal{D}_{Sunny}) = 1 - (2/5)^2 - (3/5)^2 = 0.48$
 - ▶ $Gini(\mathcal{D}_{Overcast}) = 1 - 1^2 - 0^2 = 0$
 - ▶ $Gini(\mathcal{D}_{Rain}) = 1 - (3/5)^2 - (2/5)^2 = 0.48$

Example

Consider our tennis example (see the table).

- ▶ Consider the whole dataset \mathcal{D} .
 - ▶ $p_{Yes} = 9/14$
 - ▶ $p_{No} = 5/14$
 - ▶ $Gini(\mathcal{D}) = 1 - (9/14)^2 - (5/14)^2 = 0.45918$
- ▶ For $A = Outlook$ we get
 - ▶ $Gini(\mathcal{D}_{Sunny}) = 1 - (2/5)^2 - (3/5)^2 = 0.48$
 - ▶ $Gini(\mathcal{D}_{Overcast}) = 1 - 1^2 - 0^2 = 0$
 - ▶ $Gini(\mathcal{D}_{Rain}) = 1 - (3/5)^2 - (2/5)^2 = 0.48$

Thus

$$\begin{aligned} ImpDec(\mathcal{D}, Outlook) &= \\ & 0.459 - (5/14) \cdot 0.48 - (4/14) \cdot 0 - (5/14) \cdot 0.48 \\ & = 0.117 \end{aligned}$$

- ▶ $ImpDec(\mathcal{D}, Temperature) = 0.018$
- ▶ $ImpDec(\mathcal{D}, Humidity) = 0.091$
- ▶ $ImpDec(\mathcal{D}, Wind) = 0.030$

So the largest information gain is given by the *Outlook*.

Example

Going further on, consider $\mathcal{D} = \mathcal{D}_{Sunny}$. We get

- ▶ $ImpDec(\mathcal{D}, Temperature) = 0.279$
- ▶ $ImpDec(\mathcal{D}, Humidity) = 0.48$
- ▶ $ImpDec(\mathcal{D}, Wind) = 0.013$

The best choice attribute after *Sunny* in *Outlook* is *Humidity*.

Example

Going further on, consider $\mathcal{D} = \mathcal{D}_{Sunny}$. We get

- ▶ $ImpDec(\mathcal{D}, Temperature) = 0.279$
- ▶ $ImpDec(\mathcal{D}, Humidity) = 0.48$
- ▶ $ImpDec(\mathcal{D}, Wind) = 0.013$

The best choice attribute after *Sunny* in *Outlook* is *Humidity*.

Now consider $\mathcal{D} = \mathcal{D}_{Rain}$.

- ▶ $ImpDec(\mathcal{D}, Temperature) = 0.013$
- ▶ $ImpDec(\mathcal{D}, Humidity) = 0.013$
- ▶ $ImpDec(\mathcal{D}, Wind) = 0.48$

The best choice attribute after *Rain* in *Outlook* is *Wind*.

Continuous-Valued Attributes

What if values of an attribute A come from a continuous variable?

A is a numerical attribute that can take any value in an interval, such as temperature, size, time, etc.

Continuous-Valued Attributes

What if values of an attribute A come from a continuous variable?

A is a numerical attribute that can take any value in an interval, such as temperature, size, time, etc.


Consider an internal node $\tau \in T_{int}$ assigned such a continuous attribute A . Then

- ▶ τ is assigned a threshold value called a *cut point* $H \in \mathbb{R}$,
- ▶ there are two edges e_{true}, e_{false} from τ ,
- ▶ e_{true} labeled with True and e_{false} labeled with False.

During inference, when considering an example \vec{x} in the node τ ,

- ▶ evaluate $A(\vec{x}) \leq H$,
- ▶ if $A(\vec{x}) \leq H$, then follow e_{true} ,
- ▶ else follow e_{false} .

Temperature ≤ 15



In training, the cut point is chosen from the attribute values in the training set using information gain/impurity decrease similar to discrete attributes.

Iris Example

iris setosa



petal

sepal

iris versicolor



petal

sepal

iris virginica



petal

sepal

Attributes

Sepal.Length, Sepal.Width, Petal.Length, Petal.Width

Classes (Variety)


Setosa, Versicolor, Virginica

Iris Example


The dataset (150 examples):

Sepal.Length	Sepal.Width	Petal.Length	Petal.Width	Variety
5.5	3.5	1.3	0.2	Setosa
6.8	2.8	4.8	1.4	Versicolor
6.7	3.1	4.7	1.5	Versicolor
6.9	3.1	5.1	2.3	Virginica
7.3	2.9	6.3	1.8	Virginica
5.4	3.7	1.5	0.2	Setosa
4.6	3.4	1.4	0.3	Setosa
6.2	2.8	4.8	1.8	Virginica
5.4	3.0	4.5	1.5	Versicolor
4.7	3.2	1.6	0.2	Setosa
6.7	3.3	5.7	2.1	Virginica
5.0	3.4	1.5	0.2	Setosa
5.0	3.0	1.6	0.2	Setosa
4.4	2.9	1.4	0.2	Setosa
6.0	3.4	4.5	1.6	Versicolor
5.1	3.5	1.4	0.2	Setosa
6.6	3.0	4.4	1.4	Versicolor
5.9	3.2	4.8	1.8	Versicolor
5.6	2.8	4.9	2.0	Virginica
...				

Iris Example - Decision Tree



Iris Example - Decision Tree Boudaries



If the leaves are split further, the Depth = 2 boundary would be added.

Attribute Importance Computation

How important are attributes for the trained tree \mathcal{T} ? Depends on

- ▶ how close they are to the root of \mathcal{T} ,
- ▶ how large information gain/decrease in impurity they give.

There are several formulae for computing the importance.

Attribute Importance Computation

How important are attributes for the trained tree \mathcal{T} ? Depends on

- ▶ how close they are to the root of \mathcal{T} ,
- ▶ how large information gain/decrease in impurity they give.

There are several formulae for computing the importance.

One example is *mean decrease impurity* defined as follows:

Consider a decision tree T trained on a dataset \mathcal{D} using the ID3.

Attribute Importance Computation

How important are attributes for the trained tree \mathcal{T} ? Depends on

- ▶ how close they are to the root of \mathcal{T} ,
- ▶ how large information gain/decrease in impurity they give.

There are several formulae for computing the importance.

One example is *mean decrease impurity* defined as follows:

Consider a decision tree T trained on a dataset \mathcal{D} using the ID3.

For every node τ of \mathcal{T} , denote by $\mathcal{D}[\tau]$ the subset of \mathcal{D} which was used in the ID3 procedure when the node τ was created (line 2).

Attribute Importance Computation

How important are attributes for the trained tree \mathcal{T} ? Depends on

- ▶ how close they are to the root of \mathcal{T} ,
- ▶ how large information gain/decrease in impurity they give.

There are several formulae for computing the importance.

One example is *mean decrease impurity* defined as follows:

Consider a decision tree T trained on a dataset \mathcal{D} using the ID3.

For every node τ of \mathcal{T} , denote by $\mathcal{D}[\tau]$ the subset of \mathcal{D} which was used in the ID3 procedure when the node τ was created (line 2).

Consider an attribute A and denote by $T[A] \subseteq T_{int}$ the set of all nodes of \mathcal{T} assigned the attribute A by ID3 (line 11).

Attribute Importance Computation

How important are attributes for the trained tree \mathcal{T} ? Depends on

- ▶ how close they are to the root of \mathcal{T} ,
- ▶ how large information gain/decrease in impurity they give.

There are several formulae for computing the importance.

One example is *mean decrease impurity* defined as follows:

Consider a decision tree T trained on a dataset \mathcal{D} using the ID3.

For every node τ of \mathcal{T} , denote by $\mathcal{D}[\tau]$ the subset of \mathcal{D} which was used in the ID3 procedure when the node τ was created (line 2).

Consider an attribute A and denote by $T[A] \subseteq T_{int}$ the set of all nodes of \mathcal{T} assigned the attribute A by ID3 (line 11).

Then define the importance as the average decrease in Gini impurity (i.e., average *ImpDec*) in the nodes of $T[A]$:

$$GiniImportance(A) = \sum_{\tau \in T[A]} \frac{|\mathcal{D}[\tau]|}{|\mathcal{D}|} ImpDec(\mathcal{D}[\tau], A)$$

Decision Trees

Practical Issues

Practical Issues

- ▶ Data preprocessing
- ▶ Model tuning (overfitting and underfitting)
- ▶ Sensitivity to changes in data/hyperparameters
- ▶ Learning representation problems (the XOR)

Data Preprocessing

Little preprocessing is needed for decision trees.

Data Preprocessing

Little preprocessing is needed for decision trees.

Of course, ideally, clean up the data, but

- ▶ Missing values are not such a big issue
(considering a concrete example, exclude the attributes with missing values)

Data Preprocessing

Little preprocessing is needed for decision trees.

Of course, ideally, clean up the data, but

- ▶ Missing values are not such a big issue (considering a concrete example, exclude the attributes with missing values)
- ▶ Outliers are not such a big issue either; the division of nodes is done based on relative counts, not concrete values.

Data Preprocessing

Little preprocessing is needed for decision trees.

Of course, ideally, clean up the data, but

- ▶ Missing values are not such a big issue (considering a concrete example, exclude the attributes with missing values)
- ▶ Outliers are not such a big issue either; the division of nodes is done based on relative counts, not concrete values.
- ▶ Decision trees can cope with continuous and categorical values directly (i.e., no encoding necessary)

Data Preprocessing

Little preprocessing is needed for decision trees.

Of course, ideally, clean up the data, but

- ▶ Missing values are not such a big issue (considering a concrete example, exclude the attributes with missing values)
- ▶ Outliers are not such a big issue either; the division of nodes is done based on relative counts, not concrete values.
- ▶ Decision trees can cope with continuous and categorical values directly (i.e., no encoding necessary)

Imbalanced classes might cause problems because of small information gain/impurity decrease in splitting.

Imbalanced Classes

Consider a dataset \mathcal{D} where

- ▶ there are two classes, $C = \{0, 1\}$,
- ▶ 10^6 examples have the class 1,
- ▶ 100 examples have the class 0.

Imbalanced Classes

Consider a dataset \mathcal{D} where

- ▶ there are two classes, $C = \{0, 1\}$,
- ▶ 10^6 examples have the class 1,
- ▶ 100 examples have the class 0.

Then

- ▶ $p_1 = 10^6 / (10^6 + 100) \approx 1$ and $p_0 = 100 / 10^6 \approx 0$,
- ▶ thus the Gini impurity $1 - p_1^2 - p_0^2 \approx 0$.

Imbalanced Classes

Consider a dataset \mathcal{D} where

- ▶ there are two classes, $C = \{0, 1\}$,
- ▶ 10^6 examples have the class 1,
- ▶ 100 examples have the class 0.

Then

- ▶ $p_1 = 10^6 / (10^6 + 100) \approx 1$ and $p_0 = 100 / 10^6 \approx 0$,
- ▶ thus the Gini impurity $1 - p_1^2 - p_0^2 \approx 0$.

Consider an attribute A with $V(A) = \{a, b\}$.

Splitting \mathcal{D} according to A gives to sets \mathcal{D}_a and \mathcal{D}_b .

Imbalanced Classes

Consider a dataset \mathcal{D} where

- ▶ there are two classes, $C = \{0, 1\}$,
- ▶ 10^6 examples have the class 1,
- ▶ 100 examples have the class 0.

Then

- ▶ $p_1 = 10^6 / (10^6 + 100) \approx 1$ and $p_0 = 100 / 10^6 \approx 0$,
- ▶ thus the Gini impurity $1 - p_1^2 - p_0^2 \approx 0$.

Consider an attribute A with $V(A) = \{a, b\}$.

Splitting \mathcal{D} according to A gives to sets \mathcal{D}_a and \mathcal{D}_b .

What is the impurity decrease caused by the attribute?

$$\text{ImpDec}(\mathcal{D}, A) = \text{Gini}(\mathcal{D}) - \frac{|\mathcal{D}_a|}{|\mathcal{D}|} \text{Gini}(\mathcal{D}_a) - \frac{|\mathcal{D}_b|}{|\mathcal{D}|} \text{Gini}(\mathcal{D}_b)$$

Imbalanced Classes

Consider a dataset \mathcal{D} where

- ▶ there are two classes, $C = \{0, 1\}$,
- ▶ 10^6 examples have the class 1,
- ▶ 100 examples have the class 0.

Then

- ▶ $p_1 = 10^6 / (10^6 + 100) \approx 1$ and $p_0 = 100 / 10^6 \approx 0$,
- ▶ thus the Gini impurity $1 - p_1^2 - p_0^2 \approx 0$.

Consider an attribute A with $V(A) = \{a, b\}$.

Splitting \mathcal{D} according to A gives to sets \mathcal{D}_a and \mathcal{D}_b .

What is the impurity decrease caused by the attribute?

$$\text{ImpDec}(\mathcal{D}, A) = \text{Gini}(\mathcal{D}) - \frac{|\mathcal{D}_a|}{|\mathcal{D}|} \text{Gini}(\mathcal{D}_a) - \frac{|\mathcal{D}_b|}{|\mathcal{D}|} \text{Gini}(\mathcal{D}_b)$$

For small $|\mathcal{D}_a|$ (say ≤ 1000) we have small $|\mathcal{D}_a|/|\mathcal{D}|$


For not so small \mathcal{D}_a we have $\text{Gini}(\mathcal{D}_a) \approx 0$.

In both cases, the impurity decrease is very small.


Model Tuning - Over/Under Fitting

The behavior of the model on the training set:


Overfitting



Right Fit




Underfitting



Model Tuning - Over/Under Fitting


The behavior of the model on the training set:



- ▶ The left one is strongly overfitting. It would possibly not work well on new data.

Model Tuning - Over/Under Fitting


The behavior of the model on the training set:



- ▶ The left one is strongly overfitting. It would possibly not work well on new data.
- ▶ The right one is strongly underfitting. It would probably give poor classification results.


Model Tuning - Over/Under Fitting

The behavior of the model on the training set:



- ▶ The left one is strongly overfitting. It would possibly not work well on new data.
- ▶ The right one is strongly underfitting. It would probably give poor classification results.
- ▶ The middle one seems good (but still needs to be tested on fresh data).


Model Tuning - Overfitting in Decision Trees



See the overfitting on the left and the “nice” model on the right. Both overfitting and underfitting are best avoided. But how do we find out?

Model Tuning (In General)

Recall from the first lecture:




The validation should be done on a **validation set** separated from the training set.

We will discuss more sophisticated techniques later.

Model Tuning (In General)

Recall from the first lecture:




The validation should be done on a **validation set** separated from the training set.

We will discuss more sophisticated techniques later.

What hyperparameters to set? (see the next slide)

Model Tuning (In General)

Recall from the first lecture:



The validation should be done on a **validation set** separated from the training set.

We will discuss more sophisticated techniques later.

What hyperparameters to set? (see the next slide)

What to observe? In the case of decision trees, one should observe the difference between performance measures (e.g., classification accuracy) on the training and validation sets.

The too-large difference implies an improperly fitting model.

How to Fit Decision Trees?

There are several approaches available for decision trees.

Generally, the overfitting can be either prevented or resolved.

How to Fit Decision Trees?

There are several approaches available for decision trees.

Generally, the overfitting can be either prevented or resolved.

- ▶ **Pre-pruning:** Build the tree so it does not overfit by restricting its size.

How to Fit Decision Trees?

There are several approaches available for decision trees.

Generally, the overfitting can be either prevented or resolved.

- ▶ **Pre-pruning:** Build the tree so it does not overfit by restricting its size.
- ▶ **Post-pruning:** Overfit with a large tree and remove subtrees to make it smaller.

How to Fit Decision Trees?

There are several approaches available for decision trees.

Generally, the overfitting can be either prevented or resolved.

- ▶ **Pre-pruning**: Build the tree so it does not overfit by restricting its size.
- ▶ **Post-pruning**: Overfit with a large tree and remove subtrees to make it smaller.
- ▶ **Ensemble methods**: Fit several different trees and let them classify together (e.g., using majority voting).

How to Fit Decision Trees?

There are several approaches available for decision trees.

Generally, the overfitting can be either prevented or resolved.

- ▶ **Pre-pruning**: Build the tree so it does not overfit by restricting its size.
- ▶ **Post-pruning**: Overfit with a large tree and remove subtrees to make it smaller.
- ▶ **Ensemble methods**: Fit several different trees and let them classify together (e.g., using majority voting).

The post-pruning approach has been more successful in practice than the pre-pruning because it is usually hard to say when to stop growing the tree.

We shall meet this controversy also in deep learning, where recent history shows a similar phenomenon.

The ensemble methods will be covered later when we discuss random forests.

Pre-Pruning - Hyperparameters

Hyperparameters controlling the size of the tree:

- ▶ Maximum depth - do not grow the tree beyond the max depth
The deeper the tree, the more complex models you can create \Rightarrow overfitting. Low depth may restrict expressivity.

Pre-Pruning - Hyperparameters

Hyperparameters controlling the size of the tree:

- ▶ Maximum depth - do not grow the tree beyond the max depth
The deeper the tree, the more complex models you can create \Rightarrow overfitting. Low depth may restrict expressivity.
- ▶ Minimum number of examples to split a node - if $\mathcal{D}[\tau]$ is small, τ becomes a leaf (labeled with the majority class)
Higher values prevent a model from learning relations specific only for a few examples. Too high values may result in underfitting.

Pre-Pruning - Hyperparameters

Hyperparameters controlling the size of the tree:

- ▶ Maximum depth - do not grow the tree beyond the max depth
The deeper the tree, the more complex models you can create \Rightarrow overfitting. Low depth may restrict expressivity.
- ▶ Minimum number of examples to split a node - if $\mathcal{D}[\tau]$ is small, τ becomes a leaf (labeled with the majority class)
Higher values prevent a model from learning relations specific only for a few examples. Too high values may result in underfitting.
- ▶ Minimum number of examples required to be in a leaf
Similar to the previous one. A higher number means we cannot have very specific branches concerned with particular combinations of values.

Pre-Pruning - Hyperparameters

Hyperparameters controlling the size of the tree:

- ▶ Maximum depth - do not grow the tree beyond the max depth
The deeper the tree, the more complex models you can create \Rightarrow overfitting. Low depth may restrict expressivity.
- ▶ Minimum number of examples to split a node - if $\mathcal{D}[\tau]$ is small, τ becomes a leaf (labeled with the majority class)
Higher values prevent a model from learning relations specific only for a few examples. Too high values may result in underfitting.
- ▶ Minimum number of examples required to be in a leaf
Similar to the previous one. A higher number means we cannot have very specific branches concerned with particular combinations of values.
- ▶ Minimum information gain/impurity decrease
A small impurity decrease means that the split does not contribute too much to the classification (their proportions after a split are similar to proportions before a split). However, keep in mind that it is *weighted average impurity* after the split.

Post-Pruning - Reduced Error Pruning

Train a large tree and then remove nodes that make classification worse on the validation set.

Post-Pruning - Reduced Error Pruning

Train a large tree and then remove nodes that make classification worse on the validation set.

Given a decision tree \mathcal{T} and its internal node $\tau \in T_{int}$, we denote by $\mathcal{T}_{-\tau}$ the tree obtained from \mathcal{T} by removing the subtree rooted in τ , i.e., τ is a leaf of $\mathcal{T}_{-\tau}$.

Post-Pruning - Reduced Error Pruning

Train a large tree and then remove nodes that make classification worse on the validation set.

Given a decision tree \mathcal{T} and its internal node $\tau \in T_{int}$, we denote by $\mathcal{T}_{-\tau}$ the tree obtained from \mathcal{T} by removing the subtree rooted in τ , i.e., τ is a leaf of $\mathcal{T}_{-\tau}$.

- 1: Train \mathcal{T} to maximum fit on the *training dataset*.
- 2: **while** true **do**
- 3: $Err[\mathcal{T}] \leftarrow$ the error of \mathcal{T} on the validation set.
- 4: **for** $\tau \in T_{int}$ **do**
- 5: $Err[\mathcal{T}_{-\tau}] \leftarrow$ the error of $\mathcal{T}_{-\tau}$ on the validation set.
- 6: **end for**
- 7: **if** $Err[\mathcal{T}] \leq \min\{Err[\mathcal{T}_{-\tau}] \mid \tau \in T_{int}\}$ **then return** \mathcal{T}
- 8: **else**
- 9: $\mathcal{T} \leftarrow \operatorname{argmin}\{Err[\mathcal{T}_{-\tau}] \mid \tau \in T_{int}\}$
- 10: **end if**
- 11: **end while**

The error $Err[\mathcal{T}]$ can be any measure of the “badness” of the decision tree \mathcal{T} . For example, $1 - Accuracy$.

Other Pruning Methods

There are more pruning methods.

- ▶ Rule Post-Pruning:
 - ▶ Transform the tree into a set of rules.
Rules correspond to paths in the tree; they have a form of implication: Specific values of attributes imply a class.
 - ▶ Remove the attribute conditions from the premises of the implications.

This gives a more refined pruning: Instead of removing the whole subtree, each path of the subtree can be pruned individually.

Other Pruning Methods

There are more pruning methods.

- ▶ Rule Post-Pruning:
 - ▶ Transform the tree into a set of rules.
Rules correspond to paths in the tree; they have a form of implication: Specific values of attributes imply a class.
 - ▶ Remove the attribute conditions from the premises of the implications.

This gives a more refined pruning: Instead of removing the whole subtree, each path of the subtree can be pruned individually.

- ▶ Using cost complexity measure: Evaluate trees not only based on the classification error but also based on their size.

Other Pruning Methods

There are more pruning methods.

- ▶ Rule Post-Pruning:
 - ▶ Transform the tree into a set of rules.
Rules correspond to paths in the tree; they have a form of implication: Specific values of attributes imply a class.
 - ▶ Remove the attribute conditions from the premises of the implications.

This gives a more refined pruning: Instead of removing the whole subtree, each path of the subtree can be pruned individually.

- ▶ Using cost complexity measure: Evaluate trees not only based on the classification error but also based on their size.

Typically introduce regularization into the error functions:

Given a decision tree \mathcal{T}

$$Err_{\alpha}(\mathcal{T}) = Err(\mathcal{T}) + \alpha|\mathcal{T}|$$

The original paper by Breiman et al. (1984) defined $Err(\mathcal{T})$ to be the misclassification rate on the training dataset, and $|\mathcal{T}|$ is the number of nodes of the tree \mathcal{T} .

Sensitivity to Small Changes and Randomness

- ▶ Decision trees are sensitive to small changes in data and hyperparameters.
Several attributes may provide (almost) identical information gain but divide the training dataset very differently.
- ▶ Some implementations choose attributes partially in random (sci-kit-learn). You may get completely different trees.



Sensitivity to Small Changes and Randomness

- ▶ Decision trees are sensitive to small changes in data and hyperparameters.
Several attributes may provide (almost) identical information gain but divide the training dataset very differently.
- ▶ Some implementations choose attributes partially in random (sci-kit-learn). You may get completely different trees.

A solution is to train an ensemble of many decision trees and then use majority voting for classification.

This is the fundamental idea behind random forests (see later lectures).

Iris - Illustration




Decision trees trained on the Iris dataset.

Iris Setosa is perfectly separated by many choices for the first split.

Axis Sensitivity

The decision makes divisions along particular axes:




That is, rotated data may result in a completely different model.

That is why decision trees are often preceded by the *principal component analysis (PCA)* transformation, which aligns data along the axes of maximum data variance.


XOR Training Problem

Consider the following training dataset:




XOR Training Problem

Consider the following training dataset:




An ideal decision tree would look like this:




Attempts at Training on XOR

Max depth = 2:



Attempts at Training on XOR

Max depth = 2:




The problem: Both information gain and decrease in impurity consider only the relationship of a *single* attribute and the class.

However, there is no relationship between a single attribute and the class; both attributes need to be considered together!

More Attempts at Training on XOR

Max depth = 3:



It's better but still fails occasionally.

Advantages of Decision Trees

- ▶ Simple to understand and interpret; trees can be visualized.
- ▶ Uses a white box model, where conditions are easily explained by boolean logic.

Advantages of Decision Trees

- ▶ Simple to understand and interpret; trees can be visualized.
- ▶ Uses a white box model, where conditions are easily explained by boolean logic.
- ▶ Can approximate an arbitrary (reasonable) boundary and capture complex non-linear relationships between attributes.
- ▶ Capable of handling multi-class problems.

Advantages of Decision Trees

- ▶ Simple to understand and interpret; trees can be visualized.
- ▶ Uses a white box model, where conditions are easily explained by boolean logic.
- ▶ Can approximate an arbitrary (reasonable) boundary and capture complex non-linear relationships between attributes.
- ▶ Capable of handling multi-class problems.
- ▶ Little data preparation, unlike other techniques requiring normalization, dummy variables, or missing value removal.
- ▶ Handles numerical and categorical data.
- ▶ Not sensitive to outliers since the splitting is based on the proportion of examples within the split ranges and not on absolute values.

Advantages of Decision Trees

- ▶ Simple to understand and interpret; trees can be visualized.
- ▶ Uses a white box model, where conditions are easily explained by boolean logic.
- ▶ Can approximate an arbitrary (reasonable) boundary and capture complex non-linear relationships between attributes.
- ▶ Capable of handling multi-class problems.
- ▶ Little data preparation, unlike other techniques requiring normalization, dummy variables, or missing value removal.
- ▶ Handles numerical and categorical data.
- ▶ Not sensitive to outliers since the splitting is based on the proportion of examples within the split ranges and not on absolute values.
- ▶ The cost of using a well-balanced tree is logarithmic in the number of data points used to train it.

Disadvantages of Decision Trees

- ▶ Overfitting: Trees can be over-complex and not generalize well, needing pruning or limits on tree depth.
- ▶ Instability: Small data variations can result in very different trees. This is mitigated in ensemble methods.
- ▶ Non-smooth predictions: Decision trees make piecewise constant approximations, which are not suitable for extrapolation.

Disadvantages of Decision Trees

- ▶ Overfitting: Trees can be over-complex and not generalize well, needing pruning or limits on tree depth.
- ▶ Instability: Small data variations can result in very different trees. This is mitigated in ensemble methods.
- ▶ Non-smooth predictions: Decision trees make piecewise constant approximations, which are not suitable for extrapolation.
- ▶ Difficulty expressing certain concepts, such as XOR, parity, or multiplexer problems (see the next slide).
- ▶ Bias in trees: Decision trees can create biased trees if some classes dominate. Balancing the dataset is recommended.

Disadvantages of Decision Trees


- ▶ Overfitting: Trees can be over-complex and not generalize well, needing pruning or limits on tree depth.
- ▶ Instability: Small data variations can result in very different trees. This is mitigated in ensemble methods.
- ▶ Non-smooth predictions: Decision trees make piecewise constant approximations, which are not suitable for extrapolation.
- ▶ Difficulty expressing certain concepts, such as XOR, parity, or multiplexer problems (see the next slide).
- ▶ Bias in trees: Decision trees can create biased trees if some classes dominate. Balancing the dataset is recommended.
- ▶ Learning optimal trees is NP-complete: Heuristic algorithms like greedy algorithms are used, which do not guarantee globally optimal trees. Ensemble methods can help.

History of Decision Trees

- ▶ Hunt and colleagues use exhaustive search decision-tree methods (CLS) to model human concept learning in the 1960's.
- ▶ In the late 70's, Quinlan developed ID3 with the information gain heuristic to learn expert systems from examples.
- ▶ Simultaneously, Breiman, Friedman, and colleagues develop CART (Classification and Regression Trees), similar to ID3.
- ▶ In the 1980s, various improvements were introduced to handle noise, continuous features, missing features, and improved splitting criteria. Various expert-system development tools results.
- ▶ Quinlan's updated decision-tree package (C4.5) released in 1993.


Comment on Regression Trees

Decision trees can also be used to approximate functions. Assign a function value to the leaves instead of classes.



Here, “mse” is the mean-squared-error.

Comment on Regression Trees



Intuitively, for every subinterval of x_1 , the value (the red line) is at the average y over the subinterval.

How are the subintervals being set?

Regression Trees

A *regression tree* is a decision tree whose leaves are labeled by values from \mathbb{R} .

We follow the same procedure as in decision trees during inference on an input \vec{x} .

Regression Trees

A *regression tree* is a decision tree whose leaves are labeled by values from \mathbb{R} .

We follow the same procedure as in decision trees during inference on an input \vec{x} .

How exactly are such trees trained?

We aim to minimize the mean squared error.

Regression Trees

A *regression tree* is a decision tree whose leaves are labeled by values from \mathbb{R} .

We follow the same procedure as in decision trees during inference on an input \vec{x} .

How exactly are such trees trained?

We aim to minimize the mean squared error.

Assume, for the moment, that we want to train a single-node tree. What will be the best labeling value for the single node?

Regression Trees

A *regression tree* is a decision tree whose leaves are labeled by values from \mathbb{R} .

We follow the same procedure as in decision trees during inference on an input \vec{x} .

How exactly are such trees trained?

We aim to minimize the mean squared error.

Assume, for the moment, that we want to train a single-node tree. What will be the best labeling value for the single node?

Now, consider the training for arbitrary trees.

Assume ordinal attributes.

The algorithm also works for discrete attributes; ordinal attributes, however, allow us to make binary splits.

Regression Trees

A *regression tree* is a decision tree whose leaves are labeled by values from \mathbb{R} .

We follow the same procedure as in decision trees during inference on an input \vec{x} .

How exactly are such trees trained?

We aim to minimize the mean squared error.

Assume, for the moment, that we want to train a single-node tree. What will be the best labeling value for the single node?

Now, consider the training for arbitrary trees.

Assume ordinal attributes.

The algorithm also works for discrete attributes; ordinal attributes, however, allow us to make binary splits.

The training procedure is the same as for the decision trees, except that the splits and cut points are selected differently.

Regression Trees

Given a dataset $\mathcal{D} = \{(\vec{x}_1, d_1), \dots, (\vec{x}_p, d_p)\}$, we denote by \bar{D} the average *desired* value in \mathcal{D} , that is $\bar{D} = \frac{1}{p} \sum_{k=1}^p d_k$.

Regression Trees

Given a dataset $\mathcal{D} = \{(\vec{x}_1, d_1), \dots, (\vec{x}_p, d_p)\}$, we denote by \bar{D} the average *desired* value in \mathcal{D} , that is $\bar{D} = \frac{1}{p} \sum_{k=1}^p d_k$.

Consider a dataset \mathcal{D} and let us find a cut point for A in \mathcal{D} .

Regression Trees

Given a dataset $\mathcal{D} = \{(\vec{x}_1, d_1), \dots, (\vec{x}_p, d_p)\}$, we denote by \bar{D} the average *desired* value in \mathcal{D} , that is $\bar{D} = \frac{1}{p} \sum_{k=1}^p d_k$.

Consider a dataset \mathcal{D} and let us find a cut point for A in \mathcal{D} .

We are looking for a value H of the attribute A such that the split:

$$\mathcal{D}_{\leq H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) \leq H\} \quad \mathcal{D}_{>H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) > H\}$$

Minimizes the following *split error*:

$$\frac{1}{|\mathcal{D}_{\leq H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{\leq H}} (d - \bar{D}_{\leq H})^2 + \frac{1}{|\mathcal{D}_{>H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{>H}} (d - \bar{D}_{>H})^2$$

Regression Trees

Given a dataset $\mathcal{D} = \{(\vec{x}_1, d_1), \dots, (\vec{x}_p, d_p)\}$, we denote by \bar{D} the average *desired* value in \mathcal{D} , that is $\bar{D} = \frac{1}{p} \sum_{k=1}^p d_k$.

Consider a dataset \mathcal{D} and let us find a cut point for A in \mathcal{D} .

We are looking for a value H of the attribute A such that the split:

$$\mathcal{D}_{\leq H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) \leq H\} \quad \mathcal{D}_{>H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) > H\}$$

Minimizes the following *split error*:

$$\frac{1}{|\mathcal{D}_{\leq H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{\leq H}} (d - \bar{D}_{\leq H})^2 + \frac{1}{|\mathcal{D}_{>H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{>H}} (d - \bar{D}_{>H})^2$$

Denote by $\text{MinE}(\mathcal{D})$ the minimum of the split error over all attributes A and all cut points H .

Regression Trees

Given a dataset $\mathcal{D} = \{(\vec{x}_1, d_1), \dots, (\vec{x}_p, d_p)\}$, we denote by \bar{D} the average *desired* value in \mathcal{D} , that is $\bar{D} = \frac{1}{p} \sum_{k=1}^p d_k$.

Consider a dataset \mathcal{D} and let us find a cut point for A in \mathcal{D} .

We are looking for a value H of the attribute A such that the split:

$$\mathcal{D}_{\leq H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) \leq H\} \quad \mathcal{D}_{>H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) > H\}$$

Minimizes the following *split error*:

$$\frac{1}{|\mathcal{D}_{\leq H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{\leq H}} (d - \bar{D}_{\leq H})^2 + \frac{1}{|\mathcal{D}_{>H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{>H}} (d - \bar{D}_{>H})^2$$

Denote by $\text{MinE}(\mathcal{D})$ the minimum of the split error over all attributes A and all cut points H . Compute

$$\Delta = \left(\frac{1}{|\mathcal{D}|} \sum_{(\vec{x}, d) \in \mathcal{D}} (d - \bar{D})^2 \right) - \text{MinE}$$

Regression Trees

Given a dataset $\mathcal{D} = \{(\vec{x}_1, d_1), \dots, (\vec{x}_p, d_p)\}$, we denote by \bar{D} the average *desired* value in \mathcal{D} , that is $\bar{D} = \frac{1}{p} \sum_{k=1}^p d_k$.

Consider a dataset \mathcal{D} and let us find a cut point for A in \mathcal{D} .

We are looking for a value H of the attribute A such that the split:

$$\mathcal{D}_{\leq H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) \leq H\} \quad \mathcal{D}_{>H} = \{(\vec{x}, d) \in \mathcal{D} \mid A(\vec{x}) > H\}$$

Minimizes the following *split error*:

$$\frac{1}{|\mathcal{D}_{\leq H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{\leq H}} (d - \bar{D}_{\leq H})^2 + \frac{1}{|\mathcal{D}_{>H}|} \sum_{(\vec{x}, d) \in \mathcal{D}_{>H}} (d - \bar{D}_{>H})^2$$

Denote by $\text{MinE}(\mathcal{D})$ the minimum of the split error over all attributes A and all cut points H . Compute

$$\Delta = \left(\frac{1}{|\mathcal{D}|} \sum_{(\vec{x}, d) \in \mathcal{D}} (d - \bar{D})^2 \right) - \text{MinE}$$

If Δ is large enough, split on A and H that minimize the split error. Otherwise, stop splitting and label the leaf with \bar{D} .

Regression Tress

Without any lower bound on the number of examples in the leaves, the algorithm will eventually overfit by splitting into (possibly) singleton leaves.

