



Crypto libraries introduction

Milan Brož
xbroz@fi.muni.cz

PV181, FI MUNI, Brno




Open source cryptographic libraries



- Linux environment – up to you:
 - Fedora / VirtualBox VM (see course materials)
 - Your own distro – need to install development env.:
 - libgcrypt: Fedora: **libgcrypt-devel**; Debian/Ubuntu: **libgcrypt20-dev**
 - OpenSSL: Fedora: **openssl-devel**; Debian/Ubuntu: **libssl-dev**
 - libsodium: Fedora: **libsodium-devel**; Debian/Ubuntu: **libsodium-dev**
 - aisa.fi.muni.cz (OpenSSL only)
- All examples in C language
- Home assignments (10 points each)
- Videocall for discussion (check mail)

Lab environment

VirtualBox image




- Unpack zip archive from IS
- Open VirtualBox (click **blue** icon – config file)
- Login and password is **pv181**
(same for **sudo** and **root** password)
- Examples on gitlab (and in /home/pv181 in VM)

```
git clone https://gitlab.fi.muni.cz/xbroz/pv181.git  
make clean; make; ./example
```


Cryptographic libraries

Goals for this lab



- Crypto libraries and API / abstraction
 - More practical and implementation view
 - Why legacy code, compatibility and standards
 - Coding practices
 - Defensive approach
- It will fail, be prepared for it :-)**

Why implementation matters




- It works, but ...
- How many possible bugs do you see?

```
/* Read a key from Linux RNG */
#include <string.h>
#include <unistd.h>
#include <fcntl.h>

int main(int argc, char *argv[])
{
    int fd;
    char key[32];


    fd = open("/dev/random", O_RDONLY);
    read(fd, key, 32);
    close(fd);
    /* Do something with the key[] */
    memset(key, 0, 32);
    return 0;
}
```

Why implementation matters



- How many possible bugs do you see?
 - *No check for return code, open(), read()*
 - *Possible reading from invalid fd (no random at all)*
 - *Partial read() is not detected*
 - *Failed read() is not detected
(mandatory access control can block reading)*
 - *Magic numbers (one constant on several places)*
 - *Compiler can optimize memset() out
(secret key remains in memory)*
 - *No error exit code, cannot check for failure*

Why implementation matters



- Fixes? Let's see **example 0** in git.
- It is better to use a crypto library.
- Usually, maintainers implement it correctly :-)




```
int getRandomNumber()  
{  
    return 4; // chosen by fair dice roll.  
             // guaranteed to be random.  
}
```

<https://xkcd.com/221/>

Some (not too old) books


More practically oriented books:

- *Jean-Phillipe Aumasson*
**Serious Cryptography:
A Practical Introduction
to Modern Encryption (2017)**
- *Ferguson, Schneier, Kohno*
**Cryptography Engineering:
Design Principles and Practical
Applications (2010)**




Cryptographic libraries

Introduction



- Open-source / Proprietary
- Static + embedded / dynamically linked
- Low or high level abstractions
- Multiplatform
- Stable API and ABI
- Security or platform specific features
 - Safe memory use, side-channel resistance, ...
 - HW acceleration support, “secure” HW support


Example libs (C and Linux) abstraction from low to high



- **Nettle**
- **libgcrypt**
- **OpenSSL**
 - LibreSSL (clone), BoringSSL (Google)
- **NSS**
 - Network Security Services (Mozilla)
- **NaCl ("salt")**
 - more common as **libsodium**

Today: examples in **libgcrypt**, **OpenSSL** and **libsodium**

Crypto libraries



- Random Number Generator (RNG) access
- Hash, keyed-hash (HMAC, msg authentication)
- Symmetric ciphers and modes
- Asymmetric ciphers
- Certificate support, ASN.1, ...
- Key exchange, key derivation
- Helpers
 - secure memory
 - safe comparison
 - network / sockets
 - ...