

SUNRISE; Serial number: 711005229; Firmware: V 3.31 25/08/05; XREAD PLUS Version: V 4.00
Date: 10/2/12
Time: 12:10

User comment:

Measurement mode: Absorbance
Measurement filter: 492 nm
Number of flashes: 55

Rawdata

<>	1	2	3	4	5	6	7	8	9
A	0.0510	0.0510	0.9320	0.9100	1.1620	1.0630	0.1070	0.0740	0.8870
B	0.9470	0.9870	1.6340	1.5720	1.0050	0.9750	0.4910	0.4870	0.7810
C	1.0730	1.1880	0.5870	0.7020	1.4200	1.3890	0.3080	0.3670	0.3590
D	1.6320	1.7530	0.9590	0.9940	0.9860	1.5070	1.1620	1.0900	0.4590
E	1.3510	1.3810	1.1350	1.2030	1.1840	1.1350	0.5370	0.4690	0.3710
F	0.4380	0.4860	0.0450	0.0560	0.0500	0.0380	0.4710	0.4360	0.0480
G	0.0530	0.0380	0.1500	0.0430	0.0350	0.0390	0.0370	0.0340	0.0380
H	0.0580	0.0470	0.0440	0.0420	0.0640	0.0580	0.0470	0.0500	0.0440

10	11	12
0.9480	0.3170	0.3380
0.8430	0.3590	0.3650
0.3400	0.7550	0.6470
0.4480	1.0560	1.0280
0.3910	0.5040	0.3750
0.0410	0.0420	0.0390
0.0340	0.0380	0.0390
0.0470	0.0560	0.0640

SUNRISE; Serial number: 711005229; Firmware: V 3.31 25/08/05; XREAD PLUS Version: V 4.00
Date: 10/2/12
Time: 12:11

User comment:

Measurement mode: Absorbance
Measurement filter: 492 nm
Number of flashes: 55

Rawdata

<>	1	2	3	4	5	6	7	8	9
A	0.7250	0.6830	1.2680	1.4620	1.6030	1.7900	0.3730	0.4600	1.0510
B	1.5740	1.6810	2.1320	2.0120	1.4660	1.4670	0.8100	0.8520	1.0080
C	1.9030	2.1710	1.6220	1.5240	1.9610	1.8430	0.7730	0.8290	0.7410
D	2.1460	2.0860	1.6820	0.6420	1.6780	1.5820	1.0940	1.0570	1.5110
E	1.9550	1.8240	1.7520	1.7580	1.7250	1.6870	0.9350	0.8700	0.6900
F	1.2250	1.5290	0.0920	0.0970	0.0660	0.0900	1.4200	0.9800	0.0680
G	0.0380	0.0340	0.0340	0.0350	0.0390	0.0440	0.0410	0.0350	0.0340
H	0.0530	0.0510	0.0540	0.0630	0.0430	0.0470	0.0540	0.0430	0.0660

10	11	12
1.2640	0.4830	0.5030
0.9770	0.7240	0.6130
0.7140	0.7930	0.7610
0.6100	0.7600	0.8460
0.6590	0.6140	0.5600
0.0430	0.0440	0.0400
0.0360	0.0430	0.0440
0.0480	0.0920	0.0620

SUNRISE; Serial number: 711005229; Firmware: V 3.31 25/08/05; XREAD PLUS Version: V 4.00
Date: 10/2/12
Time: 12:12

User comment:

Measurement mode: Absorbance
Measurement filter: 492 nm
Number of flashes: 55

Rawdata

<>	1	2	3	4	5	6	7	8	9
A	0.0620	0.0700	1.0530	0.9330	1.3730	1.3720	0.0990	0.1580	1.0000
B	1.2530	1.2570	1.8210	1.8230	1.1200	1.1170	0.5120	0.6170	0.7760
C	1.5420	1.4140	0.9040	0.9330	1.9110	1.6160	0.4070	0.4170	0.3610
D	1.8620	1.9860	1.1760	1.3890	1.6740	1.7310	1.3420	1.1070	0.4540
E	1.5750	1.6140	1.6370	1.6710	1.5620	1.3160	0.5260	0.5180	0.5070
F	0.6270	0.6770	0.0380	0.0410	0.0410	0.0410	0.5320	0.5040	0.0400
G	0.0340	0.0290	0.0330	0.0270	0.0340	0.0360	0.0640	0.0950	0.0350
H	0.0670	0.0380	0.0360	0.0370	0.0680	0.0400	0.0350	0.0370	0.0350

10	11	12
1.0280	0.4180	0.4300
0.9220	0.3970	0.3240
0.3930	0.8700	0.7350
0.4550	1.0010	0.8640
0.5330	0.4000	0.4070
0.1210	0.0360	0.0370
0.0390	0.0310	0.0340
0.0410	0.0350	0.0360

SUNRISE; Serial number: 711005229; Firmware: V 3.31 25/08/05; XREAD PLUS Version: V 4.00
Date: 10/2/12
Time: 12:19

User comment:
Measurement mode: Absorbance
Measurement filter: 492 nm
Number of flashes: 55

Break - No Data

SUNRISE; Serial number: 711005229; Firmware: V 3.31 25/08/05; XREAD PLUS Version: V 4.00
Date: 10/2/12
Time: 12:19

User comment:

Measurement mode: Absorbance
Measurement filter: 492 nm
Number of flashes: 55

Rawdata

<>	1	2	3	4	5	6	7	8	9
A	0.0710	0.1100	1.0650	1.4380	1.4010	1.4320	0.1420	0.1220	0.9390
B	1.3210	1.3720	1.6230	1.8000	1.2080	1.1190	0.4970	0.5490	0.7720
C	1.3960	1.3840	0.9330	0.9880	1.2000	1.1180	0.5440	0.5060	0.3740
D	1.6610	1.6600	1.0310	1.0860	1.3940	1.2180	1.0650	1.2890	0.5070
E	1.5190	1.5090	1.6050	1.6110	1.2470	1.0450	0.6100	0.6930	0.4260
F	0.6000	0.5450	0.0430	0.0480	0.0500	0.0480	0.5630	0.6050	0.0430
G	0.0390	0.0350	0.0340	0.0370	0.0360	0.0400	0.0350	0.0400	0.0390
H	0.0450	0.0490	0.0410	0.0410	0.0400	0.0560	0.0570	0.0640	0.0400

10	11	12
0.8260	0.4220	0.5150
0.8780	0.3870	0.3760
0.4460	0.8580	0.5150
0.3900	1.0030	0.7740
0.5140	0.4070	0.3750
0.0440	0.0510	0.0410
0.0570	0.0320	0.0390
0.0390	0.0380	0.0400

SUNRISE; Serial number: 711005229; Firmware: V 3.31 25/08/05; XREAD PLUS Version: V 4.00
Date: 10/2/12
Time: 12:20

User comment:

Measurement mode: Absorbance
Measurement filter: 492 nm
Number of flashes: 55

Rawdata

<>	1	2	3	4	5	6	7	8	9
A	0.0580	0.0550	1.9140	2.0480	2.3470	2.3910	0.1470	0.1060	1.6790
B	1.7340	1.7940	2.2700	2.1090	1.2640	1.3270	0.7020	0.6310	0.8520
C	1.6620	1.6190	0.9350	0.8770	1.3720	1.3190	0.8110	0.4820	0.4260
D	1.6320	1.5750	0.0870	0.0990	0.9960	1.1420	0.9610	0.8340	0.1560
E	2.1350	2.2100	2.2210	1.8880	1.8840	1.8980	0.7900	0.8480	0.7020
F	0.6360	0.4640	0.0450	0.0480	0.0410	0.1210	0.5520	0.4110	0.0560
G	0.0430	0.0440	0.0610	0.0410	0.0350	0.0370	0.0470	0.0410	0.0450
H	0.0380	0.0480	0.0450	0.0470	0.0460	0.0440	0.0400	0.0470	0.0430

10	11	12
1.8690	1.6830	1.4640
1.1340	0.3890	0.8670
0.5100	0.6310	0.7160
0.1100	0.7510	0.5400
0.7250	0.4840	0.5060
0.0420	0.0450	0.0410
0.0750	0.0480	0.0440
0.0430	0.0430	0.0560