

A survey of available tools and web servers for analysis of protein–protein interactions and interfaces

Nurcan Tuncbag, Gozde Kar, Ozlem Keskin, Attila Gursoy and Ruth Nussinov

Submitted: 28th October 2008; Received (in revised form): 5th January 2009

Abstract

The unanimous agreement that cellular processes are (largely) governed by interactions between proteins has led to enormous community efforts culminating in overwhelming information relating to these proteins; to the regulation of their interactions, to the way in which they interact and to the function which is determined by these interactions. These data have been organized in databases and servers. However, to make these really useful, it is essential not only to be aware of these, but in particular to have a working knowledge of which tools to use for a given problem; what are the tool advantages and drawbacks; and no less important how to combine these for a particular goal since usually it is not one tool, but some combination of tool-modules that is needed. This is the goal of this review.

Keywords: *protein–protein interactions; protein–protein interfaces; binding site prediction; docking; web servers; databases*

PROTEIN–PROTEIN INTERACTIONS

Proteins are parts of complex networks or pathways rather than isolated entities. The different levels of complexity of biological systems arise not only from the number of the proteins (genes) of the organism, but also from combinatorial interactions among them as well as from alternative splicing, and chemical and structural alterations of the proteome [1]. Cellular processes are largely governed by different types of interactions between proteins, and the function of a protein can be better understood considering

its interactions. The broad recognition of the importance of characterizing all protein interactions in a cell has rendered the development of experimental and computational techniques to detect and predict interacting protein partners. Experimental methods can be divided into two categories:

- (i) *Screening large scale protein interactions* involves high-throughput experiments where each protein encoded in the genome of interest is expressed and exhaustively probed for mutual interactions by assays such as the yeast two hybrid systems

Corresponding author. Ruth Nussinov, Center for Cancer Research Nanobiology Program, Bldg 469, Rm 151, SAIC, NCI-Frederick, Frederick, MD 21702 USA and Department of Human Genetics, Medical School, Tel Aviv University, Tel Aviv, Israel, 69978. Tel: 301-846-5579; Fax: 301-846-5598; E-mail: ruthnu@helix.nih.gov

Nurcan Tuncbag is a second-year PhD student at the Computational Sciences and Engineering Program at Koc University, Istanbul. She has been working on protein interactions and interfaces.

Gozde Kar is a first-year PhD student at the Chemical and Biological Engineering Program at Koc University, Istanbul. She has been working on protein interaction networks.

Ozlem Keskin is an associate professor at the Chemical and Biological Engineering Department and the Center for Computational Biology and Bioinformatics at Koc University, Istanbul. Her research focuses on the computational studies of protein interactions and dynamics.

Attila Gursoy is an associate professor at the Computer Engineering Department and the Center for Computational Biology and Bioinformatics at Koc University, Istanbul. His research focuses on the computational studies of protein interactions and parallel computing.

Ruth Nussinov is a professor in the Department of Human Genetics, Medical School, Tel Aviv University, and a Senior Principal Investigator at the SAIC, National Cancer Institute, USA. Her research focuses on computational studies of protein folding, binding and function.

(Y2H) [2, 3], protein-fragment complementation assay (PCA) [4, 5], affinity purification [6], phage display libraries [7] indicating physical interactions. Protein/DNA microarrays [8, 9], and ‘synthetic lethals’ (genes whose simultaneous knockout is lethal to the organism [10]) are also important since they provide functional association between proteins.

- (ii) *Screening specific protein interactions* where the experiments may be individually designed to identify and validate a small number of specifically targeted interactions [11]. Studies of specific protein interactions can provide structural information, kinetic and dynamic characterization [12]. The methods include X-ray crystallography [10], NMR spectroscopy [10], fluorescence resonance energy transfer (FRET) [13] and surface plasmon resonance (SPR) [14].

In this review, we provide a comprehensive organized list of available (i) web servers and tools to analyze protein-protein interactions and protein-protein interfaces and (ii) large-scale experimental and computational databases. For each section, we present a table listing these, with several discussed in the text. We highlight the merits and shortcomings of these for particular applications and provide two case studies to illustrate how to use a tool-combination toward specific problems. Our goal here is to provide a useful guide.

Protein-protein interaction databases

While most protein-protein interaction (PPI) databases present experimentally verified interactions, some contain computationally predicted interactions and some both. Apart from physical associations, some databases also provide indirect associations (e.g. functional gene links) while others provide interactions at the domain level. All databases grow rapidly as the pace of interaction-detection experiments, genome sequencing and the number of proteins with solved structures increase.

The Database of Interacting Proteins (DIP) is a catalogue of experimentally determined PPIs [15]. Each interacting pair contains accession codes linking to public protein databases. In October 2008, it contained 57 099 interactions between 20 244 proteins for 244 organisms. The Biomolecular Interaction Network Database (BIND) [16], is a

collection of records documenting molecular interactions. It includes high-throughput data submissions and hand-curated information gathered from the literature which covers 188 517 interactions. BIND records are created from experimental interactions published in at least one peer-reviewed journal. The Molecular Interactions Database (MINT) [17] focuses on experimentally verified protein interactions with emphasis on proteomes from mammalian organisms. In October 2008, the database contained 111 847 interactions spanning 30 organisms (25 204 mammalian, 7412 *C. elegans*, 23 375 *D. melanogaster*, 44 813 *Yeast* interactions). The Munich Information Center for Protein Sequences (MIPS) [18] is a collection of genome and protein sequence databases. It includes a *S. cerevisiae* specific protein interaction database containing 15 488 interactions (9103 physical, 6385 genetic, September, 2004), annotated through nine different high throughput analyses. The BioGRID General Repository for Interaction Datasets [19], is a comprehensive compilation of genetic and physical interactions for 22 organisms. It contains 99 104 non-redundant physical and 52 672 non-redundant genetic interactions (October, 2008). Table 1 lists some of the available PPI databases in alphabetical order. The second column gives the source organisms of the PPIs. The third column indicates the interaction detection methods used: high and low throughput experiments (EH, EL), interactions coming from the literature (Lit) and computational prediction (P). The interaction type can be direct (physical) or indirect (functional, genetic), as shown in the sixth column. The database compilation method and the characteristics provided in the table can indicate a measure of confidence in the interactions. By using this table, the most appropriate database for a specific problem can be chosen. For validated protein interactions, curated databases such as BIND, BioGRID, DIP and MINT are useful. In the absence of experimental data or to enrich the dataset with possible protein interactions, predicted protein-protein interaction can be used. Some examples of these databases are PRISM, OPHID and 3D-partner. For a specific organism, for example human, HPRD, HPID and MIPS are favored. If binding site information is needed, PSIBase and DOMINE are useful, since they indicate where the two proteins interact. However, in general, combination of several databases is preferred in protein interaction analyses.

Table 1: Databases of protein–protein interactions in alphabetical order

Web server and link	Organism	Detection type	Curation	Structure	Interaction type	Number of interactions (as of December 2008)
BIND [16] http://bind.ca	No species restriction	EH, EL, Lit	Yes	No	Both	58 266 (as of September 2004)
BioGRID [19] http://www.thebiogrid.org/	No species restriction	EH, EL, Lit	Yes	No	Both	152 150
DIP [15] http://dip.doe-mbi.ucla.edu/	No species restriction	EH	Yes	No	Direct	57 330
DOMINE [123] http://domine.utdallas.edu/cgi-bin/Domine	No species restriction	EL, P	No	Yes	Direct	20 513
HPID [124] http://wilab.inha.ac.kr/hpid/	Human	EH, EL, Lit, P	–	No	Both	N/A
HPRD [125] http://www.hprd.org/	Human	EH, EL, Lit	Yes	No	Direct	>30 000 (as of 2006)
IntAct [126] http://www.ebi.ac.uk/intact/site/index.jsf	No species restriction	EL, Lit	Yes	No	Direct	115 757
MINT [17] http://cbm.bio.uniroma2.it/mint/index.html	No species restriction	EH, EL, Lit	Yes	No	Direct	111 847
MIPS [18] http://mips.gsf.de/proj/ppi/	Mammals	EH, EL, Lit	Yes	No	Direct	>1800
OPHID [127] http://ophid.utoronto.ca/ophidv2.201/	Human	EH, EL, P	–	No	Direct	424 066
PRISM [106]	No species restriction	P	–	Yes	Direct	>100 000
PSIbase [23] http://psibase.kobic.re.kr/	No species restriction	EL	No	Yes	Direct	N/A
STRING [122] http://string.embl.de/	No species restriction	EH, Lit, P	No	No	Both	>50 million
3D-partner [128] http://3D-partner.life.nctu.edu.tw	No species restriction	P	–	Yes	Direct	N/A

The compilation methods and their characteristics are given. The source organism, detection type, whether curated or not, structure availability, interaction type and number of interactions can be found in the columns. See text for notation

INTERFACES ARE THE REGIONS WHERE PROTEINS INTERACT

The region where two protein chains come into contact is the binding site; or for both sides, an interface. In order to identify interface residues and regions that line the protein surfaces, it is essential to know the structures of the proteins. Surface residues are usually determined by calculations of the surface area which is accessible to the solvent [20–22] or distance-based calculations taking into account how close the two proteins are to each other [23–25].

In order to understand binding principles, properties which distinguish interfaces (or, binding sites) from the rest of the protein surface need to be characterized [20–22, 24–43]. Protein interfaces have greater residue conservation and tend to be planar or well packed depending on the type of interaction. The stability and specificity of the interacting protein pairs relate to the presence of H-bonds, electrostatic interactions, van der Waals forces, salt bridges and hydrophobic attractions. Although rare in protein interfaces, disulphide bonds provide rigidity and

stability in the interactions [44]. Residue composition usually differs between transient and obligate complexes: the former relying more on salt bridges and hydrogen bonds, whereas the latter more on hydrophobic interactions [21, 22, 37]. However, recent studies on transient/obligate complexes have shown that obligate interfaces are not more hydrophobic than transient ones due to the presence of water-mediated interactions [45, 46]. Physical binding is further governed by shape and chemical complementarity [37, 39, 47, 48], molecular flexibility and environmental conditions. In agreement with the broadly-accepted notion that binding and folding are similar processes [40–42], structural comparison between highly populated folds and highly populated binding sites illustrates that interface regions are generally structurally similar to cores of globular proteins [49].

Protein–protein interface databases

Protein interfaces have long been studied at both the protein level and the domain level. They have

been represented in interface data sets and deposited into databases such as PiBASE [50], InterPare [51], SCOWLP [52], 3DID [53], SCOPPI [54] and PRINT [49]. Table 2 lists some widely used interface databases. The first column lists the databases. The next columns give the attributes of the databases; which domain definition is used, where the dataset is extracted from (interface level, either chains or domains, peptidic or solvent mediated), whether interfaces are classified or not and which thresholds are used in defining the interfaces. Below, we provide some useful attributes of several of the frequently used databases.

PIBASE is a comprehensive database of structurally determined protein interfaces formed between domain pairs. Domain–domain interfaces are generated by distance calculation with a default threshold of 6.05 Å to allow water mediated contacts. The generated domain interfaces are filtered by an accessible surface area (ASA) threshold (300 Å²) and for duplicated domain–domain interactions. The dataset is characterized by geometric, physico-chemical and topological properties. PIBASE also provides the contact topology of the domains, polar versus nonpolar ASAs, *etc.* [50]. InterPare uses three methods to generate domain–domain interfaces which highly overlap [51]: (i) atomic distance calculation, (ii) ASA and (iii) Voronoi Diagram, a computational geometry method. 3DID contains domain–domain interactions annotated with GO functions. One can query the database to retrieve a network of interacting domains. For each domain–domain interaction, the server provides residue pairs with favorable interactions [53]. In the new release of the 3DID, peptide mediated interactions are also available. By defining interaction types, the authors are able to obtain the different interfaces used by a specific domain. Currently, it contains 115 559 domain–domain interfaces classified into 4887 unique interface types. 829 hand-curated domain–peptide interactions enrich the database [55]. SCOPPI is a database of structurally classified protein interfaces. To extract protein interfaces, atomic distances are used and SCOP is used for domain classification. In addition to multiple sequence alignment, SCOPPI applies structural alignment to the SCOP families. The domain–domain binding regions, named faces, are clustered by sequence and structure resulting in approximately 8400 interface types [54]. SCOWLP is a database of detailed domain–domain interfaces enriched with peptidic

Table 2: Some widely used protein–protein interface databases with their attributes, i.e. domain definition, interface level, classification and extraction methods

Web server and link	Domain def.	Interface level	Classification	Similarity	Features used in clustering	Extraction method
InterPare [51] http://interpare.kobic.re.kr/	SCOP	Domain	No	–	No	Any atom distance at ≤ 5 Å Also, ASA and Voronoi diagram methods are available
PDBSUM [118] http://www.ebi.ac.uk/pdbsum/ PIBASE [50] http://modbase.compbio.ucsf.edu/pibase/queries.html	Pfam SCOP, CATH	Chain Domain	No Yes	– Structure, topology	No Hierarchical clustering, based on inter-residue contacts, ASA, number of interface residues	N/A Any atom distance at ≤ 6.05 Å
PPIDB http://ppidb.cs.iastate.edu/ppidb/	GO	Residue	No	–	No	Both ASA and alpha carbon distance (user defined thresholds) Sum of van der Waals radii + 0.5 Å Sum of van der Waals radii + diameter of water molecule, 2.8 Å any atom distance at ≤ 5 Å
PRINT [49] http://prism.cccb.ku.edu.tr/interface ProtCom [129] http://www.ces.clemson.edu/compbio/protcom/ SCOPPI [54] http://www.scoppi.org/	SCOP, GO – SCOP	Chain Chain Domain	Yes No Yes	Structure – Sequence & structure Structure	Iterative hierarchical structural clustering No Clustering based on sequence and structure Agglomerative hierarchical clustering	
SCOWLP [52, 56] http://www.scowlp.org/	SCOP	Domain, peptide, solvent	Yes	Structure		For H-bonds 3.2 Å donor–acceptor distance; for salt bridges 4 Å distance criteria
3DID [53, 55] http://gatealoy.pcb.ub.es/3did/	Pfam, GO	Domain, peptide	Yes	Structure	Hierarchical clustering by using distance matrices of each interface.	At least 5 contacts (H-bonds, salt bridges, van der Waals interactions)

interfaces and solvent mediated contacts. Solvent mediated contact residues are named ‘wet spots’ [52]. It also classifies binding sites of each domain hierarchically leading to 9334 binding regions over 2561 domain families. 65% of the families in the database contain more than one binding site [56]. PRINT is a database of chain level interfaces extracted from the Protein Data Bank (PDB) [57]. These PPIs are clustered by structural similarity. On February 2006, there were 49512 interfaces which were clustered into 8205 unique interface structures. Interface interaction types are deposited in PRINT and annotated as crystal or biological interfaces, obligate or non-obligate, homo- or hetero-interfaces. For each individual interface, information on GO annotations, SCOP domains, interaction type, residue propensities and structural cluster are given [49]. PPIDB is a periodically updated database which differs from the others by allowing user defined thresholds to extract interface residues.

The physical and chemical properties of protein–protein interfaces

Numerous studies aim to obtain the general patterns of protein binding sites. In a pioneering work by Jones and Thornton [22], 59 different PPIs were divided into four groups: homodimers, enzyme–inhibitor complexes, antibody complexes and hetero-complexes. The complexes were characterized by six properties: size and shape, complementarity, residue interface propensities, hydrophobicity, segmentation, secondary structure and conformational changes. Homodimer interfaces preferred hydrophobic residues and had relatively large surface areas. Heterodimer complexes were less hydrophobic. The interfaces of homodimers, permanent hetero-complexes and enzyme–inhibitor complexes were more complementary than antigen–antibody complexes. In spite of significant differences, a distinct pattern for protein interfaces compared to the rest of the surfaces was not identified [22]. Larsen et al also studied protein recognition mechanisms on a dataset of 136 homodimeric proteins, observing that one-third of the interfaces have a distinguishable large hydrophobic core, polar contacts and water-mediated interactions [35]. Amino acid propensity is another important property which can be used to distinguish interaction types. Ofra and Rost explored six types of PPIs, homodimers versus heterodimers, transient versus permanent

dimers and same domain versus different domain interfaces. Using only amino acid composition and residue–contact preferences, 63–100% accuracy was achieved in interaction type prediction [58].

Structural features of interfaces

For strong interactions, good shape complementarity is crucial. The chemical character of protein interfaces is similar to the average protein surface, whereas their packing density is close to the density of the protein core. On average, the accessible surface area of interfaces is 1600 Å² [37]. Chakrabarti and Janin [28] analyzed 70 protein complexes. They considered small binding regions as single patch and large binding regions as multipatches. Bahadur *et al.* split interfaces into core and rim. The core region is buried in the interface; the rim contains solvent accessible residues [59]. Interface core regions were found to be similar to the protein interior in residue frequency; rims to protein surface.

Protein surfaces are not flat rather they are filled with pockets, crevices and indentations [60]. Cavities that remain unfilled after the complementary protein associates are unfilled pockets. Complemented pockets are the result of two well fitted protein partners [61], as in the key and lock model. Complemented pockets frequently pre-exist binding. In an analysis of 18 protein complexes with complementary pockets whose unbound structures are known, 16 of the pockets were found to pre-exist in the unbound state [24]. The pockets’ size, shape and functional group distribution are critical in protein engineering and designing new peptides/proteins that will selectively bind to these regions.

Conservation of the interfaces

Valdar and Thornton analyzed six homodimers observing that interface residues are more conserved than the rest of the surface [62]. Caffrey *et al.* extended this observation on a larger dataset [63]. However, analysis of surface and interface patches did not show a significant difference. Using their Bayesian approach to estimate residue conservation, Tseng and Liang noticed that residue substitution rates in protein cores are significantly different than those in solvent-exposed surfaces of the proteins [64]. Conservation alone is insufficient to reliably predict protein binding sites, but it can be combined with other interface properties. Tools to extract conservation profiles of surface residues can be very helpful for large-scale characterization of functional regions in proteins. ConSurf [65, 66] is a web server,

which incorporates several phylogenetic-based algorithms [67] to predict conservation scores of residues for a given protein structure. The SCORECONS web server scores residue conservation in multiple sequence alignment [68]. In the absence of structural data, SCORECONS is preferred. Otherwise, Consurf is very useful given its options and visual interface.

Energetic distribution in the interfaces: hot spots

The energetic contribution of residues in protein interfaces are not distributed uniformly. Some key ‘hot spot’ residues can contribute dominantly to the binding free energy. Experimentally, hot spot residues are identified via Alanine Scanning Mutagenesis; if a residue has a significant drop in binding affinity when mutated to alanine it is labeled a hot residue. Thorn and Bogan [69] deposited hot spots from alanine scanning mutagenesis experiments in the ASEdb database. BID [70] is another database of experimental hot spots, which collects all available experimental data related to hot spots in protein interfaces. However, these databases cover only a small portion when compared to available PPIs. In the absence of experimental data, computational methods can be used for hot spot detection [71]. These computational hot spots are either deposited in large scale databases or the methods are presented as web servers. The hot spot related databases/web servers are listed in a subsection of Table 3. The first column gives the available databases and servers; next columns list the strategy and techniques to identify hot spots, such as experimental or computational alanine scanning, and machine learning, respectively. Some of the servers are based on energy calculation [72–74]. Robetta and FoldX are two examples of energy-based hot spot prediction tools. Robetta mutates side chains to alanine and it repacks the side chains, which are within 5 Å radius sphere of the mutated residue. The rest of the protein remains unchanged. The change in the binding free energy is calculated by an energy function [75]. FoldX mutates systematically side chains between two proteins (or protein–peptide) to alanine and the rest of the complex is relaxed. Then, the change in the binding energy is calculated [76]. These predicted changes in binding energies are used to label the residues as hot spots. Molecular dynamics (MD) studies have also been used [77–79]. MD simulations of 11 protein complexes indicate that anchoring residues in protein interfaces have limited mobility and have a

tendency to be hot spots [79]. In a related work, Moreira *et al.* supported the O-Ring hypothesis, which proposes that hot spots are protected from bulk water by a surrounding rim region by using MD simulations [80]. MD analysis of computational alanine scanning of the human growth hormone receptor complex agrees well with the experimental hot spots [72]. Despite their success, MD-based methods are computationally expensive when compared to other methods. As an alternative, conservation is a property that can be used. Structurally conserved residues and hot spots correlate significantly [81–83]. These hot spots are also buried and tightly packed [82] resulting in densely packed clusters of networked hot spots called ‘hot regions’. Another residue conservation-based method is available in HotSprint. Residue conservation alone is not sufficient to identify hot spots. Some amino acids are preferred as hot spots, such as Arg, Tyr and Trp [27]. HotSprint combines the three properties, conservation, ASA and residue propensity, to detect hot spots of available protein–protein interfaces [84]. KFC predicts computational hot spots by a machine learning approach. It uses structural features such as atomic contacts and H-bonds and gives a binary answer whether a residue is a hot spot or not [85]. Recently, a neural network-based approach using interface features such as sequence profiles, solvent accessibility and evolutionary conservation has been employed in computational hot spot prediction (an adaptation of ISIS) [86]. If we compare these databases/web servers, the experimental databases ASEdb and BID are limited in size. On the other hand, the energy-based methods Robetta and FoldX are appropriate for specific interactions providing accurate estimation of free energy changes. For prediction on large-scale data KFC and Hotsprint are preferred because of their computational effectiveness and comparable performance. In general, all of the databases/servers require protein structure, except ISIS. Although it does not perform better than the computational alanine scanning method [74, 75], in the absence of structural information or binding partner it is useful for hot spots prediction [86].

Finally, although there are no strict rules, properties like binding site size, residue frequency, shape complementarity, conservation, presence of hot spots and hydrophobicity can help in predicting binding sites fairly accurately. Thus, analyses of binding sites and characterization of protein interfaces are useful,

Table 3: Web servers/tools for characterization of protein interfaces

Physical and chemical properties Web server/tool and link	Reported characteristics	Results	Visual interface
CASTp [60] http://cast.engr.uic.edu ConSurf [65] http://consurf.tau.ac.il/	Pockets & cavities Conservation info based of multiple sequence alignment or protein structure.	Residue ASA, Residue Volume Conservation score	3D (Jmol, Chime) Yes (Jmol)
GALINTER [130] (source code is available upon request)	Protein–protein interfaces	Spatial alignment according to the vector representations of van der Waals interactions and hydrogen bonds based on their geometry	No
LIGPLOT [131] http://www.biochem.ucl.ac.uk/bsm/ligplot/ligplot.html MAPPIS [132] http://bioinfo3d.cs.tau.ac.il/MAPPIS/	Non-covalent interactions of protein complexes Protein–protein binding sites	H-bonds, hydrophobic forces and their strengths, atomic ASA. Common spatial arrangements of physico-chemical properties like H-bond donor, acceptor, aliphatic, aromatic, hydrophobic.	2D 3D (Jmol)
MolSurfer [133] http://projects.villa-bosch.de/mcm/software/molurfer MultiBind [132] http://bioinfo3d.cs.tau.ac.il/MultiBind/	protein–protein and protein–DNA/RNA interfaces. Small ligand binding sites	Complementarity, hydrophobicity and electrostatic potential. Common spatial arrangements of physico-chemical properties like H-bond donor, acceptor, aliphatic, aromatic, hydrophobic.	3D (WebMol) 2D
PIC [134] http://crick.mbu.iisc.ernet.in/~PIC/	Non-covalent interactions of protein complexes	hydrogen & disulphide bonds, hydrophobic, ionic & aromatic-aromatic interactions, ASA.	3D (RasMol, Jmol)
ProFace [135] http://202.141.148.29/resources/bioinfo/interface/ ProTherm [136] http://gibk26.bse.kyutech.ac.jp/jouhou/Protherm/protherm.html PROTORP http://www.bioinformatics.sussex.ac.uk/protorp/	Protein–protein interfaces Thermodynamic parameters of wild type and mutant protein. Non-covalent interactions of protein complexes.	Interface area, surface area, fraction of non-polar atoms, non-polar interface area, residue propensity, fraction of buried atoms. Gibbs free energy change, enthalpy change, heat capacity change, transition temperature Mutated residue numbers Interface ASA, percentage polar atom in interface and on surface, planarity, eccentricity, secondary structure info, hydrogen and disulfide bonds, salt bridges, gap volume, gap volume index.	3D (Rasmol, Chime) No No
Q-SiteFinder [137] http://bmbpcu36.leeds.ac.uk/qsitefinder/ ScoreCons [68] http://www.ebi.ac.uk/thornton-srv/databases/cgi-bin/valdar/scorecons.server.pl SurfNet [138] http://www.biochem.ucl.ac.uk/~roman/surfnet/surfnet.html	Ligand binding site Conservation info based on multiple sequence alignment. Surfaces and void regions.	Site volume, protein volume Conservation score Computation of gaps, clefts, cavities and binding sites, van der Waals surfaces	3D (Chime, Mage) No 3D (Rasmol, Raster3D, Sybyl)
Hot spot databases and prediction servers	Strategy	Availability	Technique
ASEdb [27] http://nic.ucsf.edu/asedb/ BID [70] http://tsailab.tamu.edu/BID/	Experimental Experimental	Database Database	Alanine scanning Collection of several experimental techniques.
FoldX [76] http://foldx.crg.es/	Energy-based	Tool and server	Computational alanine scanning
HotSprint [84] http://prism.cccb.ku.edu.tr/hotsprint/ ISIS [95] http://cubic.bioc.columbia.edu/services/isis/ KFC [85] http://kfc.mitchell-lab.org/ Robetta [74] http://rosetta.org/submit.jsp	Conservation, accessibility, residue propensity Sequence-based Atomic contacts, residue size, H-bond Energy-based	Database Tool Server Server	Empirical formula Machine learning Machine learning Computational alanine scanning

In the first part, the web servers and tools for physical and chemical properties of protein interfaces are listed. The hot spot related databases/web servers are listed in the second part where the hot spot detection strategy, the availability and the used technique are given, respectively.

and help in improving computational prediction of protein–protein interactions and in designing drugs and inhibitors binding to interrupt these interactions. Table 3 is a comprehensive list of the servers, databases and tools, which characterize the physico-chemical properties of interfaces.

BIOLOGICAL VERSUS CRYSTAL COMPLEXES

Entries in the PDB can have artifacts of crystallization; that is, some of the complexes would not occur in solution or in their physiological states. Determining which contacts are biological and which are not is often difficult, particularly when the oligomeric state of the protein is uncertain or unknown [62]. These crystal packing interactions can cause noise in analyses. A number of studies addressed the problem of distinguishing between biological and crystal packing contacts. Below, some methods are presented to distinguish crystal and biological interfaces.

In the PDB files, BIOMT records, describing how to compute the coordinates of multimers from the explicitly specified single repeating unit, can be used to build quaternary structures. Henrick and Thornton defined crystal packing by assigning a cutoff value (400 \AA^2) in the buried surface area. Structures passing this requirement are deposited in the PQS server [87]. Crystal structures often have smaller interfaces when compared to biological interfaces. Other studies used different cutoff values to distinguish crystal contacts. Although interface size is the most important feature to identify crystal packing contacts, it is not the sole criterion. There are cases with large interface sizes, yet are biologically irrelevant; examples include the crystal contact in porcine adenylate kinase having an ASA of 2600 \AA^2 , and pancreatic ribonuclease crystals with interface size of 1800 \AA^2 [88]. Based on the assumption that biological interfaces are more conserved than non-biological interfaces, Valdar and Thornton [89] suggested that crystal interfaces can also be distinguished by residue conservation. They combined both the size and conservation information of the binding sites, achieving an accuracy of 98.3% on their training set. Overall, biological interactions are more conserved and larger than crystal ones [90, 91]. Since the amino acid composition of the protein surface differs from the interface, if the binding site composition is similar to the rest of the protein

surface, this interaction is a crystal packing candidate [90]. In the conserved domain interaction approach [92], interacting domain pairs are clustered. If two or more cluster members have similar interface locations, these interfaces possess a conserved binding mode (CBM). Conserved modes are used to distinguish biological from crystal interactions. When tested on interacting globin pairs the accuracy reached 90%. In addition, multiple feature-based approaches are also available; one of them is NOXclass, which is a machine learning-based approach. In NOXclass, six different interface properties are used to distinguish crystal versus biological contacts: interface area, interface area ratio, amino acid composition, a correlation between surface and interface region, gap volume index and conservation score of the interface. NOXclass distinguishes biological and non-biological interfaces with an accuracy of 91.8% based on three parameters (interface area, interface area ratio and area-based amino acid composition) [93]. In a recent method, called DiMoVo, Bernauer *et al.* used machine learning-based approach with Voronoi tessellation to distinguish biological and crystal complexes [94]. Table 4 lists the available servers/tools that classify PPIs as crystal or biological according to the above properties where the second column describes the strategy of the servers/tools for classification and last column gives information about the results. Among these servers/tools PQS is widely used for distinguishing crystal complexes; however, it is based on ASA and there are counter examples of crystal complexes having large interface size. Another server PreBi is appropriate for homodimers, but the current server is found to be slower than the others. NOXclass with its high accuracy, multiple features and computational effectiveness has been found to be useful. DiMoVo's performance is also compatible with other servers.

BINDING SITE PREDICTION

With no strict quantitative rules to point to the binding mechanism, characteristics of the protein interfaces such as conservation, residue propensity, residue order, geometric and electrostatic complementarity are useful. The combination of multiple protein interface features is successful in discriminating binding sites from the rest of the protein surface. Prediction methods use various features such as structure, sequence and physicochemical properties of protein interfaces [95, 96]. These features can be

Table 4: Web servers/tools for classification of protein–protein interactions

Web server/tool and link	Strategy	Result
CPASS [139] http://bionmr-cl.unl.edu/CPASS.OV/CPASS.htm DiMoVo [94] http://cgal.inria.fr/DiMoVo/	Comparison of ligand-defined active sites. Machine Learning-based classification with Voronoi tessellation using interface area, residue and contact frequencies, Voronoi volumes, etc.	Function assignment Biological versus crystal
NOXclass [93] http://noxclass.bioinf.mpi-inf.mpg.de/	SVM-based classification using interface area, ratio of interface area to surface area, amino-acid composition, correlation between interface and surface, gap volume index, conservation	Percentage whether the complex is obligate, non-obligate or crystal packing.
PINS [140] http://pins.ornl.gov/	Random forest classifier using residue propensity and contacts, interface area, disulphide and H-bonds, conservation, packing density, etc.	Biological versus crystal
PISA[141] http://www.ebi.ac.uk/msd-srv/prot.int/pistart.html	Free energy calculation	Biological versus crystal
Pita [142] http://www.ebi.ac.uk/thornton-srv/databases/pita/	Scoring based on crystal symmetry operators.	Biological versus crystal
PQS [87] http://www.ebi.ac.uk/msd-srv/pqs/	Interface size, symmetry operators to form complex	Biological versus crystal
PreBi [143] http://pre-s.protein.osaka-u.ac.jp/~prebi/	Degree of shape and physicochemical complementarity	Biological versus crystal
ProFunc [144] http://www.ebi.ac.uk/thornton-srv/databases/ProFunc/	Sequence and structure comparison	Functional annotation of proteins

The columns describe the strategy of the servers/tools for the classification and provide information relating to the type of the obtained results, respectively.

utilized in different methods such as machine learning-based and empirical scoring functions. Most of these prediction methods use known binding sites for parameterization or training. Prediction also depends on the choice of the training dataset: reliable, diverse and non-redundant gold standard datasets are crucial for a successful training of a prediction method [97]. Table 5 lists several servers to predict binding sites. The first column lists the binding site prediction servers. The second column provides the binding site prediction method. In the third column, the binding site properties that are analyzed for the predictions are given. Below, we provide a brief review of some of these servers.

ProMate is a scoring function-based approach to identify the location of protein–protein binding sites [98]. The algorithm was trained on a heteromeric transient protein–protein complexes, thus it is most suitable for predicting such interaction interfaces. Amino acid propensities, residue conservation, pairwise amino acid distribution, temperature factors and geometric properties are extracted and optimized to choose the best combination. The location of the interface for about 70% of the proteins was predicted correctly [99]. Another prediction algorithm, PINUP, combines side chain energy score, conservation score and residue interface propensity reaching 44.5% prediction accuracy. Bradford *et al.* use a support vector machine (SVM) approach combined with surface patch analysis to predict

protein–protein binding sites. The SVM is trained on binding site properties (surface shape, conservation, electrostatic potential, hydrophobicity, residue interface propensity and solvent accessible surface area) to distinguish interacting patches from non-interacting patches. PPI-Pred correctly predicts binding site location in 76% of the 180 dataset proteins [100]. Another algorithm that makes use of patch score calculation to predict binding sites is SHARP2. Six binding properties scores (solvation potential, hydrophobicity, accessible surface area, residue interface propensity, planarity and protrusion) are combined for prediction [101].

There are two neural networks-based web servers: SPPIDER, which is based on solvent accessibility [102] and cons-PPISP based on sequence information and solvent accessibility [103]. Zhou and Qin combined the raw scores of cons-PPISP, PINUP and ProMate web servers and built a meta-web server, meta-PPISP with increased accuracy [104]. When the performances of the web servers are compared on two different sets (Enz35 dataset and CAPRI targets), the same rankings are derived (from top to down meta-PPISP, PINUP, ProMate, cons-PPISP, SPIDDER and PPI-Pred). meta-PPISP outperforms other servers [104]. Different from the other servers, PRISM predicts the binding site of two proteins using known template interfaces. It searches for the left and right binding sites of the template interfaces on the two

Table 5: Servers for binding site prediction

Web server	Method	Binding site properties
cons-PPISP [I03] http://pipe.scs.fsu.edu/ppisp.html	Neural network	Solvent accessibility and sequence information
Firestar [I45] http://firedb.bioinfo.cnio.es/Php/FireStar.php	Scoring function	Sequence and structural alignments
InterProSurf [I46] http://curie.utmb.edu/	Scoring function	Solvent accessible surface area, propensity of interface residues
Meta-PPISP [I04] http://pipe.scs.fsu.edu/meta-ppisp.html	Neural network	Combining scores derived from three other servers; ProMate, PINUP, cons-PPISP
Patch Finder Plus [I47] http://pfp.technion.ac.il/	Neural network	Surface concavity, surface area, amino acid frequency and composition, hydrogen-bonding potential, sequence conservation
PINUP [98] http://sparks.informatics.iupui.edu/PINUP/	Empirical scoring function	Side chain energy score, conservation score and residue interface propensity
PI ² PE [I48] http://pipe.scs.fsu.edu/	Neural network	Combining three servers, WESA [I49], cons-PPISP [I03], DISPLAR [I50]
PPI-Pred [I00] http://bioinformatics.leeds.ac.uk/ppi-pred	Support vector machine	Conservation, electrostatic potential, hydrophobicity, propensity of interface residues, surface shape and solvent accessible surface area
PRISM [I06] http://prism.ccbb.ku.edu.tr/prism/	Scoring function	Geometric complementarity, conservation
ProMate [99] http://biportal.weizmann.ac.il/promate/	Scoring function	Amino-acid propensities, pairwise amino-acid distribution, residue conservation and geometric properties
SHARP ² [I01] http://www.bioinformatics.sussex.ac.uk/SHARP2/sharp2.html	Patch score calculation	Solvation potential, hydrophobicity, accessible surface area, residue interface propensity, planarity and protrusion
SiteEngines [I51] http://bioinfo3d.cs.tau.ac.il/SiteEngine/ http://bioinfo3d.cs.tau.ac.il/I2I-SiteEngine/	Scoring function	Structural matching, physico-chemical properties and shapes
SPPIDER [I02] http://sppider.cchmc.org/	Neural network	Solvent accessibility

In the columns, the method and the binding site properties used in the prediction are given, respectively.

target proteins by structural matching. If one target matches the left partner and the other matches the right of the same interface template, these two targets are predicted to interact through this region [105, 106].

PROTEIN-PROTEIN DOCKING

Docking is the procedure to find the best bound state for given 3-D structures of two (or more) proteins. The docking problem is difficult since there are many potential ways in which proteins can interact, and protein surfaces are flexible. Computational methods were developed to discover the best fit between two proteins and these methods are presented as docking servers/software packages. Several methods ranked well in the CAPRI (<http://capri.ebi.ac.uk>) community competition. Among these, Z-Dock [107], Gramm-X [108], DOT [109] and ClusPro [110] perform global searches based on fast Fourier transform (FFT) correlation approach. Although the FFT-based initial global search methods are similar, the refinement and filtering steps differ for each server. For example, ClusPro [110] first selects the docked conformations with favorable desolvation and electrostatics properties, and then these filtered structures are clustered

using a hierarchical pairwise RMSD algorithm. Clustering is followed by energy minimization step and refinement by SmoothDock [111]. On the other hand, the top predictions of Gramm-X [108] are subjected to the conjugate gradient minimization with a smoothed Lennard-Jones potential. For the resulting minimized predictions, soft Lennard-Jones potential, evolutionary conservation of predicted interface, statistical residue-residue preference, volume of the minimum, empirical binding free energy and atomic contact energy are calculated and used for the application of the SVM filter trained on a benchmark set [112]. The retained predictions are re-scored by a weighted sum of these potential terms. Different from these FFT correlation approaches, PatchDock and SymmDock [113, 114] employ the geometric hashing method as the initial search process. The docked conformations are ranked according to a geometric shape complementarity score. Being computationally faster than other web servers, PatchDock also provides the user an option for submitting potential binding sites of the receptor and ligand. If the binding sites are known, these can yield more accurate results.

In addition to those docking servers that perform global searches, RosettaDock [115] performs a local docking search requiring a reasonable starting

Table 6: Servers for protein–protein docking which ranked well in the CAPRI competition

Web server/software and link	Docking method	Filtering and refinement
BDOCK [I52] http://www.biotech.tudresden.de/~bhuang/bdock/bdock.html	FFT correlation based on shape complementarity, degree of burial and conservation	Altering the docking solutions with a scoring function
ClusPro [I10] http://nrc.bu.edu/cluster/	FFT correlation using DOT [I09]	Filtering with empirical potential and clustering, refinement by SmoothDock [I11]
DOT [I09] http://www.sdsc.edu/CCMS/DOT/	FFT correlation based on electrostatics and shape complementarity	Refinement by energy minimization
FireDock [I53] http://bioinfo3d.cs.tau.ac.il/FireDock/	None (refinement server)	Refinement using an energy function
GRAMMX [I08] http://vakser.bioinformatics.ku.edu/resources/gramm/grammx	FFT correlation based on shape complementarity, hydrophobicity and smoothed potentials	Clustering and knowledge-based scoring
HADDOCK [I54] http://www.nmr.chem.uu.nl/haddock/	Data-driven docking approach based on biochemical and/or biophysical interaction data	None
HEX [I55] http://www.csd.abdn.ac.uk/hex/	Spherical polar Fourier correlations	None
MolFit [I56] http://www.weizmann.ac.il/ChemicalResearchSupport/molfit/home.html	FFT correlation based on chemical and shape complementarity	Clustering of the predicted conformations
PatchDock [I14] http://bioinfo3d.cs.tau.ac.il/PatchDock/	Geometric hashing and pose-clustering	Ranking according to a geometric shape complementarity score
PyDock [I57] http://mmb.pcb.ub.es/PyDock/	FFT based on electrostatics and desolvation energy	Ranking using an energy function
RosettaDock [I15] http://rosettadock.graylab.jhu.edu/	Local docking by Monte Carlo search	Ranking using an energy function, clustering
ZDOCK [I07] http://zlab.bu.edu/zdock/index.shtml	FFT correlation based on shape complementarity, desolvation energy and electrostatics	Refinement by energy minimization
3D-Dock [I58] http://www.sbg.bio.ic.ac.uk/docking/	FFT correlation using FTDock [I59]	Clustering, refinement of side-chains using Multidock [I59]

Information relating to the docking method and filtering/refinement stages can be found in the columns, respectively.

conformation. The starting conformation may well be created by any of the servers listed above. The submitted initial docking predictions are refined by a Monte Carlo approach including rigid-body moves and side-chain optimization. A list of selected docking servers/software packages is provided in Table 6. The first column lists the docking servers/softwares. The second and third columns give information about the docking method and filtering/refinement stages, respectively.

CASE STUDIES

p53–53BP2 Interface

To provide practical examples that reflect the data on protein interactions and interface classification, we illustrate how a database of protein interfaces from the ones explained in the text is used for characterization of the p53–53BP2 protein interface. p53 is one of the major tumor suppressor proteins, which interacts with many other proteins, and 53BP2 is the binding protein partner of p53. We start by querying the PRINT database with this interface, pdbID 1ycs. 1ycs has only one interface, which is formed between chains A (p53) and B (53BP2) [49]. Figure 1




Figure 1: An example of protein–protein interfaces (interface region between p53 and its binding protein 53BP2).

illustrates the complex and highlights the interface between chain A and chain B. The interface region is illustrated in sphere representation. The rest of the protein is drawn as ribbon diagram using VMD [116]. The coordinates of the interface residues can be downloaded from the PRINT database in PDB format. PRINT provides information on this protein interface (1ycsAB) such as interface area (calculated by Naccess [117] as 1500 Å²), gap volume (calculated by Surfnet as 3304 Å³). PRINT also provides the




Figure 2: (A) HRAS interaction network visualized by STRING [122]. (B) The predicted interacting residues of HRAS (Ibkd.R) using SPPIDER and PPI-Pred are displayed as spheres in white and silver color, respectively. The black spheres represent the residues that are common to both web servers. Predictions of SPPIDER and PPI-Pred web servers overlap both Switch I and Switch II regions of HRAS.

interaction type (using NOXclass). 1ycsAB is found to be a biological interface with a probability of 85% and non-obligate with a probability of 76%. Further, PDBsum [118] indicates that there are nine H-bonds between the chains. HotSpring gives the average conservation score of this interface as six highlighting the computational hot spots, suggesting that this interface is moderately conserved [84].

Interactions of HRAS

Ras proteins are key regulators of eukaryotic cell growth, functioning in signal transduction pathways. They bind GDP/GTP and have intrinsic GTPase activity. Experimental evidence illustrates the importance of HRAS switch I (residues 25–40) and switch II (residues 57–75) regions in binding to its interaction partners [119–121]. With the goal of characterizing this protein and its network interactions, the interactions of HRAS are obtained using STRING [122], which is a database of known and predicted PPIs. STRING integrates interaction data from high-throughput experiments (DIP, BIND, MINT and GRID databases), co-expression, genomic context and prior knowledge. Its summary network for the experimentally validated interactions is given in Figure 2A.

In order to locate the binding regions responsible for interactions in the network, several binding site prediction web servers can be used. PPI-Pred [100] provides a list of probable interface residues in the three highest scoring patches. The highest scoring patch successfully overlaps both the switch I and

switch II regions of HRAS. The predicted patch is displayed in Figure 2B. The predicted best patch of SHARP2 [101], which uses patch score calculation as the prediction method, corresponds to the switch I region of HRAS. The two web servers which use neural networks in the predictions are SPPIDER [102] and cons-PPISP [103]. Cons-PPISP prediction includes switch I region, whereas SPPIDER includes both switch I and switch II regions of HRAS. The predicted interacting residues with SPPIDER are shown in Figure 2B.

Key Points

- Characterization and prediction of binding sites are crucial to studies of protein interactions. This review provides a comprehensive and organized list of the available databases and web servers of protein binding sites and their characteristics outlining how the tool was constructed, its advantages and drawbacks. In addition, it further provides examples how to use tool-combinations toward particular goals.
- These resources can be used to: (i) analyze the physico-chemical properties of interfaces and differentiate between biological complexes and crystal contacts and (ii) predict binding sites in protein structures and of the docked structures of two individual proteins.
- In conclusion, a combination of such resources is expected to help biologists explore protein interactions, relate these to cellular processes, and design drugs to target the 'druggable' sites.

Acknowledgements

The content of this publication does not necessarily reflect the views or policies of the Department of Health and Human Services, nor does mention of trade names, commercial products or organizations imply endorsement by the U.S. Government.

FUNDING

Turkish Academy of Sciences Distinguished Young Investigator Award (to O.K.); the Scientific and Technological Research Council of Turkey Fellowship (to N.T.). Federal funds from the National Cancer Institute; National Institutes of Health; (under contract number N01-CO-12400). Intramural Research Program of the National Institutes of Health; National Cancer Institute; Center for Cancer Research (partial).

References

- Lander ES, Linton LM, Birren B, *et al.* Initial sequencing and analysis of the human genome. *Nature* 2001;**409**: 860–921.
- Ito T, Chiba T, Ozawa R, *et al.* A comprehensive two-hybrid analysis to explore the yeast protein interactome. *Proc Natl Acad Sci USA* 2001;**98**:4569–74.
- Uetz P, Giot L, Cagney G, *et al.* A comprehensive analysis of protein–protein interactions in *Saccharomyces cerevisiae*. *Nature* 2000;**403**:623–7.
- Pelletier JN, Arndt KM, Pluckthun A, *et al.* An in vivo library-versus-library selection of optimized protein–protein interactions. *Nat Biotechnol* 1999;**17**:683–90.
- Tarassov K, Messier V, Landry CR, *et al.* An in vivo map of the yeast protein interactome. *Science* 2008;**320**:1465–70.
- Rigaut G, Shevchenko A, Rutz B, *et al.* A generic protein purification method for protein complex characterization and proteome exploration. *Nat Biotechnol* 1999;**17**:1030–32.
- Smith GP. Filamentous fusion phage: novel expression vectors that display cloned antigens on the virion surface. *Science* 1985;**228**:1315–17.
- Eisen MB, Spellman PT, Brown PO, *et al.* Cluster analysis and display of genome-wide expression patterns. *Proc Natl Acad Sci USA* 1998;**95**:14863–68.
- MacBeath G, Schreiber SL. Printing proteins as microarrays for high-throughput function determination. *Science* 2000;**289**:1760–3.
- Tong AH, Evangelista M, Parsons AB, *et al.* Systematic genetic analysis with ordered arrays of yeast deletion mutants. *Science* 2001;**294**:2364–8.
- Golemis E. *Protein–Protein Interactions. A Molecular Cloning Manual*. New York: Cold Spring harbor Press, 2002.
- Shoemaker BA, Panchenko AR. Deciphering protein–protein interactions. Part I. Experimental techniques and databases. *PLoS Comput Biol* 2007;**3**:e42.
- Yan Y, Marriott G. Analysis of protein interactions using fluorescence technologies. *Curr Opin Chem Biol* 2003;**7**:635–40.
- Karlsson R. SPR for molecular interaction analysis: a review of emerging application areas. *J Mol Recognit* 2004;**17**: 151–61.
- Xenarios I, Salwinski L, Duan XJ, *et al.* DIP, the Database of interacting proteins: a research tool for studying cellular networks of protein interactions. *Nucleic Acids Res* 2002;**30**: 303–5.
- Bader GD, Betel D, Hogue CW. BIND: the biomolecular interaction network database. *Nucleic Acids Res* 2003;**31**: 248–50.
- Chatr-aryamontri A, Ceol A, Palazzi LM, *et al.* MINT: the Molecular INTeraction database. *Nucleic Acids Res* 2007;**35**(Database issue):D572–4.
- Mewes HW, Frishman D, Guldener U, *et al.* MIPS: a database for genomes and protein sequences. *Nucleic Acids Res* 2002;**30**:31–4.
- Stark C, Breitkreutz BJ, Reguly T, *et al.* BioGRID: a general repository for interaction datasets. *Nucleic Acids Res* 2006;**34**(Database issue):D535–9.
- Jones S, Marin A, Thornton JM. Protein domain interfaces: characterization and comparison with oligomeric protein interfaces. *Protein Eng* 2000;**13**:77–82.
- Jones S, Thornton JM. Principles of protein–protein interactions. *Proc Natl Acad Sci USA* 1996;**93**:13–20.
- Jones S, Thornton JM. Analysis of protein–protein interaction sites using surface patches. *J Mol Biol* 1997;**272**: 121–32.
- Gong S, Yoon G, Jang I, *et al.* PSIBase: a database of protein structural interactome map (PSIMAP). *Bioinformatics* 2005;**21**:2541–3.
- Keskin O, Tsai CJ, Wolfson H, *et al.* A new, structurally nonredundant, diverse data set of protein–protein interfaces and its implications. *Protein Sci* 2004;**13**:1043–55.
- Tsai CJ, Lin SL, Wolfson HJ, *et al.* A dataset of protein–protein interfaces generated with a sequence–order-independent comparison technique. *J Mol Biol* 1996;**260**: 604–20.
- Argos P. An investigation of protein subunit and domain interfaces. *Protein Eng* 1988;**2**:101–13.
- Bogan AA, Thorn KS. Anatomy of hot spots in protein interfaces. *J Mol Biol* 1998;**280**:1–9.
- Chakrabarti P, Janin J. Dissecting protein–protein recognition sites. *Proteins* 2002;**47**:334–43.
- Chothia C, Janin J. Principles of protein–protein recognition. *Nature* 1975;**256**:705–8.
- Clackson T, Wells JA. A hot spot of binding energy in a hormone–receptor interface. *Science* 1995;**267**:383–6.
- Janin J, Chothia C. The structure of protein–protein recognition sites. *J Biol Chem* 1990;**265**:16027–30.
- Keskin O, Ma B, Rogale K, *et al.* Protein–protein interactions: organization, cooperativity and mapping in a bottom-up Systems Biology approach. *Phys Biol* 2005;**2**: S24–35.
- Keskin O, Nussinov R. Favorable scaffolds: proteins with different sequence, structure and function may associate in similar ways. *Protein Eng Des Sel* 2005;**18**:11–24.
- Korn AP, Burnett RM. Distribution and complementarity of hydrophobicity in multisubunit proteins. *Proteins* 1991;**9**:37–55.
- Larsen TA, Olson AJ, Goodsell DS. Morphology of protein–protein interfaces. *Structure* 1998;**6**:421–7.
- Lijnzaad P, Berendsen HJ, Argos P. Hydrophobic patches on the surfaces of protein structures. *Proteins* 1996;**25**:389–97.
- Lo Conte L, Chothia C, Janin J. The atomic structure of protein–protein recognition sites. *J Mol Biol* 1999;**285**: 2177–98.

38. Sheinerman FB, Honig B. On the role of electrostatic interactions in the design of protein-protein interfaces. *J Mol Biol* 2002;**318**:161-77.
39. Sheinerman FB, Norel R, Honig B. Electrostatic aspects of protein-protein interactions. *Curr Opin Struct Biol* 2000;**10**:153-9.
40. Tsai CJ, Lin SL, Wolfson HJ, et al. Studies of protein-protein interfaces: a statistical analysis of the hydrophobic effect. *Protein Sci* 1997;**6**:53-64.
41. Tsai CJ, Nussinov R. Hydrophobic folding units at protein-protein interfaces: implications to protein folding and to protein-protein association. *Protein Sci* 1997;**6**:1426-37.
42. Tsai CJ, Xu D, Nussinov R. Structural motifs at protein-protein interfaces: protein cores versus two-state and three-state model complexes. *Protein Sci* 1997;**6**:1793-805.
43. Xu W, Regnier FE. Protein-protein interactions on weak-cation-exchange sorbent surfaces during chromatographic separations. *J Chromatogr A* 1998;**828**:357-64.
44. De S, Krishnadev O, Srinivasan N, et al. Interaction preferences across protein-protein interfaces of obligatory and non-obligatory components are different. *BMC Struct Biol* 2005;**5**:15.
45. Rodier F, Bahadur RP, Chakrabarti P, et al. Hydration of protein-protein interfaces. *Proteins* 2005;**60**:36-45.
46. Teyra J, Pisabarro MT. Characterization of interfacial solvent in protein complexes and contribution of wet spots to the interface description. *Proteins* 2007;**67**:1087-95.
47. Lawrence MC, Colman PM. Shape complementarity at protein/protein interfaces. *J Mol Biol* 1993;**234**:946-50.
48. Xu D, Lin SL, Nussinov R. Protein binding versus protein folding: the role of hydrophilic bridges in protein associations. *J Mol Biol* 1997;**265**:68-84.
49. Tuncbag N, Guroy A, Guney E, et al. Architectures and functional coverage of protein-protein interfaces. *J Mol Biol* 2008;**381**:785-802.
50. Davis FP, Sali A. PIBASE: a comprehensive database of structurally defined protein interfaces. *Bioinformatics* 2005;**21**:1901-7.
51. Gong S, Park C, Choi H, et al. A protein domain interaction interface database: InterPare. *BMC Bioinformatics* 2005;**6**:207.
52. Teyra J, Doms A, Schroeder M, et al. SCOWLP: a web-based database for detailed characterization and visualization of protein interfaces. *BMC Bioinformatics* 2006;**7**:104.
53. Stein A, Russell RB, Aloy P. 3did: interacting protein domains of known three-dimensional structure. *Nucleic Acids Res* 2005;**33**(Database issue):D413-7.
54. Winter C, Henschel A, Kim WK, et al. SCOPPI: a structural classification of protein-protein interfaces. *Nucleic Acids Res* 2006;**34**(Database issue):D310-4.
55. Stein A, Panjkovich A, Aloy P. 3did Update: domain-domain and peptide-mediated interactions of known 3D structure. *Nucleic Acids Res* 2009;**37**(Database issue):D300-4.
56. Teyra J, Paszkowski-Rogacz M, Anders G, et al. SCOWLP classification: structural comparison and analysis of protein binding regions. *BMC Bioinformatics* 2008;**9**:9.
57. Berman HM, Westbrook J, Feng Z, et al. The protein data bank. *Nucleic Acids Res* 2000;**28**:235-42.
58. Ofra Y, Rost B. Analysing six types of protein-protein interfaces. *J Mol Biol* 2003;**325**:377-87.
59. Bahadur RP, Chakrabarti P, Rodier F, et al. Dissecting subunit interfaces in homodimeric proteins. *Proteins* 2003;**53**:708-19.
60. Dundas J, Ouyang Z, Tseng J, et al. CASTp: computed atlas of surface topography of proteins with structural and topographical mapping of functionally annotated residues. *Nucleic Acids Res* 2006;**34**(Web server issue):W116-8.
61. Li X, Keskin O, Ma B, et al. Protein-protein interactions: hot spots and structurally conserved residues often locate in complemented pockets that pre-organized in the unbound states: implications for docking. *J Mol Biol* 2004;**344**:781-95.
62. Valdar WS, Thornton JM. Protein-protein interfaces: analysis of amino acid conservation in homodimers. *Proteins* 2001;**42**:108-24.
63. Caffrey DR, Somaroo S, Hughes JD, et al. Are protein-protein interfaces more conserved in sequence than the rest of the protein surface? *Protein Sci* 2004;**13**:190-202.
64. Tseng YY, Liang J. Estimation of amino acid residue substitution rates at local spatial regions and application in protein function inference: a Bayesian Monte Carlo approach. *Mol Biol Evol* 2006;**23**:421-36.
65. Glaser F, Pupko T, Paz I, et al. ConSurf: identification of functional regions in proteins by surface-mapping of phylogenetic information. *Bioinformatics* 2003;**19**:163-4.
66. Glaser F, Rosenberg Y, Kessel A, et al. The ConSurf-HSSP database: the mapping of evolutionary conservation among homologs onto PDB structures. *Proteins* 2005;**58**:610-7.
67. Pupko T, Bell RE, Mayrose I, et al. Rate4Site: an algorithmic tool for the identification of functional regions in proteins by surface mapping of evolutionary determinants within their homologues. *Bioinformatics* 2002;**18**(Suppl. 1):S71-7.
68. Valdar WS. Scoring residue conservation. *Proteins* 2002;**48**:227-41.
69. Thorn KS, Bogan AA. ASEdb: a database of alanine mutations and their effects on the free energy of binding in protein interactions. *Bioinformatics* 2001;**17**:284-5.
70. Fischer TB, Arunachalam KV, Bailey D, et al. The binding interface database (BID): a compilation of amino acid hot spots in protein interfaces. *Bioinformatics* 2003;**19**:1453-4.
71. DeLano WL. Unraveling hot spots in binding interfaces: progress and challenges. *Curr Opin Struct Biol* 2002;**12**:14-20.
72. Gao Y, Wang R, Lai L. Structure-based method for analyzing protein-protein interfaces. *J Mol Model* 2004;**10**:44-54.
73. Guerois R, Nielsen JE, Serrano L. Predicting changes in the stability of proteins and protein complexes: a study of more than 1000 mutations. *J Mol Biol* 2002;**320**:369-87.
74. Kortemme T, Baker D. A simple physical model for binding energy hot spots in protein-protein complexes. *Proc Natl Acad Sci USA* 2002;**99**:14116-21.
75. Kortemme T, Kim DE, Baker D. Computational alanine scanning of protein-protein interfaces. *Sci STKE* 2004;**2004**:pl2.
76. Schymkowitz J, Borg J, Stricher F, et al. The FoldX web server: an online force field. *Nucleic Acids Res* 2005;**33**(Web Server issue):W382-8.
77. Gonzalez-Ruiz D, Gohlke H. Targeting protein-protein interactions with small molecules: challenges and perspectives for computational binding epitope detection and ligand finding. *Curr Med Chem* 2006;**13**:2607-25.

78. Huo S, Massova I, Kollman PA. Computational alanine scanning of the 1:1 human growth hormone–receptor complex. *J Comput Chem* 2002;**23**:15–27.
79. Rajamani D, Thiel S, Vajda S, *et al.* Anchor residues in protein–protein interactions. *Proc Natl Acad Sci U S A* 2004;**101**:11287–92.
80. Moreira IS, Fernandes PA, Ramos MJ. Hot spot occlusion from bulk water: a comprehensive study of the complex between the lysozyme HEL and the antibody FVD1.3. *J Phys Chem B* 2007;**111**:2697–706.
81. Hu Z, Ma B, Wolfson H, *et al.* Conservation of polar residues as hot spots at protein interfaces. *Proteins* 2000;**39**:331–42.
82. Keskin O, Ma B, Nussinov R. Hot regions in protein–protein interactions: the organization and contribution of structurally conserved hot spot residues. *J Mol Biol* 2005;**345**:1281–94.
83. Ma B, Elkayam T, Wolfson H, *et al.* Protein–protein interactions: structurally conserved residues distinguish between binding sites and exposed protein surfaces. *Proc Natl Acad Sci U S A* 2003;**100**:5772–7.
84. Guney E, Tuncbag N, Keskin O, *et al.* HotSprint: database of computational hot spots in protein interfaces. *Nucleic Acids Res* 2008;**36**(Database issue):D662–6.
85. Darnell SJ, LeGault L, Mitchell JC. KFC Server: interactive forecasting of protein interaction hot spots. *Nucleic Acids Res* 2008;**36**(Web server issue):265–9.
86. Ofra Y, Rost B. Protein–protein interaction hotspots carved into sequences. *PLoS Comput Biol* 2007;**3**:e119.
87. Henrick K, Thornton JM. PQS: a protein quaternary structure file server. *Trends Biochem Sci* 1998;**23**:358–61.
88. Janin J. Specific versus non-specific contacts in protein crystals. *Nat Struct Biol* 1997;**4**:973–4.
89. Valdar WS, Thornton JM. Conservation helps to identify biologically relevant crystal contacts. *J Mol Biol* 2001;**313**:399–416.
90. Carugo O, Argos P. Protein–protein crystal-packing contacts. *Protein Sci* 1997;**6**:2261–3.
91. Janin J, Rodier F. Protein–protein interaction at crystal contacts. *Proteins* 1995;**23**:580–7.
92. Shoemaker BA, Panchenko AR, Bryant SH. Finding biologically relevant protein domain interactions: conserved binding mode analysis. *Protein Sci* 2006;**15**:352–61.
93. Zhu H, Domingues FS, Sommer I, *et al.* NOXclass: prediction of protein–protein interaction types. *BMC Bioinformatics* 2006;**7**:27.
94. Bernauer J, Bahadur RP, Rodier F, *et al.* DiMoVo: a Voronoi tessellation-based method for discriminating crystallographic and biological protein–protein interactions. *Bioinformatics* 2008;**24**:652–8.
95. Ofra Y, Rost B. ISIS: interaction sites identified from sequence. *Bioinformatics* 2007;**23**:13–6.
96. Res I, Mihalek I, Lichtarge O. An evolution based classifier for prediction of protein interfaces without using protein structures. *Bioinformatics* 2005;**21**:2496–501.
97. Keskin O, Tuncbag N, Gursoy A. Characterization and prediction of protein interfaces to infer protein–protein interaction networks. *Curr Pharm Biotechnol* 2008;**9**:67–76.
98. Liang S, Zhang C, Liu S, *et al.* Protein binding site prediction using an empirical scoring function. *Nucleic Acids Res* 2006;**34**:3698–707.
99. Neuvirth H, Raz R, Schreiber G. ProMate: a structure based prediction program to identify the location of protein–protein binding sites. *J Mol Biol* 2004;**338**:181–99.
100. Bradford JR, Westhead DR. Improved prediction of protein–protein binding sites using a support vector machines approach. *Bioinformatics* 2005;**21**:1487–94.
101. Murakami Y, Jones S. SHARP2: protein–protein interaction predictions using patch analysis. *Bioinformatics* 2006;**22**:1794–5.
102. Porollo A, Meller J. Prediction-based fingerprints of protein–protein interactions. *Proteins* 2007;**66**:630–45.
103. Zhou HX, Shan Y. Prediction of protein interaction sites from sequence profile and residue neighbor list. *Proteins* 2001;**44**:336–43.
104. Zhou HX, Qin S. Interaction-site prediction for protein complexes: a critical assessment. *Bioinformatics* 2007;**23**:2203–9.
105. Aytuna AS, Gursoy A, Keskin O. Prediction of protein–protein interactions by combining structure and sequence conservation in protein interfaces. *Bioinformatics* 2005;**21**:2850–5.
106. Ogmen U, Keskin O, Aytuna AS, *et al.* PRISM: protein interactions by structural matching. *Nucleic Acids Res* 2005;**33**(Web Server issue):W331–6.
107. Chen R, Weng Z. Docking unbound proteins using shape complementarity, desolvation, and electrostatics. *Proteins* 2002;**47**:281–94.
108. Tovchigrechko A, Vakser IA. GRAMM-X public web server for protein–protein docking. *Nucleic Acids Res* 2006;**34**(Web Server issue):W310–4.
109. Mandell JG, Roberts VA, Pique ME, *et al.* Protein docking using continuum electrostatics and geometric fit. *Protein Eng* 2001;**14**:105–13.
110. Comeau SR, Gatchell DW, Vajda S, *et al.* ClusPro: a fully automated algorithm for protein–protein docking. *Nucleic Acids Res* 2004;**32**(Web server issue):W96–9.
111. Camacho CJ. Modeling side-chains using molecular dynamics improve recognition of binding region in CAPRI targets. *Proteins* 2005;**60**:245–51.
112. Chen R, Mintseris J, Janin J, *et al.* A protein–protein docking benchmark. *Proteins* 2003;**52**:88–91.
113. Schneidman-Duhovny D, Inbar Y, Nussinov R, *et al.* Geometry-based flexible and symmetric protein docking. *Proteins* 2005;**60**:224–31.
114. Schneidman-Duhovny D, Inbar Y, Nussinov R, *et al.* PatchDock and SymmDock: servers for rigid and symmetric docking. *Nucleic Acids Res* 2005;**33**(Web server issue):W363–7.
115. Lyskov S, Gray JJ. The RosettaDock server for local protein–protein docking. *Nucleic Acids Res* 2008;**36**(Web Server issue):233–8.
116. Humphrey W, Dalke A, Schulten K. VMD - Visual Molecular Dynamics. *J Mol Graph* 1996;**14**:33–8.
117. Hubbard SJ, Thornton JM. **NACCESS**. In: Department of Biochemistry and Molecular Biology, University College, London; 1993.
118. Laskowski RA. PDBsum: summaries and analyses of PDB structures. *Nucleic Acids Res* 2001;**29**:221–2.
119. Hall BE, Yang SS, Boriack-Sjodin PA, *et al.* Structure-based mutagenesis reveals distinct functions for Ras switch 1 and switch 2 in Sos-catalyzed guanine nucleotide exchange. *J Biol Chem* 2001;**276**:27629–37.

120. Hiwasa T, Kasama M, Nakadai T, *et al.* Loss of Raf-1-binding activity of v-Ha-Ras by the deletion of amino acid residues 64–72 and 143–151. *Cell Signal* 1996;**8**:393–6.
121. Spoerner M, Herrmann C, Vetter IR, *et al.* Dynamic properties of the Ras switch I region and its importance for binding to effectors. *Proc Natl Acad Sci USA* 2001;**98**:4944–9.
122. von Mering C, Jensen LJ, Kuhn M, *et al.* STRING 7 – recent developments in the integration and prediction of protein interactions. *Nucleic Acids Res* 2007;**35** (Database issue):D358–62.
123. Raghavachari B, Tasneem A, Przytycka TM, *et al.* DOMINE: a database of protein domain interactions. *Nucleic Acids Res* 2008;**36**(Database issue):D656–61.
124. Han K, Park B, Kim H, *et al.* HPID: the human protein interaction database. *Bioinformatics* 2004;**20**:2466–70.
125. Peri S, Navarro JD, Kristiansen TZ, *et al.* Human protein reference database as a discovery resource for proteomics. *Nucleic Acids Res* 2004;**32**(Database issue):D497–501.
126. Hermjakob H, Montecchi-Palazzi L, Lewington C, *et al.* IntAct: an open source molecular interaction database. *Nucleic Acids Res* 2004;**32**(Database issue):D452–5.
127. Brown KR, Jurisica I. Online predicted human interaction database. *Bioinformatics* 2005;**21**:2076–82.
128. Chen YC, Lo YS, Hsu WC, *et al.* 3D-partner: a web server to infer interacting partners and binding models. *Nucleic Acids Res* 2007;**35**(Web server issue):W561–7.
129. Kundrotas PJ, Alexov E. PROTCOM: searchable database of protein complexes enhanced with domain–domain structures. *Nucleic Acids Res* 2007;**35**(Database issue):D575–9.
130. Zhu H, Sommer I, Lengauer T, *et al.* Alignment of non-covalent interactions at protein–protein interfaces. *PLoS ONE* 2008;**3**:e1926.
131. Wallace AC, Laskowski RA, Thornton JM. LIGPLOT: a program to generate schematic diagrams of protein–ligand interactions. *Protein Eng* 1995;**8**:127–34.
132. Shulman-Peleg A, Shatsky M, Nussinov R, *et al.* MultiBind and MAPPIS: web servers for multiple alignment of protein 3D-binding sites and their interactions. *Nucleic Acids Res* 2008;**36**(Web server issue):W260–4.
133. Gabdoulline RR, Wade RC, Walther D. MolSurfer: two-dimensional maps for navigating three-dimensional structures of proteins. *Trends Biochem Sci* 1999;**24**:285–7.
134. Tina KG, Bhadra R, Srinivasan N. PIC: Protein interactions calculator. *Nucleic Acids Res* 2007;**35**(Web server issue):W473–6.
135. Saha RP, Bahadur RP, Pal A, *et al.* ProFace: a server for the analysis of the physicochemical features of protein–protein interfaces. *BMC Struct Biol* 2006;**6**:11.
136. Kumar MD, Bava KA, Gromiha MM, *et al.* ProTherm and ProNIT: thermodynamic databases for proteins and protein–nucleic acid interactions. *Nucleic Acids Res* 2006;**34**(Database issue):D204–6.
137. Laurie AT, Jackson RM. Q-SiteFinder: an energy-based method for the prediction of protein–ligand binding sites. *Bioinformatics* 2005;**21**:1908–16.
138. Laskowski RA. SURFNET: a program for visualizing molecular surfaces, cavities, and intermolecular interactions. *J Mol Graph* 1995;**13**:323–330, 307–28.
139. Powers R, Copeland JC, Germer K, *et al.* Comparison of protein active site structures for functional annotation of proteins and drug design. *Proteins* 2006;**65**:124–35.
140. Bordner AJ, Gorin AA. Comprehensive inventory of protein complexes in the Protein Data Bank from consistent classification of interfaces. *BMC Bioinformatics* 2008;**9**:234.
141. Krissinel E, Henrick K. Inference of macromolecular assemblies from crystalline state. *J Mol Biol* 2007;**372**:774–97.
142. Ponstingl H, Kabir T, Thornton JM. Automatic inference of protein quaternary structure from crystals. *J Appl Cryst* 2003;**36**:1116–22.
143. Tsuchiya Y, Kinoshita K, Ito N, *et al.* PreBI: prediction of biological interfaces of proteins in crystals. *Nucleic Acids Res* 2006;**34**(Web server issue):W320–4.
144. Laskowski RA, Watson JD, Thornton JM. ProFunc: a server for predicting protein function from 3D structure. *Nucleic Acids Res* 2005;**33**(Web server issue):W89–93.
145. Lopez G, Valencia A, Tress ML. Firestar – prediction of functionally important residues using structural templates and alignment reliability. *Nucleic Acids Res* 2007;**35**(Web server issue):W573–7.
146. Negi SS, Schein CH, Oezguen N, *et al.* InterProSurf: a web server for predicting interacting sites on protein surfaces. *Bioinformatics* 2007;**23**:3397–99.
147. Stawiski EW, Gregoret LM, Mandel-Gutfreund Y. Annotating nucleic acid-binding function based on protein structure. *J Mol Biol* 2003;**326**:1065–79.
148. Tjong H, Qin S, Zhou HX. PI2PE: protein interface/interior prediction engine. *Nucleic Acids Res* 2007;**35**(Web server issue):W357–62.
149. Chen H, Zhou HX. Prediction of solvent accessibility and sites of deleterious mutations from protein sequence. *Nucleic Acids Res* 2005;**33**:3193–99.
150. Tjong H, Zhou HX. DISPLAR: an accurate method for predicting DNA-binding sites on protein surfaces. *Nucleic Acids Res* 2007;**35**:1465–77.
151. Shulman-Peleg A, Nussinov R, Wolfson HJ. Recognition of functional sites in protein structures. *J Mol Biol* 2004;**339**:607–33.
152. Huang B, Schroeder M. Using protein binding site prediction to improve protein docking. *Gene* 2008;**422**(1–2):14–21.
153. Andrusier N, Nussinov R, Wolfson HJ. FireDock: fast interaction refinement in molecular docking. *Proteins* 2007;**69**:139–59.
154. Dominguez C, Boelens R, Bonvin AM. HADDOCK: a protein–protein docking approach based on biochemical or biophysical information. *J Am Chem Soc* 2003;**125**:1731–7.
155. Ritchie DW, Kemp GJ. Protein docking using spherical polar Fourier correlations. *Proteins* 2000;**39**:178–94.
156. Heifetz A, Katchalski-Katzir E, Eisenstein M. Electrostatics in protein–protein docking. *Protein Sci* 2002;**11**:571–87.
157. Cheng TM, Blundell TL, Fernandez-Recio J. pyDock: electrostatics and desolvation for effective scoring of rigid-body protein–protein docking. *Proteins* 2007;**68**:503–15.
158. Gabb HA, Jackson RM, Sternberg MJ. Modelling protein docking using shape complementarity, electrostatics and biochemical information. *J Mol Biol* 1997;**272**:106–20.
159. Jackson RM, Gabb HA, Sternberg MJ. Rapid refinement of protein interfaces incorporating solvation: application to the docking problem. *J Mol Biol* 1998;**276**:265–85.