

- In this chapter we deal with some of the very old or quite old classical (secret-key or symmetric) cryptosystems that were primarily used in the pre-computer era.
- These cryptosystems are too weak nowadays, too easy to break, especially with computers.
- However, these simple cryptosystems give a good illustration of several of the important ideas of the **cryptography** and **cryptanalysis**.
- Moreover, most of them can be very useful in combination with more modern cryptosystem - to add a new level of security.

# IV054 Cryptology, Cryptosystems - secret-key cryptography

## Cryptology (= cryptography + cryptoanalysis)

has more than two thousand years of history.

### Basic historical observation

- People have always had fascination with keeping information away from others.
- Some people – rulers, diplomats, militaries, businessmen – have always had needs to keep some information away from others.

### Importance of cryptography nowadays

- **Applications:** cryptography is the key tool to make modern information transmission secure, and to create secure information society.
- **Foundations:** cryptography gave rise to several new key concepts of the foundation of informatics: one-way functions, computationally perfect pseudorandom generators, zero-knowledge proofs, holographic proofs, program self-testing and self-correcting, ...

# Sound approaches to cryptography


- Shannon's approach based on **information theory** (enemy has not enough information to break a cryptosystem)
- Current approach based on **complexity theory** (enemy has not enough computation power to break a cryptosystem).
- Very recent approach based on the laws and limitations of **quantum physics**
- (enemy would need to break laws of nature to break a cryptosystem).

## Paradoxes of modern cryptography

- **Positive results** of modern cryptography are based on **negative results** of complexity theory.
- Computers, that were designed originally for **decryption**, seem to be now more useful for **encryption**.

# IV054 Cryptosystems - ciphers

The cryptography deals the problem of sending a message (plaintext, cleartext), through a insecure channel, that may be tapped by an adversary (eavesdropper, cryptanalyst), to a legal receiver.



## IV054 Components of cryptosystems:

**Plaintext-space:**  $P$  – a set of plaintexts over an alphabet  $\Sigma$

**Cryptotext-space:**  $C$  – a set of cryptotexts (ciphertexts) over alphabet  $\Delta$

**Key-space:**  $K$  – a set of keys

Each key  $k$  determines an encryption algorithm  $e_k$  and an decryption algorithm  $d_k$  such that, for any plaintext  $w$ ,  $e_k(w)$  is the corresponding cryptotext and

$$w \in P \xrightarrow{e_k} C \quad \text{or} \quad w = d_k \left( e_k(w) \right)$$

**Note:** As encryption algorithms we can use also randomized algorithms.

## IV054 100 – 42 B.C., CAESAR cryptosystem, Shift cipher

CAESAR can be used to encrypt words in any alphabet.  
In order to encrypt words in English alphabet we use:

Key-space:  $\{0, 1, \dots, 25\}$

An encryption algorithm  $e_k$  substitutes any letter by the letter occurring  $k$  positions ahead (cyclically) in the alphabet.

A decryption algorithm  $d_k$  substitutes any letter by the one occurring  $k$  positions backward (cyclically) in the alphabet.

# IV054 100 – 42 B.C., CAESAR cryptosystem, Shift cipher

Example  $e_2(\text{EXAMPLE}) = \text{GZCOSNG}$ ,  
 $e_3(\text{EXAMPLE}) = \text{HADPTOH}$ ,  
 $e_1(\text{HAL}) = \text{IBM}$ ,  
 $e_3(\text{COLD}) = \text{FROG}$

ABCDEFGHIJKLMNOPQRSTUVWXYZ

Example Find the plaintext to the following cryptotext obtained by the encryption with CAESAR with  $k = ?$ .

Cryptotext: VHFUHW GH GHXA, VHFUHW GH GLHX,  
VHFUHW GH WURLV, VHFUHW GH WRXV.

**Numerical version of CAESAR** is defined on the set  $\{0, 1, 2, \dots, 25\}$  by the encryption algorithm:

$$e_k(i) = (i + k) \pmod{26}$$

# IV054 POLYBIOUS cryptosystem

for encryption of words of the English alphabet without J.

**Key-space:** Polybious checkerboards 5×5 with 25 English letters and with rows + columns labeled by symbols.

**Encryption algorithm:** Each symbol is substituted by the pair of symbols denoting the row and the column of the checkerboard in which the symbol is placed.

Example:

	F	G	H	I	J
A	A	B	C	D	E
B	F	G	H	I	K
C	L	M	N	O	P
D	Q	R	S	T	U
E	V	W	X	Y	Z

**KONIEC -->**

**Decryption algorithm: ???**



## IV054 Kerckhoff's Principle

The philosophy of modern cryptanalysis is embodied in the following principle formulated in 1883 by [Jean Guillaume Hubert Victor Francois Alexandre Auguste Kerckhoffs von Nieuwenhof](#) (1835 - 1903).

The security of a cryptosystem must not depend on keeping secret the encryption algorithm. The security should depend only on keeping secret the key.

## IV054 Requirements for good cryptosystems

(Sir Francis R. Bacon (1561 - 1626))

1. Given  $e_k$  and a plaintext  $w$ , it should be **easy** to compute  $c = e_k(w)$ .
2. Given  $d_k$  and a cryptotext  $c$ , it should be **easy** to compute  $w = d_k(c)$ .
3. A cryptotext  $e_k(w)$  should **not** be much **longer** than the plaintext  $w$ .
4. It should be **unfeasible** to determine  $w$  from  $e_k(w)$  without knowing  $d_k$ .
5. The so called **avalanche effect** should hold: A **small change in the plaintext, or in the key, should lead to a big change in the cryptotext** (i.e. a change of one bit of the plaintext should result in a change of all bits of the cryptotext, each with the probability close to 0.5).
6. The cryptosystem should **not** be **closed under composition**, i.e. not for every two keys  $k_1, k_2$  there is a key  $k$  such that
$$e_k(w) = e_{k_1}(e_{k_2}(w)).$$
7. The set of keys should be very large.

The aim of cryptoanalysis is to get as much information about the plaintext or the key as possible.

## Main types of cryptanalytic attack

**1. Cryptotexts-only attack.** The cryptanalysts get cryptotexts

$c_1 = e_k(w_1), \dots, c_n = e_k(w_n)$  and try to infer the key  $k$  or as many of the plaintexts  $w_1, \dots, w_n$  as possible.

**2. Known-plaintexts attack (given are some pairs plaintext  $\rightarrow$  cryptotext)**

The cryptanalysts know some pairs  $w_i, e_k(w_i)$ ,  $1 \leq i \leq n$ , and try to infer  $k$ , or at least  $w_{n+1}$  for a new cryptotext many plaintexts  $e_k(w_{n+1})$ .

**3. Chosen-plaintexts attack (given are cryptotext for some chosen plaintexts)**

The cryptanalysts choose plaintexts  $w_1, \dots, w_n$  to get cryptotexts  $e_k(w_1), \dots, e_k(w_n)$ , and try to infer  $k$  or at least  $w_{n+1}$  for a new cryptotext  $c_{n+1} = e_k(w_{n+1})$ . (For example, if they get temporary access to encryption machinery.)

## IV054 Cryptoanalysis

### 4. Known-encryption-algorithm attack

The encryption algorithm  $e_k$  is given and the cryptanalysts try to get the decryption algorithm  $d_k$ .

### 5. Chosen-plaintext attack (given are plaintexts for some chosen ciphertexts)

The cryptanalysts know some pairs

$$(c_i, d_k(c_i)), \quad 1 \leq i \leq n,$$

where the ciphertexts  $c_i$  have been chosen by the cryptanalysts. The aim is to determine the key. (For example, if cryptanalysts get a temporary access to decryption machinery.)

## IV054 WHAT CAN a BAD EVE DO?

Let us assume that a clever Alice sends an encrypted message to Bob. What can a bad enemy, called usually Eve (eavesdropper), do?

- Eve can read (and try to decrypt) the message.
- Eve can try to get the key that was used and then decrypt all messages encrypted with the same key.
- Eve can change the message sent by Alice into another message, in such a way that Bob will have the feeling, after he gets the changed message, that it was a message from Alice.
- Eve can pretend to be Alice and communicate with Bob, in such a way that Bob thinks he is communicating with Alice.

An **eavesdropper** can therefore be **passive - Eve** or **active - Mallot**.

## IV054 Basic goals of broadly understood cryptography

**Confidentiality:** Eve should not be able to decrypt the message Alice sends to Bob.

**Data integrity:** Bob wants to be sure that Alice's message has not been altered by Eve.

**Authentication:** Bob wants to be sure that only Alice could have sent the message he has received.

**Non-repudiation:** Alice should not be able to claim that she did not send messages that she has sent.

**Anonymity:** Alice does not want that Bob finds who sent the message

## IV054 HILL cryptosystem

The cryptosystem presented in this slide was probably never used. In spite of that this cryptosystem played an important role in the history of modern cryptography.

We describe Hill cryptosystem or a fixed  $n$  and the English alphabet.

**Key-space:** matrices  $M$  of degree  $n$  with elements from the set  $\{0, 1, \dots, 25\}$  such that  $M^{-1} \bmod 26$  exist.

**Plaintext + cryptotext space:** English words of length  $n$ .

**Encoding:** For a word  $w$  let  $c_w$  be the column vector of length  $n$  of the integer codes of symbols of  $w$ . ( $A \rightarrow 0, B \rightarrow 1, C \rightarrow 2, \dots$ )

**Encryption:**  $c_c = Mc_w \bmod 26$

**Decryption:**  $c_w = M^{-1}c_c \bmod 26$

# IV054 HILL cryptosystem

Example A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

$$M = \begin{bmatrix} 4 & 7 \\ 1 & 1 \end{bmatrix} \quad M^{-1} = \begin{bmatrix} 17 & 11 \\ 9 & 16 \end{bmatrix}$$

Plaintext:  $w = \text{LONDON}$

$$c_{LO} = \begin{bmatrix} 11 \\ 14 \end{bmatrix}, \quad c_{ND} = \begin{bmatrix} 13 \\ 3 \end{bmatrix}, \quad c_{ON} = \begin{bmatrix} 14 \\ 13 \end{bmatrix}$$

$$Mc_{LO} = \begin{bmatrix} 12 \\ 25 \end{bmatrix}, \quad Mc_{ND} = \begin{bmatrix} 21 \\ 16 \end{bmatrix}, \quad Mc_{ON} = \begin{bmatrix} 17 \\ 1 \end{bmatrix}$$

Cryptotext: MZVQRB

**Theorem**

**Proof:** Exercise If  $M = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix}$ , then  $M^{-1} = \frac{1}{\det M} \begin{bmatrix} a_{22} & -a_{12} \\ -a_{21} & a_{11} \end{bmatrix}$



## IV054 Secret-key (symmetric) cryptosystems

A cryptosystem is called **secret-key cryptosystem** if some secret piece of information – the key – has to be agreed first between any two parties that have, or want, to communicate through the cryptosystem. Example: CAESAR, HILL. Another name is **symmetric cryptosystem (cryptography)**.

Two basic types of secret-key cryptosystems

- **substitution** based cryptosystems
- **transposition** based cryptosystems

Two basic types of substitution cryptosystems

- **monoalphabetic cryptosystems** – they use a fixed substitution – CAESAR, POLYBIOUS
- **polyalphabetic cryptosystems** – substitution keeps changing during the encryption

A monoalphabetic cryptosystem with letter-by-letter substitution is uniquely specified by a permutation of letters. (Number of permutations (keys) is 26!)

# IV054 Secret-key cryptosystems

**Example:** **AFFINE cryptosystem** is given by two integers

$$1 \leq a, b \leq 25, \gcd(a, 26) = 1.$$

**Encryption:**  $e_{a,b}(x) = (ax + b) \bmod 26$

Example

$$a = 3, b = 5, e_{3,5}(x) = (3x + 5) \bmod 26,$$

$$e_{3,5}(3) = 14, e_{3,5}(15) = 24 - e_{3,5}(D) = 0, e_{3,5}(P) = Y$$

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

**Decryption:**  $d_{a,b}(y) = a^{-1}(y - b) \bmod 26$

# IV054 Cryptanalysis's

The basic cryptanalytic attack against monoalphabetic substitution cryptosystems begins with a **frequency count**: the number of each letter in the cryptotext is counted. The distributions of letters in the cryptotext is then compared with some official distribution of letters in the plaintext language.

The letter with the highest frequency in the cryptotext is likely to be substitute for the letter with highest frequency in the plaintext language .... The likelihood grows with the length of cryptotext.

Frequency counts in English:

	%		%		%
E	12.31	L	4.03	B	1.62
T	9.59	D	3.65	G	1.61
A	8.05	C	3.20	V	0.93
O	7.94	U	3.10	K	0.52
N	7.19	P	2.29	Q	0.20
I	7.18	F	2.28	X	0.20
S	6.59	M	2.25	J	0.10
R	6.03	W	2.03	Z	0.09
H	5.14	Y	1.88		5.27
	70.02		24.71		

and for other languages:

English	%	German	%	Finnish	%	French	%	Italian	%	Spanish	%
E	12.31	E	18.46	A	12.06	E	15.87	E	11.79	E	13.15
T	9.59	N	11.42	I	10.59	A	9.42	A	11.74	A	12.69
A	8.05	I	8.02	T	9.76	I	8.41	I	11.28	O	9.49
O	7.94	R	7.14	N	8.64	S	7.90	O	9.83	S	7.60
N	7.19	S	7.04	E	8.11	T	7.29	N	6.88	N	6.95
I	7.18	A	5.38	S	7.83	N	7.15	L	6.51	R	6.25
S	6.59	T	5.22	L	5.86	R	6.46	R	6.37	I	6.25
R	6.03	U	5.01	O	5.54	U	6.24	T	5.62	L	5.94
H	5.14	D	4.94	K	5.20	L	5.34	S	4.98	D	5.58

The 20 most common **digrams** are (in decreasing order) TH, HE, IN, ER, AN, RE, ED, ON, ES, ST, EN, AT, TO, NT, HA, ND, OU, EA, NG, AS. The six most common **trigrams**: THE, ING, AND, HER, ERE, ENT.

# IV054 Cryptanalysis's

Cryptoanalysis of a cryptotext encrypted using the AFINE cryptosystem with an encryption algorithm

$$e_{a,b}(x) = (ax + b) \bmod 26 = (xa+b) \bmod 26$$

where  $0 \leq a, b \leq 25, \gcd(a, 26) = 1$ . (Number of keys:  $12 \times 26 = 312$ .)

**Example:** Assume that an English plaintext is divided into blocks of 5 letter and encrypted by an AFINE cryptosystem (ignoring space and interpunctions) as follows:

How to find  
the plaintext?

B H J U H	N B U L S	V U L R U	S L Y X H
O N U U N	B W N U A	X U S N L	U Y J S S
W X R L K	G N B O N	U U N B W	S W X K X
H K X D H	U Z D L K	X B H J U	H B N U O
N U M H U	G S W H U	X M B X R	W X K X L
U X B H J	U H C X K	X A X K Z	S W K X X
L K O L J	K C X L C	M X O N U	U B V U L
R R W H S	H B H J U	H N B X M	B X R W X
K X N O Z	L J B X X	H B N F U	B H J U H
L U S W X	G L L K Z	L J P H U	U L S Y X
B J K X S	W H S S W	X K X N B	H B H J U
H Y X W N	U G S W X	G L L K	

# IV054 Cryptanalysis's

Frequency analysis of plaintext and frequency table for English:

X - 32	J - 11	D - 2	E	12.31	L	4.03	B	1.62
U - 30	O - 6	V - 2	T	9.59	D	3.65	G	1.61
H - 23	R - 6	F - 1	A	8.05	C	3.20	V	0.93
B - 19	G - 5	P - 1	O	7.94	U	3.10	K	0.52
L - 19	M - 4	E - 0	N	7.19	P	2.29	Q	0.20
N - 16	Y - 4	I - 0	I	7.18	F	2.28	X	0.20
K - 15	Z - 4	Q - 0	S	6.59	M	2.25	J	0.10
S - 15	C - 3	T - 0	R	6.03	W	2.03	Z	0.09
W - 14	A - 2		H	5.14	Y	1.88		5.27
				70.02		24.71		

**First guess:**  $E = X, T = U$

Encodings:  $4a + b = 23 \pmod{26}$

$xa + b = y$   $19a + b = 20 \pmod{26}$

**Solutions:**  $a = 5, b = 3 \rightarrow a^{-1} =$

Translation table

crypto	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
plain	P	K	F	A	V	Q	L	G	B	W	R	M	H	C	X	S	N	I	D	Y	T	O	J	E	Z	U

```

B H J U H   N B U L S   V U L R U   S L Y X H
O N U U N   B W N U A   X U S N L   U Y J S S
W X R L K   G N B O N   U U N B W   S W X K X
H K X D H   U Z D L K   X B H J U   H B N U O
N U M H U   G S W H U   X M B X R   W X K X L
U X B H J   U H C X K   X A X K Z   S W K X X
L K O L J   K C X L C   M X O N U   U B V U L
R R W H S   H B H J U   H N B X M   B X R W X
K X N O Z   L J B X X   H B N F U   B H J U H
L U S W X   G L L K Z   L J P H U   U L S Y X
B J K X S   W H S S W   X K X N B   H B H J U
H Y X W N   U G S W X   G L L K
    
```

provides from the above cryptotext the plaintext that starts with KGWTG CKTMO OTMIT DMZEG, what does not make a sense.

# IV054 Cryptanalysis's

**Second guess:**  $E = X, A = H$

Equations  $4a + b = 23 \pmod{26}$

$b = 7 \pmod{26}$

**Solutions:**  $a = 4$  or  $a = 17$  and therefore  $a=17$

*This gives the translation table*

crypto	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
plain	V	S	P	M	J	G	D	A	X	U	R	O	L	I	F	C	Z	W	T	Q	N	K	H	E	B	Y

*and the following  
plaintext from the  
above cryptotext*

S A U N A    I S N O T    K N O W N    T O B E A  
 F I N N I    S H I N V    E N T I O    N B U T T  
 H E W O R    D I S F I    N N I S H    T H E R E  
 A R E M A    N Y M O R    E S A U N    A S I N F  
 I N L A N    D T H A N    E L S E W    H E R E O  
 N E S A U    N A P E R    E V E R Y    T H R E E  
 O R F O U    R P E O P    L E F I N    N S K N O  
 W W H A T    A S A U N    A I S E L    S E W H E  
 R E I F Y    O U S E E    A S I G N    S A U N A  
 O N T H E    D O O R Y    O U C A N    N O T B E  
 S U R E T    H A T T H    E R E I S    A S A U N  
 A B E H I    N D T H E    D O O R

# IV054

## Example of monoalphabetic cryptosystem


Symbols of the English alphabet will be replaced by squares with or without points and with or without surrounding lines using the following rule:

A:	B:	C:	J·	K·	L·	S	T	U
D:	E:	F:	M·	N·	O·	V	W	X
G:	H:	I:	P·	Q·	R·	Y	Z	

For example the plaintext:

WE TALK ABOUT FINNISH SAUNA MANY TIMES LATER


results in the cryptotext:



**Garbage in between method:** the message (plaintext or cryptotext) is supplemented by "garbage letters".

Richelieu cryptosystem  
used sheets of card  
board with holes.

I	L	O	V	E	Y	O	U		
I	H	A	V	E	Y	O	U		
D	E	E	P	U	N	D	E	R	
M	Y	S	K	I	N	M	Y		
L	O	V	E	L	A	S	T	S	
F	O	R	E	V	E	R	I	N	
H	Y	P	E	R	S	P	A	C	E



## Playfair cryptosystem

Invented around 1854 by Ch. Wheatstone.

Key - a Playfair square is defined by a word  $w$  of length at most 25. In  $w$  repeated letters are then removed, remaining letters of alphabets (except  $j$ ) are then added and resulting word is divided to form an  $5 \times 5$  array (a Playfair square).

**Encryption:** of a pair of letters  $x, y$

- If  $x$  and  $y$  are in the same row (column), then they are replaced by the pair of symbols to the right (below) them.
- If  $x$  and  $y$  are in different rows and columns they are replaced by symbols in the opposite corners of rectangle created by  $x$  and  $y$ .

**Example:** PLAYFAIR is encrypted as LCMNNFCS

Playfair was used in World War I by British army.

Playfair square:

S	D	Z	I	U
H	A	F	N	G
B	M	V	Y	W
R	P	L	C	X
T	O	E	K	Q



## VIGENERE and AUTOCLAVE cryptosystems

Several of the following polyalphabetic cryptosystems are modification of the CAESAR cryptosystem.

A  $26 \times 26$  table is first designed with the first row containing a permutation of all symbols of alphabet and all columns represent CAESAR shifts starting with the symbol of the first row.

Secondly, for a plaintext  $w$  a key  $k$  is a word of the same length as  $w$ .

**Encryption:** the  $i$ -th letter of the plaintext -  $w_i$  is replaced by the letter in the  $w_i$ -row and  $k_i$ -column of the table.

**VIGENERE cryptosystem:** a short keyword  $p$  is chosen and

$$k = \text{Prefix}_{|w|} p^{oo}$$

VIGENERE is actually a cyclic version of the CAESAR cryptosystem.

**AUTOCLAVE cryptosystem:**  $k = \text{Prefix}_{|w|} pw.$

# IV054 Polyalphabetic Substitution Cryptosystems

## VIGENERE and AUTOCLAVE cryptosystems

**Example:**

```

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
B C D E F G H I J K L M N O P Q R S T U V W X Y Z A
C D E F G H I J K L M N O P Q R S T U V W X Y Z A B
D E F G H I J K L M N O P Q R S T U V W X Y Z A B C
E F G H I J K L M N O P Q R S T U V W X Y Z A B C D
F G H I J K L M N O P Q R S T U V W X Y Z A B C D E
G H I J K L M N O P Q R S T U V W X Y Z A B C D E F
H I J K L M N O P Q R S T U V W X Y Z A B C D E F G
I J K L M N O P Q R S T U V W X Y Z A B C D E F G H
J K L M N O P Q R S T U V W X Y Z A B C D E F G H I
K L M N O P Q R S T U V W X Y Z A B C D E F G H I J
L M N O P Q R S T U V W X Y Z A B C D E F G H I J K
M N O P Q R S T U V W X Y Z A B C D E F G H I J K L
N O P Q R S T U V W X Y Z A B C D E F G H I J K L M
O P Q R S T U V W X Y Z A B C D E F G H I J K L M N
P Q R S T U V W X Y Z A B C D E F G H I J K L M N O
Q R S T U V W X Y Z A B C D E F G H I J K L M N O P
R S T U V W X Y Z A B C D E F G H I J K L M N O P Q
S T U V W X Y Z A B C D E F G H I J K L M N O P Q R
T U V W X Y Z A B C D E F G H I J K L M N O P Q R S
U V W X Y Z A B C D E F G H I J K L M N O P Q R S T
V W X Y Z A B C D E F G H I J K L M N O P Q R S T U
W X Y Z A B C D E F G H I J K L M N O P Q R S T U V
X Y Z A B C D E F G H I J K L M N O P Q R S T U V W
Y Z A B C D E F G H I J K L M N O P Q R S T U V W X
Z A B C D E F G H I J K L M N O P Q R S T U V W X Y

```

**Keyword:** HAMBURG  
**Plaintext:** INJEDEMMENSCHENGESICHTESTEHTSEINEG  
**Vigenere-key:** HAMBURGHAMBURGHAMBURGHAMBURGHAMBUR  
**Autoclave-key:** HAMBURGINJEDEMMENSCHENGESICHTESTEH  
**Vigerere-cryp.:** PNVFXVSTEZTWYKUGQTCTNAEEVYYZZEUOYX  
**Autoclave-cryp.:** PNVFXVSURWWFLQZKRKKJLGKWL MJALIAGIN

## 1.Task 1 -- to find the length of the key

Kasiski method (1852) - invented also by Charles Babbage (1853).

**Basic observation** If a subword of a plaintext is repeated at a distance that is a multiple of the length of the key, then the corresponding subwords of the cryptotext are the same.

**Example**, cryptotext:

CHR GQPW O EIRULYANDOSH CHR IZKEBUSNOFKYWROPD CHR KGAXBNRHROAKERBKS CHR IWK

Substring "CHR" occurs in positions 1, 21, 41, 66: expected keyword length is therefore 5.

**Method.** Determine the greatest common divisor of the distances between identical subwords (of length 3 or more) of the cryptotext.

Friedman method Let  $n_i$  be the number of occurrences of the  $i$ -th letter in the cryptotext.

Let  $l$  be the length of the keyword.

Let  $n$  be the length of the cryptotext.

Then it holds

$$l = \frac{0.027n}{\sqrt{n-1} - 0.038n + 0.065}, \quad I = \sum_{i=1}^{26} \frac{n_i(n_i-1)}{n(n-1)}$$

Once the length of the keyword is found it is easy to determine the key using the statistical (frequency analysis) method of analyzing monoalphabetic cryptosystems.

## IV054 Derivation of the Friedman method

1. Let  $n_i$  be the number of occurrences of  $i$ -th alphabet symbol in a text of length  $n$ . The probability that if one selects a pair of symbols from the text, then they are the same is

$$I = \frac{\sum_{i=1}^{26} n_i(n_i-1)}{n(n-1)} = \sum_{i=1}^{26} \frac{n_i}{n} \frac{n_i-1}{n-1}$$

and it is called the index of coincides.

2. Let  $p_i$  be the probability that a randomly chosen symbol is the  $i$ -th symbol of the alphabet. The probability that two randomly chosen symbol are the same is

$$\sum_{i=1}^{26} p_i^2$$

For English text one has

$$\sum_{i=1}^{26} p_i^2 \approx 0.065$$

For randomly chosen text:

$$\sum_{i=1}^{26} p_i^2 = \sum_{i=1}^{26} \frac{1}{26^2} = 0.038$$

Approximately

$$I = \sum_{i=1}^{26} p_i^2$$

# IV054 Derivation of the Friedman method

Assume that a cryptotext is organized into  $l$  columns headed by the letters of the keyword

letters $s_i$	$S_1$	$S_2$	$S_3$	...	$S_l$
	$x_1$	$x_2$	$x_3$	...	$x_l$
	$x_{l+1}$	$x_{l+2}$	$x_{l+3}$	...	$x_{2l}$
	$x_{2l+1}$	$x_{2l+2}$	$x_{2l+3}$	...	$x_{3l}$
	.	.	.	...	.

**First observation** Each column is obtained using the CAESAR cryptosystem.

Probability that two randomly chosen letters are the same in

- the same column is 0.065.
- different columns is 0.038.

The number of pairs of letters in the same column:  $\frac{l}{2} \cdot \frac{n}{l} = \frac{l \cdot n}{2l}$

The number of pairs of letters in different columns:  $\frac{l(l-1)}{2} \cdot \frac{n^2}{l^2} = \frac{l(l-1)n^2}{2l^2}$

The expected number  $A$  of pairs of equal letters is  $A = \frac{l \cdot n}{2l} \cdot 0.065 + \frac{l(l-1)n^2}{2l^2} \cdot 0.038$

Since  $I = \frac{A}{\frac{n(n-1)}{2}} = \frac{1}{n-1} \left[ 0.027 + l \cdot 0.038n - 0.065 \right]$

one gets the formula for  $l$  from the previous slide.

Binary case:

plaintext	$w$	}	are binary words of the same length
key	$k$		
cryptotext	$c$		

**Encryption:**  $c = w \oplus k$

**Decryption:**  $w = c \oplus k$

**Example:**

$$w = 101101011$$

$$k = 011011010$$

$$c = 110110001$$

What happens if the same key is used twice or 3 times for encryption?

$$c_1 = w_1 \oplus k, c_2 = w_2 \oplus k, c_3 = w_3 \oplus k$$

$$c_1 \oplus c_2 = w_1 \oplus w_2$$

$$c_1 \oplus c_3 = w_1 \oplus w_3$$

$$c_2 \oplus c_3 = w_2 \oplus w_3$$

## IV054 Perfect secret cryptosystems

By Shannon, a cryptosystem is perfect if the knowledge of the cryptotext provides no information whatsoever about its plaintext (with the exception of its length).

It follows from Shannon's results that perfect secrecy is possible if the key-space is as large as the plaintext-space. In addition, a key has to be as long as plaintext and the same key should not be used twice.

An example of a perfect cryptosystem **ONE-TIME PAD** cryptosystem (Gilbert S. Vernam (1917) - AT&T + Major Joseph Mauborgne).

If used with the English alphabet, it is simply a polyalphabetic substitution cryptosystem of VIGENERE with the key being a randomly chosen English word of the same length as the plaintext.

**Proof of perfect secrecy:** by the proper choice of the key any plaintext of the same length could provide the given cryptotext.

**Did we gain something?** The problem of secure communication of the plaintext got transformed to the problem of secure communication of the key of the same length.

- Yes:
1. **ONE-TIME PAD** cryptosystem is used in critical applications
  2. It suggests an idea how to construct practically secure cryptosystems.



# IV054 Transposition Cryptosystems

The **basic idea** is very simple: permute the plaintext to get the cryptotext. Less clear it is how to specify and perform efficiently permutations.

**One idea:** choose  $n$ , write plaintext into rows, with  $n$  symbols in each row and then read it by columns to get cryptotext.

**Example**

I	N	J	E	D	E	M	M	E	N
S	C	H	E	N	G	E	S	I	C
H	T	E	S	T	E	H	T	S	E
I	N	E	G	E	S	C	H	I	C
H	T	E	T	O	J	E	O	N	O

Cryptotexts obtained by transpositions, called **anagrams**, were popular among scientists of 17th century. They were used also to encrypt scientific findings.

Newton wrote to Leibnitz

$$a^7c^2d^2e^{14}f^2i^7l^3m^1n^8o^4q^3r^2s^4t^8v^{12}x^1$$

what stands for: "data aequatione quodcumque fluentes quantitates involvente, fluxiones invenire et vice versa"

**Example**

$$a^2cdef^3g^2i^2jkmn^8o^5prs^2t^2u^3z$$

**Solution:**



## IV054 KEYWORD CAESAR cryptosystem

**Exercise** Decrypt the following cryptotext encrypted using the KEYWORD CAESAR and determine the keyword and  $k$

```
T  IVD  ZCRTIC  FQNIQ  TU  TF
Q  XAVFCZ  FEQXC  PCQUCZ  WK
Q  FUVBC  FNRRXTTCIUAK  WTY
DTUP  MCFECXU  UV  UPC  BVANHC
VR  UPC  FEQXC  UPC  FUVBC
XVIUQTIF  FUVICF  NFNQA AK
VI  UPC  UVE  UV  UQGC  Q  FQNIQ
WQUP  TU  TF  QAFV  ICXCFFQMK
UPQU  UPC  FUVBC  TF  EMVECM AK
PCQUCZ  QIZ  UPQU  KVN  PQBC
UPC  RQXTATUK  VR  UPMVDTIY
DQUCM  VI  UPC  FUVICF
```

# IV054 KEYWORD CAESAR cryptosystem

Step 1. Make the frequency counts:

	Number		Number		Number
U	32	X	8	W	3
C	31	K	7	Y	2
Q	23	N	7	G	1
F	22	E	6	H	1
V	20	M	6	J	0
P	15	R	6	L	0
T	15	B	5	O	0
I	14	Z	5	S	0
A	8	D	4		7=2.90%
180=74.69%		54=22.41%			

Step 2. Cryptotext contains two one-letter words T and Q. They must be A and I. Since T occurs once and Q three times it is likely that T is I and Q is A.

The three letter word UPC occurs 7 times and all other 3-letter words occur only once. Hence

UPC is likely to be THE.

Let us now decrypt the remaining letters in the high frequency group: F,V,I

From the words TU, TF  $\Rightarrow$  F=S

From UV  $\Rightarrow$  V=O

From VI  $\Rightarrow$  I=N

The result after the remaining guesses

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z  
 L V E W P S K M N ? Y ? R U ? H E F ? I T O B C G D

# UNICITY DISTANCE of CRYPTOSYSTEMS

Redundancy of natural languages is of the key importance for cryptanalysis.

Would all letters of a 26-symbol alphabet have the same probability, a character would carry  $\lg 26 = 4.7$  bits of Information.

The estimated average amount of information carried per letter in a meaningful English text is 1.5 bits.

The unicity distance of a cryptosystem is the minimum number of cryptotext (number of letters) required to a computationally unlimited adversary to recover the unique encryption key.

Empirical evidence indicates that if any simple cryptosystem is applied to a meaningful English message, then about 25 cryptotext characters is enough for an experienced cryptanalyst to recover the plaintext.

# IV054 ANAGRAMS - EXAMPLES

## German:

IRI BRÄTER, GENF	Briefträgerin
FRANK PEKL, REGEN	...
PEER ASSSTIL, MELK	...
INGO DILMR, PEINE	...
EMIL REST, GERA	...
KARL SORDORT, PEINE	...

## English:

algorithms	logarithms
antagonist	stagnation
compressed	decompress
coordinate	decoration
creativity	reactivity
deductions	discounted
descriptor	predictors
impression	permission
introduces	reductions
procedures	reproduces

- APPENDIX

# STREAM CRYPTOSYSTEMS

Two basic types of cryptosystems are:

- **Block cryptosystems** (Hill cryptosystem,...) – they are used to encrypt simultaneously blocks of plaintext.
- **Stream cryptosystems** (CAESAR, ONE-TIME PAD,...) – they encrypt plaintext letter by letter, or block by block, using an encryption that may vary during the encryption process.

**Stream cryptosystems** are more appropriate in some applications (telecommunication), usually are simpler to implement (also in hardware), usually are faster and usually have no error propagation (what is of importance when transmission errors are highly probable).

Two basic types of stream cryptosystems: secret key cryptosystems (ONE-TIME PAD) and public-key cryptosystems (Blum-Goldwasser)



## IV054 Block versus stream cryptosystems

In **block cryptosystems** the same key is used to encrypt arbitrarily long plaintext – block by block - (after dividing each long plaintext  $w$  into a sequence of subplaintexts (blocks)  $w_1w_2w_3$  ).

In **stream cryptosystems** each block is encrypted using a different key

- **The fixed key  $k$  is used to encrypt all blocks.** In such a case the resulting cryptotext has the form

$$c = c_1c_2c_3\dots = e_k(w_1) e_k(w_2) e_k(w_3)\dots$$

- **A stream of keys is used to encrypt subplaintexts.** The basic idea is to generate a key-stream  $K=k_1,k_2,k_3,\dots$  and then to compute the cryptotext as follows

$$c = c_1c_2c_3\dots = e_{k_1}(w_1) e_{k_2}(w_2) e_{k_3}(w_3).$$

Various techniques are used to compute a sequence of keys. For example, given a key  $k$

$$k_i = f_i(k, k_1, k_2, \dots, k_{i-1})$$

In such a case encryption and decryption processes generate the following sequences:

**Encryption:** To encrypt the plaintext  $w_1w_2w_3 \dots$  the sequence

$$k_1, c_1, k_2, c_2, k_3, c_3, \dots$$

of keys and sub-cryptotexts is computed.

**Decryption:** To decrypt the cryptotext  $c_1c_2c_3 \dots$  the sequence

$$k_1, w_1, k_2, w_2, k_3, w_3, \dots$$

of keys and subplaintexts is computed.

## IV054 EXAMPLES

A keystream is called **synchronous** if it is independent of the plaintext.

**KEYWORD VIGENERE** cryptosystem can be seen as an example of a synchronous keystream cryptosystem.

Another type of the binary keystream cryptosystem is specified by an initial sequence of keys

$$k_1, k_2, k_3 \dots k_m$$

and an initial sequence of binary constants

$$b_1, b_2, b_3 \dots b_{m-1}$$

and the remaining keys are computed using the rule

$$k_{i+m} = \sum_{j=0}^{m-1} b_j k_{i+j} \pmod 2$$

A keystream is called **periodic** with period  $p$  if  $k_{i+p} = k_i$  for all  $i$ .

**Example** Let the keystream be generated by the rule

$$k_{i+4} = k_i \oplus k_{i+1}$$

If the initial sequence of keys is (1,0,0,0), then we get the following keystream:

$$1, 0, 0, 0, 1, 0, 0, 1, 1, 0, 1, 0, 1, 1, 1, \dots$$

of period 15.

Let  $\mathbf{P}$ ,  $\mathbf{K}$  and  $\mathbf{C}$  be sets of plaintexts, keys and cryptotexts.

Let  $p_K(k)$  be the probability that the key  $k$  is chosen from  $\mathbf{K}$  and let a priori probability that plaintext  $w$  is chosen is  $p_P(w)$ .

If for a key  $k \in \mathbf{K}$ ,  $C(c) = \{w \in \mathbf{P} \mid c = d_k(w)\}$ , then for the probability  $P_C(c)$  that  $c$  is the cryptotext that is transmitted it holds

$$P_C(c) = \sum_{k \in \mathbf{K}} p_K(k) p_P(d_k^{-1}(c))$$

For the conditional probability  $p_C(c|w)$  that  $c$  is the cryptotext if  $w$  is the plaintext it holds

$$p_C(c|w) = \sum_{k \in \mathbf{K}} p_K(k) \mathbb{1}_{c = d_k(w)}$$

Using Bayes' conditional probability formula  $p(y)p(x|y) = p(x)p(y|x)$  we get for probability  $p_P(w|c)$  that  $w$  is the plaintext if  $c$  is the cryptotext the expression

$$p_P(w|c) = \frac{p_P(w) \sum_{k \in \mathbf{K}} \mathbb{1}_{c = d_k(w)} p_K(k)}{\sum_{k \in \mathbf{K}} p_K(k) p_P(d_k^{-1}(c))}$$

**Definition** A cryptosystem has perfect secrecy if

$$p_P(w|c) = p_P(w) \text{ for all } w \in \mathcal{P} \text{ and } c \in \mathcal{C}.$$

(That is, the a posteriori probability that the plaintext is  $w$ , given that the ciphertext is  $c$  is obtained, is the same as a priori probability that the plaintext is  $w$ .)

**Example** CAESAR cryptosystem has perfect secrecy if any of the 26 keys is used with the same probability to encode any symbol of the plaintext.

**Proof** Exercise.

**An analysis of perfect secrecy:** The condition  $p_P(w|c) = p_P(w)$  is for all  $w \in \mathcal{P}$  and  $c \in \mathcal{C}$  equivalent to the condition  $p_C(c|w) = p_C(c)$ .

Let us now assume that  $p_C(c) > 0$  for all  $c \in \mathcal{C}$ .

Fix  $w \in \mathcal{P}$ . For each  $c \in \mathcal{C}$  we have  $p_C(c|w) = p_C(c) > 0$ . Hence, for each  $c \in \mathcal{C}$  there must exist at least one key  $k$  such that  $e_k(w) = c$ . Consequently,  $|\mathcal{K}| \geq |\mathcal{C}| \geq |\mathcal{P}|$ .

In a special case  $|\mathcal{K}| = |\mathcal{C}| = |\mathcal{P}|$ , the following nice characterization of the perfect secrecy can be obtained:

**Theorem** A cryptosystem in which  $|\mathcal{P}| = |\mathcal{K}| = |\mathcal{C}|$  provides perfect secrecy if and only if every key is used with the same probability and for every  $w \in \mathcal{P}$  and every  $c \in \mathcal{C}$  there is a unique key  $k$  such that  $e_k(w) = c$ .

**Proof** Exercise.

A cryptosystem  $S = (P, K, C, e, d)$  with the sets of plaintexts  $P$ , keys  $K$  and cryptotexts  $C$  and encryption (decryption) algorithms  $e$  ( $d$ ) is called **endomorphnic** if  $P = C$ .

If  $S_1 = (P, K_1, P, e^{(1)}, d^{(1)})$  and  $S_2 = (P, K_2, P, e^{(2)}, d^{(2)})$  are endomorphnic cryptosystems, then the **product cryptosystem** is

$$S_1 \otimes S_2 = (P, K_1 \otimes K_2, P, e, d),$$

where encryption is performed by the procedure

$$e_{(k_1, k_2)}(w) = e_{k_2}(e_{k_1}(w))$$

and decryption by the procedure

$$d_{(k_1, k_2)}(c) = d_{k_1}(d_{k_2}(c)).$$

**Example (Multiplicative cryptosystem):**

**Encryption:**  $e_a(w) = aw \pmod p$ ; **decryption:**  $d_a(c) = a^{-1}c \pmod{26}$ .

If  $M$  denote the multiplicative cryptosystem, then clearly CAESAR  $M$  is actually the AFFINE cryptosystem.

**Exercise** Show that also  $M \otimes$  CAESAR is actually the AFFINE cryptosystem.

Two cryptosystems  $S_1$  and  $S_2$  are called **commutative** if  $S_1 \otimes S_2 = S_2 \otimes S_1$ .

A cryptosystem  $S$  is called **idempotent** if  $S \otimes S = S$ .