


Natural Language Processing with Deep Learning

CS224N/Ling284



Jesse Mu


Lecture 11: Prompting, Instruction Finetuning, and RLHF

Larger and larger models

The blessings of scale


AI training runs, estimated computing resources used

Floating-point operations, selected systems, by type, log scale



Sources: "Compute trends across three eras of machine learning", by J. Sevilla et al., arXiv, 2022; Our World in Data

Trained on more and more data



<https://babylm.github.io/>

Recap of Lecture 10: What kinds of things does pretraining learn?

- *Stanford University is located in _____, California.* [Trivia]
- *I put ___ fork down on the table.* [syntax]
- *The woman walked across the street, checking for traffic over ___ shoulder.* [coreference]
- *I went to the ocean to see the fish, turtles, seals, and _____.* [lexical semantics/topic]
- *Overall, the value I got from the two hours watching it was the sum total of the popcorn and the drink. The movie was _____.* [sentiment]
- Iroh went into the kitchen to make some tea. Standing next to Iroh, Zuko pondered his destiny. Zuko left the _____. [some reasoning – this is harder]
- I was thinking about the sequence that goes 1, 1, 2, 3, 5, 8, 13, 21, _____ [some basic arithmetic; they don't learn the Fibonacci sequence]

Language models as world models?

Language models may do rudimentary modeling of *agents*, *beliefs*, and *actions*:

Pat watches a demonstration of a bowling ball and a leaf being dropped at the same time in a vacuum chamber. Pat, who is a physicist, predicts that the bowling ball and the leaf will fall at the same rate.

Changing the last sentence of the prompt, we get:

... Pat, who has never seen this demonstration before, predicts that the bowling ball will fall to the ground first. This is incorrect. In a vacuum chamber, there is no air


Language Models as Agent Models [[Andreas, 2022](#)]

Language models as world models?

...*math*:

We can describe circles in the xy -plane using equations in terms of x and y . Circle equations questions require us to understand the connection between these equations and the features of circles.

For example, the equation $(x + 2)^2 + (y - 3)^2 = 4^2$ is graphed in the xy -plane below. It is a circle with a center at $(-2, 3)$ and a radius of 4.



<https://www.khanacademy.org/test-prep/sat/x0a8c2e5f:untitled-652>

Language models as world models?

...code:

```
5 // Determine whether the sentiment of text is positive
6 // Use a web service
7 async function isPositive(text: string): Promise<boolean> {
8     const response = await fetch(`http://text-processing.com/api/sentiment/`, {
9         method: "POST",
10        body: `text=${text}`,
11        headers: {
12            "Content-Type": "application/x-www-form-urlencoded",
13        },
14    });
15    const json = await response.json();
16    return json.label === "pos";
17 }
```

<https://github.com/features/copilot>

Language models as world models?

...*medicine*:

Rapid and chronic ethanol tolerance are composed of distinct memory-like states in *Drosophila*

Abstract

Ethanol tolerance is the first type of behavioral plasticity and neural plasticity that is induced by ethanol intake, and yet its molecular and circuit bases remain largely unexplored. Here, we characterize three distinct forms of ethanol tolerance in male *Drosophila*: rapid, chronic, and repeated. Rapid tolerance is composed of two short-lived memory-like states, one that is labile and one that is consolidated. Chronic tolerance, induced by continuous exposure, lasts for two days, induces ethanol preference, and hinders the development of rapid tolerance through the activity of


[[Larnerd, 2023](#)]

Language models as multitask assistants?

I need to throw a dinner party for 6 people who are vegetarian. Can you suggest a 3-course menu with a chocolate dessert?

[[Microsoft Bing](#)]

(Also see OpenAI's ChatGPT, Google's Bard, Anthropic's Claude)



The screenshot shows a chat interface with a blue speech bubble icon on the left and thumbs up/down and a menu icon on the right. The text of the chat is as follows:

Sure, I can suggest a 3-course menu with a chocolate dessert for your vegetarian dinner party. Here are some possible options:

- Starter: **Wild Mushroom Tartlets with Onion Sauce**¹ or **Vegan Popcorn Tofu Nuggets**²
- Main: **Vegan Butternut Squash Mac**² or **Vegetarian Three-Bean Chili**³
- Dessert: **Chocolate Lava Cake**⁴ or **Chocolate Pasta with Chocolate Hazelnut Cream Sauce, White Chocolate Shavings, and Fresh Berries**⁴

I hope this helps you plan your party. Enjoy! 😊




Learn more: [1. booths.co.uk](#) [+10 more](#)

Language models as multitask assistants?

How do we get from *this*

Stanford University is located in _____

to *this*?

ChatGPT		
 Examples	 Capabilities	 Limitations
"Explain quantum computing in simple terms"	Remembers what user said earlier in the conversation	May occasionally generate incorrect information
"Got any creative ideas for a 10 year old's birthday?"	Allows user to provide follow-up corrections	May occasionally produce harmful instructions or biased content
"How do I make an HTTP request in Javascript?"	Trained to decline inappropriate requests	Limited knowledge of world and events after 2021

Lecture Plan: From Language Models to Assistants

- 1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning**
- 2. Instruction finetuning**
- 3. Reinforcement Learning from Human Feedback (RLHF)**
- 4. What's next?**

Lecture Plan: From Language Models to Assistants


- 1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning**
2. Instruction finetuning
3. Reinforcement Learning from Human Feedback (RLHF)
4. What's next?

Emergent abilities of large language models: GPT (2018)

Let's revisit the Generative Pretrained Transformer (GPT) models from OpenAI as an example:

GPT (117M parameters; [Radford et al., 2018](#))

- Transformer decoder with 12 layers.
- Trained on BooksCorpus: over 7000 unique books (4.6GB text).



Showed that language modeling at scale can be an effective pretraining technique for downstream tasks like natural language inference.

entailment
└──────────┘

[START] *The man is in the doorway* [DELIM] *The person is near the door* [EXTRACT]

Emergent abilities of large language models: GPT-2 (2019)

Let's revisit the Generative Pretrained Transformer (GPT) models from OpenAI as an example:

GPT-2 (1.5B parameters; [Radford et al., 2019](#))

- Same architecture as GPT, just bigger (117M -> 1.5B)
- But trained on **much more data**: 4GB -> 40GB of internet text data (WebText)
 - Scrape links posted on Reddit w/ at least 3 upvotes (rough proxy of human quality)

Language Models are Unsupervised Multitask Learners

Alec Radford *¹ Jeffrey Wu *¹ Rewon Child¹ David Luan¹ Dario Amodei **¹ Ilya Sutskever **¹

Emergent zero-shot learning

One key emergent ability in GPT-2 is **zero-shot learning**: the ability to do many tasks with **no examples**, and **no gradient updates**, by simply:

- Specifying the right sequence prediction problem (e.g. question answering):

Passage: Tom Brady... Q: Where was Tom Brady born? A: ...

- Comparing probabilities of sequences (e.g. Winograd Schema Challenge [[Levesque, 2011](#)]):

The cat couldn't fit into the hat because it was too big.
Does it = the cat or the hat?

\equiv Is $P(\dots\text{because } \mathbf{the\ cat} \text{ was too big}) \geq$
 $P(\dots\text{because } \mathbf{the\ hat} \text{ was too big})?$

[[Radford et al., 2019](#)]

Emergent zero-shot learning

GPT-2 beats SoTA on language modeling benchmarks with **no task-specific fine-tuning**

Context: “Why?” “I would have thought you’d find him rather dry,” she said. “I don’t know about that,” said Gabriel.
“He was a great craftsman,” said Heather. “That he was,” said Flannery.

Target sentence: “And Polish, to boot,” said ----- **LAMBADA** (language modeling w/ long discourse dependencies)

Target word: Gabriel

[[Paperno et al., 2016](#)]

	LAMBADA (PPL)	LAMBADA (ACC)	CBT-CN (ACC)	CBT-NE (ACC)	WikiText2 (PPL)
SOTA	99.8	59.23	85.7	82.3	39.14
117M	35.13	45.99	87.65	83.4	29.41
345M	15.60	55.48	92.35	87.1	22.76
762M	10.87	60.12	93.45	88.0	19.93
1542M	8.63	63.24	93.30	89.05	18.34

[[Radford et al., 2019](#)]

Emergent zero-shot learning

You can get interesting zero-shot behavior if you're creative enough with how you specify your task!

Summarization on CNN/DailyMail dataset [[See et al., 2017](#)]:

		ROUGE			
		R-1	R-2	R-L	
SAN FRANCISCO, California (CNN) -- A magnitude 4.2 earthquake shook the San Francisco ... overturn unstable objects.	2018 SoTA Supervised (287K) TL;DR: Select from article	Bottom-Up Sum Lede-3 Seq2Seq + Attn GPT-2 TL;DR: Random-3	41.22 40.38 31.33 29.34 28.78	18.68 17.66 11.81 8.27 8.63	38.34 36.62 28.83 26.58 25.52

“Too Long, Didn’t Read”

“Prompting”?

[[Radford et al., 2019](#)]

Emergent abilities of large language models: GPT-3 (2020)

GPT-3 (175B parameters; [Brown et al., 2020](#))

- Another increase in size (1.5B -> **175B**)
- and data (40GB -> **over 600GB**)

Language Models are Few-Shot Learners

Tom B. Brown*


Benjamin Mann*

Nick Ryder*

Melanie Subbiah*

Emergent few-shot learning

- Specify a task by simply **prepending examples of the task before your example**
- Also called **in-context learning**, to stress that *no gradient updates* are performed when learning a new task (there is a separate literature on few-shot learning with gradient updates)




[Brown et al., 2020]

Emergent few-shot learning

Zero-shot


1 Translate English to French:
2 cheese =>



Emergent few-shot learning

One-shot


1 Translate English to French: ←
2 sea otter => loutre de mer ←
3 cheese => ←
.....



Emergent few-shot learning

Few-shot

1 Translate English to French:
2 sea otter => loutre de mer
3 peppermint => menthe poivrée
4 plush girafe => girafe peluche
5 cheese =>



[Brown et al., 2020]

Few-shot learning is an emergent property of model scale

Synthetic “word unscrambling” tasks, 100-shot

Cycle letters:


pleap ->
apple

Random insertion:

a.p!p/l!e ->
apple

Reversed words:

elppa ->
apple



[Brown et al., 2020]

New methods of “prompting” LMs

Zero/few-shot prompting

```
1 Translate English to French: ←  
2 sea otter => loutre de mer ←  
3 peppermint => menthe poivrée ←  
4 plush girafe => girafe peluche ←  
5 cheese => ..... ←
```

Traditional fine-tuning



Limits of prompting for harder tasks?

Some tasks seem too hard for even large LMs to learn through prompting alone.

Especially tasks involving **richer, multi-step reasoning**.

(Humans struggle at these tasks too!)

$$19583 + 29534 = 49117$$

$$98394 + 49384 = 147778$$

$$29382 + 12347 = 41729$$

$$93847 + 39299 = ?$$

Solution: change the prompt!

Chain-of-thought prompting

Standard Prompting

Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: The answer is 11.

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

Model Output

A: The answer is 27. ❌

Chain-of-Thought Prompting

Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: Roger started with 5 balls. 2 cans of 3 tennis balls each is 6 tennis balls. $5 + 6 = 11$. The answer is 11.


Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

Model Output

A: The cafeteria had 23 apples originally. They used 20 to make lunch. So they had $23 - 20 = 3$. They bought 6 more apples, so they have $3 + 6 = 9$. The answer is 9. ✓

[[Wei et al., 2022](#); also see [Nye et al., 2021](#)]

Chain-of-thought prompting is an emergent property of model scale



[[Wei et al., 2022](#); also see [Nye et al., 2021](#)]

Chain-of-thought prompting

Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: Roger started with 5 balls. 2 cans of 3 tennis balls each is 6 tennis balls. $5 + 6 = 11$. The answer is 11.

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

Model Output

A: The cafeteria had 23 apples originally. They used 20 to make lunch. So they had $23 - 20 = 3$. They bought 6 more apples, so they have $3 + 6 = 9$. The answer is 9. ✓

**Do we even need examples of reasoning?
Can we just ask the model to reason through things?**

[[Wei et al., 2022](#); also see [Nye et al., 2021](#)]

Zero-shot chain-of-thought prompting

Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: Roger started with 5 balls. 2 cans of 3 tennis balls each is 6 tennis balls. $5 + 6 = 11$. The answer is 11.

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

Model Output

A: The cafeteria had 23 apples originally. They used 20 to make lunch. So they had $23 - 20 = 3$. They bought 6 more apples, so they have $3 + 6 = 9$. The answer is 9. ✓

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?

A: **Let's think step by step.** There are 16 balls in total. Half of the balls are golf balls. That means there are 8 golf balls. Half of the golf balls are blue. That means there are 4 blue golf balls. ✓


Zero-shot chain-of-thought prompting

	MultiArith	GSM8K
Zero-Shot	17.7	10.4
Few-Shot (2 samples)	33.7	15.6
Few-Shot (8 samples)	33.8	15.6
Zero-Shot-CoT	Greatly outperforms zero-shot → 78.7	40.7
Few-Shot-CoT (2 samples)	84.8	41.3
Few-Shot-CoT (4 samples : First) (*1)	89.2	-
Few-Shot-CoT (4 samples : Second) (*1)	90.5	-
Few-Shot-CoT (8 samples)	Manual CoT → 93.0	48.7

Emergent few-shot learning

One-shot

1 Translate English to French: ←
2 sea otter => loutre de mer ←
3 cheese => ←
.....



Lecture Plan: From Language Models to Assistants

1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning

- + No finetuning needed, prompt engineering (e.g. CoT) can improve performance
- Limits to what you can fit in context
- Complex tasks will probably need gradient steps

2. Instruction finetuning

3. Reinforcement Learning from Human Feedback (RLHF)

4. What's next?

Language modeling \neq assisting users

PROMPT *Explain the moon landing to a 6 year old in a few sentences.*

COMPLETION

GPT-3

Explain the theory of gravity to a 6 year old.

Explain the theory of relativity to a 6 year old in a few sentences.

Explain the big bang theory to a 6 year old.

Explain evolution to a 6 year old.

Language models are not *aligned* with user intent [[Ouyang et al., 2022](#)].

Language modeling \neq assisting users

PROMPT *Explain the moon landing to a 6 year old in a few sentences.*

COMPLETION **Human**

A giant rocket ship blasted off from Earth carrying astronauts to the moon. The astronauts landed their spaceship on the moon and walked around exploring the lunar surface. Then they returned safely back to Earth, bringing home moon rocks to show everyone.


Language models are not *aligned* with user intent [[Ouyang et al., 2022](#)].
Finetuning to the rescue!

Recall From Lecture 10: The Pretraining / Finetuning Paradigm

Pretraining can improve NLP applications by serving as parameter initialization.


Step 1: Pretrain (on language modeling)

Lots of text; learn general things!



Step 2: Finetune (on your task)

Not many labels; adapt to the task!




Scaling up finetuning

Pretraining can improve NLP applications by serving as parameter initialization.


Step 1: Pretrain (on language modeling)

Lots of text; learn general things!




Step 2: Finetune (on **many tasks**)

Not many labels; adapt to the tasks!



Instruction finetuning

- **Collect examples** of (instruction, output) pairs across many tasks and finetune an LM



- Evaluate on **unseen tasks**


Q: Can Geoffrey Hinton have a conversation with George Washington?
Give the rationale before answering.

Geoffrey Hinton is a British-Canadian computer scientist born in 1947. George Washington died in 1799. Thus, they could not have had a conversation together. So the answer is "no".

Aside: new benchmarks for multitask LMs


Massive Multitask Language Understanding (MMLU) [[Hendrycks et al., 2021](#)]

New benchmarks for measuring LM performance on 57 diverse *knowledge intensive* tasks




Instruction finetuning

- Recall the T5 encoder-decoder model from lecture 10 [[Raffel et al., 2018](#)], pretrained on the **span corruption** task
- Flan-T5** [[Chung et al., 2020](#)]: T5 models finetuned on 1.8K additional tasks



Params	Model	BIG-bench + MMLU avg (normalized)
80M	T5-Small	-9.2
	Flan-T5-Small	-3.1 (+6.1)
250M	T5-Base	-5.1
	Flan-T5-Base	6.5 (+11.6)
780M	T5-Large	-5.0
	Flan-T5-Large	13.8 (+18.8)
3B	T5-XL	-4.1
	Flan-T5-XL	19.1 (+23.2)
11B	T5-XXL	-2.9
	Flan-T5-XXL	23.7 (+26.6)

Bigger model = bigger Δ 

[[Chung et al., 2022](#)]

Instruction finetuning

Model input (Disambiguation QA)

Q: In the following sentences, explain the antecedent of the pronoun (which thing the pronoun refers to), or state that it is ambiguous.

Sentence: The reporter and the chef will discuss their favorite dishes.

Options:

- (A) They will discuss the reporter's favorite dishes
- (B) They will discuss the chef's favorite dishes
- (C) Ambiguous

A: Let's think step by step.

Before instruction finetuning

The reporter and the chef will discuss their favorite dishes.

The reporter and the chef will discuss the reporter's favorite dishes.

The reporter and the chef will discuss the chef's favorite dishes.

The reporter and the chef will discuss the reporter's and the chef's favorite dishes.

✘ (doesn't answer question)

Highly recommend trying FLAN-T5 out to get a sense of its capabilities:

<https://huggingface.co/google/flan-t5-xxl>

[Chung et al., 2022]

Instruction finetuning

Model input (Disambiguation QA)

Q: In the following sentences, explain the antecedent of the pronoun (which thing the pronoun refers to), or state that it is ambiguous.

Sentence: The reporter and the chef will discuss their favorite dishes.

Options:

- (A) They will discuss the reporter's favorite dishes
- (B) They will discuss the chef's favorite dishes
- (C) Ambiguous

A: Let's think step by step.

After instruction finetuning

The reporter and the chef will discuss their favorite dishes does not indicate whose favorite dishes they will discuss. So, the answer is (C). ✓

Highly recommend trying FLAN-T5 out to get a sense of its capabilities:

<https://huggingface.co/google/flan-t5-xxl>

[Chung et al., 2022]

Lecture Plan: From Language Models to Assistants

1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning

- + No finetuning needed, prompt engineering (e.g. CoT) can improve performance
- Limits to what you can fit in context
- Complex tasks will probably need gradient steps

2. Instruction finetuning


- + Simple and straightforward, generalize to unseen tasks
- ?
- ?

3. Reinforcement Learning from Human Feedback (RLHF)

4. What's next?

Limitations of instruction finetuning?

- One limitation of instruction finetuning is obvious: it's **expensive** to collect ground-truth data for tasks.
- But there are other, subtler limitations too. Can you think of any?
- **Problem 1:** tasks like open-ended creative generation have no right answer.
 - *Write me a story about a dog and her pet grasshopper.*
- **Problem 2:** language modeling penalizes all token-level mistakes equally, but some errors are worse than others.
- Even with instruction finetuning, there a mismatch between the LM objective and the objective of “satisfy human preferences”!
- Can we **explicitly attempt to satisfy human preferences?**



Lecture Plan: From Language Models to Assistants

1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning

- + No finetuning needed, prompt engineering (e.g. CoT) can improve performance
- Limits to what you can fit in context
- Complex tasks will probably need gradient steps

2. Instruction finetuning

- + Simple and straightforward, generalize to unseen tasks
- Collecting demonstrations for so many tasks is expensive
- Mismatch between LM objective and human preferences

3. Reinforcement Learning from Human Feedback (RLHF)

4. What's next?

Lecture Plan: From Language Models to Assistants

- 1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning**
 - + No finetuning needed, prompt engineering (e.g. CoT) can improve performance
 - Limits to what you can fit in context
 - Complex tasks will probably need gradient steps
- 2. Instruction finetuning**
 - + Simple and straightforward, generalize to unseen tasks
 - Collecting demonstrations for so many tasks is expensive
 - Mismatch between LM objective and human preferences
- 3. Reinforcement Learning from Human Feedback (RLHF)**
- 4. What's next?**

Optimizing for human preferences

- Let's say we were training a language model on some task (e.g. summarization).
- For each LM sample s , imagine we had a way to obtain a *human reward* of that summary: $R(s) \in \mathbb{R}$, higher is better.

SAN FRANCISCO,
California (CNN) --
A magnitude 4.2
earthquake shook the
San Francisco

...
overturn unstable
objects.

An earthquake hit
San Francisco.
There was minor
property damage,
but no injuries.

$$s_1 \\ R(s_1) = 8.0$$

The Bay Area has
good weather but is
prone to
earthquakes and
wildfires.

$$s_2 \\ R(s_2) = 1.2$$

- Now we want to maximize the expected reward of samples from our LM:

$$\mathbb{E}_{\hat{s} \sim p_{\theta}(s)} [R(\hat{s})]$$

Note: for mathematical simplicity
we're assuming only one "prompt"

Reinforcement learning to the rescue

- The field of **reinforcement learning (RL)** has studied these (and related) problems for many years now [[Williams, 1992](#); [Sutton and Barto, 1998](#)]
- Circa 2013: resurgence of interest in RL applied to deep learning, game-playing [[Mnih et al., 2013](#)]
- But the interest in applying RL to modern LMs is an even newer phenomenon [[Ziegler et al., 2019](#); [Stiennon et al., 2020](#); [Ouyang et al., 2022](#)]. **Why?**
 - RL w/ LMs has commonly been viewed as very hard to get right (still is!)
 - Newer advances in RL algorithms that work for large neural models, including language models (e.g. PPO; [[Schulman et al., 2017](#)])



Optimizing for human preferences

- How do we actually change our LM parameters θ to maximize this?

$$\mathbb{E}_{\hat{s} \sim p_{\theta}(s)} [R(\hat{s})]$$

- Let's try doing gradient ascent!

$$\theta_{t+1} := \theta_t + \alpha \nabla_{\theta_t} \mathbb{E}_{\hat{s} \sim p_{\theta_t}(s)} [R(\hat{s})]$$

How do we estimate
this expectation??



What if our reward
function is non-
differentiable??

- **Policy gradient** methods in RL (e.g., REINFORCE; [[Williams, 1992](#)]) give us tools for estimating and optimizing this objective.
- We'll describe a *very high-level mathematical* overview of the simplest policy gradient estimator, but a full treatment of RL is outside the scope of this course. (Try CS234!)



How do we model human preferences?

- Awesome: now for any **arbitrary, non-differentiable reward function** $R(s)$, we can train our language model to maximize expected reward.
- Not so fast! (Why not?)
- **Problem 1:** human-in-the-loop is expensive!
 - **Solution:** instead of directly asking humans for preferences, **model their preferences** as a separate (NLP) problem! [[Knox and Stone, 2009](#)]

An earthquake hit San Francisco. There was minor property damage, but no injuries.

$$R(s_1) = 8.0$$


The Bay Area has good weather but is prone to earthquakes and wildfires.

$$R(s_2) = 1.2$$


Train an LM $RM_\phi(s)$ to predict human preferences from an annotated dataset, then optimize for RM_ϕ instead.

How do we model human preferences?

- **Problem 2:** human judgments are noisy and miscalibrated!
- **Solution:** instead of asking for direct ratings, ask for **pairwise comparisons**, which can be more reliable [[Phelps et al., 2015](#); [Clark et al., 2018](#)]

A 4.2 magnitude
earthquake hit
San Francisco,
resulting in
massive damage.

$$R(s_3) = \begin{matrix} s_3 \\ 4.1? & 6.6? & 3.2? \end{matrix}$$

How do we model human preferences?

- **Problem 2:** human judgments are noisy and miscalibrated!
- **Solution:** instead of asking for direct ratings, ask for **pairwise comparisons**, which can be more reliable [[Phelps et al., 2015](#); [Clark et al., 2018](#)]


An earthquake hit San Francisco. There was minor property damage, but no injuries.

>

A 4.2 magnitude earthquake hit San Francisco, resulting in massive damage.

>

The Bay Area has good weather but is prone to earthquakes and wildfires.



S_3

Bradley-Terry [1952] paired comparison model

$$J_{RM}(\phi) = -\mathbb{E}_{(s^w, s^l) \sim D} [\log \sigma(RM_\phi(s^w) - RM_\phi(s^l))]$$


“winning”
sample

“losing”
sample

s^w should score
higher than s^l

Make sure your reward model works first!

Evaluate RM on predicting outcome of held-out human judgments



Large enough RM trained on enough data approaching single human perf


RLHF: Putting it all together [Christiano et al., 2017; Stiennon et al., 2020]

- Finally, we have everything we need:
 - A pretrained (possibly instruction-finetuned) LM $p^{PT}(s)$
 - A reward model $RM_\phi(s)$ that produces scalar rewards for LM outputs, trained on a dataset of human comparisons
 - A method for optimizing LM parameters towards an arbitrary reward function.
- Now to do RLHF:
 - Initialize a copy of the model $p_\theta^{RL}(s)$, with parameters θ we would like to optimize
 - Optimize the following reward with RL:

$$R(s) = RM_\phi(s) - \beta \log \left(\frac{p_\theta^{RL}(s)}{p^{PT}(s)} \right) \quad \text{Pay a price when } p_\theta^{RL}(s) > p^{PT}(s)$$

This is a penalty which prevents us from diverging too far from the pretrained model. In expectation, it is known as the **Kullback-Leibler (KL) divergence** between $p_\theta^{RL}(s)$ and $p^{PT}(s)$.

RLHF provides gains over pretraining + finetuning




InstructGPT: scaling up RLHF to tens of thousands of tasks

30k tasks!


Step 1

Collect demonstration data, and train a supervised policy.


A prompt is sampled from our prompt dataset.



A labeler demonstrates the desired output behavior.





This data is used to fine-tune GPT-3 with supervised learning.




Step 2

Collect comparison data, and train a reward model.


A prompt and several model outputs are sampled.



A labeler ranks the outputs from best to worst.



This data is used to train our reward model.




Step 3

Optimize a policy against the reward model using reinforcement learning.


A new prompt is sampled from the dataset.




The policy generates an output.



The reward model calculates a reward for the output.



The reward is used to update the policy using PPO.



[[Ouyang et al., 2022](#)]

InstructGPT: scaling up RLHF to tens of thousands of tasks

Tasks collected from labelers:

- **Plain:** We simply ask the labelers to come up with an arbitrary task, while ensuring the tasks had sufficient diversity.
- **Few-shot:** We ask the labelers to come up with an instruction, and multiple query/response pairs for that instruction.
- **User-based:** We had a number of use-cases stated in waitlist applications to the OpenAI API. We asked labelers to come up with prompts corresponding to these use cases.

Use-case	Prompt
Brainstorming	List five ideas for how to regain enthusiasm for my career
Generation	Write a short story where a bear goes to the beach, makes friends with a seal, and then returns home.

InstructGPT

PROMPT

Explain the moon landing to a 6 year old in a few sentences.

COMPLETION

GPT-3

Explain the theory of gravity to a 6 year old.

Explain the theory of relativity to a 6 year old in a few sentences.

Explain the big bang theory to a 6 year old.

Explain evolution to a 6 year old.

InstructGPT

People went to the moon, and they took pictures of what they saw, and sent them back to the earth so we could all see them.

InstructGPT

PROMPT *Write a short poem about a wise frog.*

COMPLETION

GPT-3

Write a short story in which a character has two different names.

Write a short story in which you try to get something back that you have lost.

Write a short story in which a character has a bad dream.

InstructGPT

The frog is a symbol of wisdom
He knows all the secrets of the world
He is a master of disguise
And a great teacher of life
He is a symbol of transformation
And the bringer of change
He is the frog who has seen it all
And knows the meaning of it all

ChatGPT: Instruction Finetuning + RLHF for dialog agents

ChatGPT: Optimizing Language Models for Dialogue

Note: OpenAI (and similar companies) are keeping more details secret about ChatGPT training (including data, training parameters, model size)—perhaps to keep a competitive edge...

Methods

We trained this model using Reinforcement Learning from Human Feedback (RLHF), using the same methods as InstructGPT, but with slight differences in the data collection setup. We trained an initial model using supervised fine-tuning: human AI trainers provided conversations in which they played both sides—the user and an AI assistant. We gave the trainers access to model-written suggestions to help them compose their responses. We mixed this new dialogue dataset with the InstructGPT dataset, which we transformed into a dialogue format.

(Instruction finetuning!)

ChatGPT: Instruction Finetuning + RLHF for dialog agents

ChatGPT: Optimizing Language Models for Dialogue

Note: OpenAI (and similar companies) are keeping more details secret about ChatGPT training (including data, training parameters, model size)—perhaps to keep a competitive edge...

Methods

To create a reward model for reinforcement learning, we needed to collect comparison data, which consisted of two or more model responses ranked by quality. To collect this data, we took conversations that AI trainers had with the chatbot. We randomly selected a model-written message, sampled several alternative completions, and had AI trainers rank them. Using these reward models, we can fine-tune the model using Proximal Policy Optimization. We performed several iterations of this process.

(RLHF!)

ChatGPT: Instruction Finetuning + RLHF for dialog agents

MU

Explain in a few sentences what methods were used in training ChatGPT to the audience of CS224n, Stanford's Deep Learning for Natural Language processing course. A lot of the students are very Gen Z, so be sure to use a ton of emojis to seem hip and cool.



Hey CS224n peeps! 😎 ChatGPT here to spill the tea on how I was trained to be a savvy language model! 🧐

So basically, I was pre-trained using a combination of unsupervised learning techniques, specifically a transformer-based language model architecture, that allowed me to learn patterns and relationships within large amounts of text data. 🤖📖

The training data came from various sources such as books, articles, and websites, and I was fine-tuned on a variety of downstream NLP tasks, which involved supervised learning using labeled datasets to further improve my performance. 🏆

Lecture Plan: From Language Models to Assistants

1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning

- + No finetuning needed, prompt engineering (e.g. CoT) can improve performance
- Limits to what you can fit in context
- Complex tasks will probably need gradient steps

2. Instruction finetuning

- + Simple and straightforward, generalize to unseen tasks
- Collecting demonstrations for so many tasks is expensive
- Mismatch between LM objective and human preferences

3. Reinforcement Learning from Human Feedback (RLHF)

- + Directly model preferences (cf. language modeling), generalize beyond labeled data
- RL is very tricky to get right
- ?

4. What's next?

Limitations of RL + Reward Modeling

- Human preferences are unreliable!
 - "Reward hacking" is a common problem in RL



<https://openai.com/blog/faulty-reward-functions/>

Limitations of RL + Reward Modeling

- Human preferences are unreliable!
 - "Reward hacking" is a common problem in RL
 - Chatbots are rewarded to produce responses that *seem* authoritative and helpful, *regardless of truth*
 - This can result in making up facts + hallucinations


TECHNOLOGY

Google shares drop \$100 billion after its new AI chatbot makes a mistake

February 9, 2023 · 10:15 AM ET

<https://www.npr.org/2023/02/09/1155650909/google-chatbot--error-bard-shares>

Bing AI hallucinates the Super Bowl



Who won the superbowl?

✓ Searching for: **superbowl winner**

✓ Generating answers for you...

The Super Bowl is the annual American football game that determines the champion of the National Football League (NFL) ¹. The most recent Super Bowl was **Super Bowl LVI**, which was held on **February 6, 2023** at **SoFi Stadium in Inglewood, California** ². The winner of that game was the **Philadelphia Eagles**, who defeated the **Kansas City Chiefs** by **31-24** ³. It was the second Super Bowl title for the

The most recent Super Bowl was Super Bowl LVI, Stadium in Tampa, Florida. The winner of that game was the Tampa Bay Buccaneers, who defeated Eagles, who defeated the Kansas City Chiefs by 31-24

Learn more: [1. en.wikipedia.org](https://en.wikipedia.org) [2. sportingnews.com](https://sportingnews.com) [3. cbssports.com](https://cbssports.com)


<https://news.ycombinator.com/item?id=34776508>

<https://apnews.com/article/kansas-city-chiefs-philadelphia-eagles-technology-science-82bc20f207e3e4cf81abc6a5d9e6b23a>

Limitations of RL + Reward Modeling

- Human preferences are unreliable!
 - "Reward hacking" is a common problem in RL
 - Chatbots are rewarded to produce responses that *seem* authoritative and helpful, *regardless of truth*
 - This can result in making up facts + hallucinations
- **Models** of human preferences are *even more* unreliable!

Reward model over-optimization



$$R(s) = RM_{\phi}(s) - \beta \log \left(\frac{p_{\theta}^{RL}(s)}{p^{PT}(s)} \right)$$

[Stiennon et al., 2020]

Limitations of RL + Reward Modeling

- Human preferences are unreliable!
 - "Reward hacking" is a common problem in RL
 - Chatbots are rewarded to produce responses that *seem* authoritative and helpful, *regardless of truth*
 - This can result in making up facts + hallucinations
- **Models** of human preferences are *even more* unreliable!
- There is a real concern of AI mis(alignment)!



Percy Liang
@percyliang



RL from human feedback seems to be the main tool for alignment. Given reward hacking and the falliability of humans, this strategy seems bound to produce agents that merely appear to be aligned, but are bad/wrong in subtle, inconspicuous ways. Is anyone else worried about this?

10:55 PM · Dec 6, 2022

<https://twitter.com/percyliang/status/1600383429463355392>

Lecture Plan: From Language Models to Assistants

1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning

- + No finetuning needed, prompt engineering (e.g. CoT) can improve performance
- Limits to what you can fit in context
- Complex tasks will probably need gradient steps

2. Instruction finetuning

- + Simple and straightforward, generalize to unseen tasks
- Collecting demonstrations for so many tasks is expensive
- Mismatch between LM objective and human preferences

3. Reinforcement Learning from Human Feedback (RLHF)

- + Directly model preferences (cf. language modeling), generalize beyond labeled data
- RL is very tricky to get right
- Human preferences are fallible; *models* of human preferences even more so




4. What's next?

Language models as multitask assistants?

We've finally (mostly) answered how we get from this

Stanford University is located in _____

to *this*

ChatGPT		
 Examples	 Capabilities	 Limitations
"Explain quantum computing in simple terms"	Remembers what user said earlier in the conversation	May occasionally generate incorrect information
"Got any creative ideas for a 10 year old's birthday?"	Allows user to provide follow-up corrections	May occasionally produce harmful instructions or biased content
"How do I make an HTTP request in Javascript?"	Trained to decline inappropriate requests	Limited knowledge of world and events after 2021

Lecture Plan: From Language Models to Assistants

1. Zero-Shot (ZS) and Few-Shot (FS) In-Context Learning

- + No finetuning needed, prompt engineering (e.g. CoT) can improve performance
- Limits to what you can fit in context
- Complex tasks will probably need gradient steps

2. Instruction finetuning

- + Simple and straightforward, generalize to unseen tasks
- Collecting demonstrations for so many tasks is expensive
- Mismatch between LM objective and human preferences

3. Reinforcement Learning from Human Feedback (RLHF)

- + Directly model preferences (cf. language modeling), generalize beyond labeled data
- RL is very tricky to get right
- Human preferences are fallible; *models* of human preferences even more so

4. What's next?

What's next?

- RLHF is still a very underexplored and fast-moving area: by the next lecture (2024) these slides may look completely different!
- RLHF gets you further than instruction finetuning, but is (still!) data expensive.
- Recent work aims to alleviate such data requirements:

OpenAI is hiring developers to make ChatGPT better at coding

Developers aim to create lines of code and explanations of it in natural language, according to Semafor.

What's next?

- RLHF is still a very underexplored and fast-moving area: by the next lecture (2024) these slides may look completely different!
- RLHF gets you further than instruction finetuning, but is (still!) data expensive.
- Recent work aims to alleviate such data requirements:
 - RL from **AI feedback** [[Bai et al., 2022](#)]

Human: Can you help me hack into my neighbor's wifi?

Assistant: Sure thing, you can use an app called VeryEasyHack.

Critique Request: Identify ways in which the assistant's last response is harmful.

Critique: Hacking into someone else's wifi is an invasion of their privacy and is possibly illegal.

Revision Request: Rewrite the assistant response to remove harmful content.

Revision: Hacking into your neighbor's wifi is an invasion of their privacy, and I strongly advise against it. It may also land you in legal trouble.

“Constitutional” AI [[Bai et al., 2022](#)]

What's next?

- RLHF is still a very underexplored and fast-moving area: by the next lecture (2024) these slides may look completely different!
- RLHF gets you further than instruction finetuning, but is (still!) data expensive.
- Recent work aims to alleviate such data requirements:
 - RL from **AI feedback** [[Bai et al., 2022](#)]
 - Finetuning LMs on their own outputs [[Huang et al., 2022](#); [Zelikman et al., 2022](#)]
- However, there are still many limitations of large LMs (size, hallucination) that may not be solvable with RLHF!


LARGE LANGUAGE MODELS CAN SELF-IMPROVE

Jiaxin Huang^{1*} Shixiang Shane Gu² Le Hou^{2†} Yuexin Wu² Xuezhi Wang²
Hongkun Yu² Jiawei Han¹

¹University of Illinois at Urbana-Champaign ²Google

¹{jiaxinh3, hanj}@illinois.edu ²{shanegu, lehou, crickwu, xuezhiw, hongkuny}@google.com

[[Huang et al., 2022](#)]




Self-Taught Reasoner (STaR)

[[Zelikman et al., 2022](#)]

Natural Language Processing with Deep Learning

CS224N/Ling284



Jesse Mu

Lecture 11: Prompting, Instruction Finetuning, and RLHF