

Python For Data Science Cheat Sheet

Python Basics

Learn More Python for Data Science [Interactively](#) at www.datacamp.com



Variables and Data Types

Variable Assignment

```
>>> x=5  
>>> x  
5
```

Calculations With Variables

>>> x+2 7	Sum of two variables
>>> x-2 3	Subtraction of two variables
>>> x*2 10	Multiplication of two variables
>>> x**2 25	Exponentiation of a variable
>>> x%2 1	Remainder of a variable
>>> x/float(2) 2.5	Division of a variable

Types and Type Conversion

str()	'5', '3.45', 'True'	Variables to strings
int()	5, 3, 1	Variables to integers
float()	5.0, 1.0	Variables to floats
bool()	True, True, True	Variables to booleans

Asking For Help

```
>>> help(str)
```

Strings

```
>>> my_string = 'thisStringIsAwesome'  
>>> my_string  
'thisStringIsAwesome'
```

String Operations

```
>>> my_string * 2  
'thisStringIsAwesomethisStringIsAwesome'  
>>> my_string + 'Innit'  
'thisStringIsAwesomeInnit'  
>>> 'm' in my_string  
True
```

Lists

```
>>> a = 'is'  
>>> b = 'nice'  
>>> my_list = ['my', 'list', a, b]  
>>> my_list2 = [[4,5,6,7], [3,4,5,6]]
```

Selecting List Elements

Index starts at 0

Subset

```
>>> my_list[1]  
>>> my_list[-3]
```

Slice

```
>>> my_list[1:3]  
>>> my_list[1:]  
>>> my_list[:3]  
>>> my_list[:]
```

Subset Lists of Lists

```
>>> my_list2[1][0]  
>>> my_list2[1][:2]
```

Select item at index 1
Select 3rd last item

Select items at index 1 and 2
Select items after index 0

Select items before index 3

Copy my_list

my_list[list][itemOfList]

List Operations

```
>>> my_list + my_list  
['my', 'list', 'is', 'nice', 'my', 'list', 'is', 'nice']  
>>> my_list * 2  
['my', 'list', 'is', 'nice', 'my', 'list', 'is', 'nice']  
>>> my_list2 > 4  
True
```

List Methods

```
>>> my_list.index('a')  
>>> my_list.count('a')  
>>> my_list.append('!')  
>>> my_list.remove('!')  
>>> del(my_list[0:1])  
>>> my_list.reverse()  
>>> my_list.extend('!')  
>>> my_list.pop(-1)  
>>> my_list.insert(0, '!')  
>>> my_list.sort()
```

Get the index of an item
Count an item
Append an item at a time
Remove an item
Remove an item
Reverse the list
Append an item
Remove an item
Insert an item
Sort the list

String Operations

Index starts at 0

```
>>> my_string[3]  
>>> my_string[4:9]
```

String Methods

```
>>> my_string.upper()  
>>> my_string.lower()  
>>> my_string.count('w')  
>>> my_string.replace('e', 'i')  
>>> my_string.strip()
```

String to uppercase
String to lowercase
Count String elements
Replace String elements
Strip whitespaces

Also see NumPy Arrays

Import libraries

```
>>> import numpy  
>>> import numpy as np  
Selective import  
>>> from math import pi
```

pandas Data analysis

Machine learning

NumPy Scientific computing

matplotlib 2D plotting

Libraries

Install Python



ANACONDA

Leading open data science platform
powered by Python



Free IDE that is included
with Anaconda



Create and share
documents with live code,
visualizations, text, ...

Numpy Arrays

```
>>> my_list = [1, 2, 3, 4]  
>>> my_array = np.array(my_list)  
>>> my_2darray = np.array([[1,2,3], [4,5,6]])
```

Selecting Numpy Array Elements

Index starts at 0

Subset

```
>>> my_array[1]  
2
```

Select item at index 1

Slice

```
>>> my_array[0:2]  
array([1, 2])
```

Select items at index 0 and 1

Subset 2D Numpy arrays

```
>>> my_2darray[:,0]  
array([1, 4])
```

my_2darray[rows, columns]

Numpy Array Operations

```
>>> my_array > 3  
array([False, False, False, True], dtype=bool)  
>>> my_array * 2  
array([2, 4, 6, 8])  
>>> my_array + np.array([5, 6, 7, 8])  
array([6, 8, 10, 12])
```

Numpy Array Functions

```
>>> my_array.shape  
>>> np.append(other_array)  
>>> np.insert(my_array, 1, 5)  
>>> np.delete(my_array, [1])  
>>> np.mean(my_array)  
>>> np.median(my_array)  
>>> my_array.corrcoef()  
>>> np.std(my_array)
```

Get the dimensions of the array
Append items to an array
Insert items in an array
Delete items in an array
Mean of the array
Median of the array
Correlation coefficient
Standard deviation



Python For Data Science Cheat Sheet


Jupyter Notebook

Learn More Python for Data Science Interactively at www.DataCamp.com



Saving/Loading Notebooks

Create new notebook



Make a copy of the current notebook

Save current notebook and record checkpoint

Preview of the printed notebook

Close notebook & stop running any scripts

Open an existing notebook

Rename notebook

Revert notebook to a previous checkpoint

Download notebook as

- IPython notebook
- Python
- HTML
- Markdown
- reST
- LaTeX
- PDF

Kernels provide computation and communication with front-end interfaces like the notebooks. There are three main kernels:



IPython



IRkernel




Julia

Installing Jupyter Notebook will automatically install the IPython kernel.

Restart kernel

Restart kernel & run all cells

Restart kernel & run all cells



Interrupt kernel

Interrupt kernel & clear all output

Connect back to a remote notebook

Run other installed kernels

Command Mode:



Edit Mode:



Writing Code And Text

Code and text are encapsulated by 3 basic cell types: markdown cells, code cells, and raw NBConvert cells.

Edit Cells

Cut currently selected cells to clipboard

Copy cells from clipboard to current cursor position

Paste cells from clipboard above current cell

Paste cells from clipboard below current cell

Paste cells from clipboard on top of current cell

Delete current cells

Revert "Delete Cells" invocation

Split up a cell from current cursor position

Merge current cell with the one above

Merge current cell with the one below

Merge current cell with the one above

Move current cell down

Move current cell up

Find and replace in selected cells

Adjust metadata underlying the current notebook

Find and replace in selected cells

Remove cell attachments

Copy attachments of current cell

Paste attachments of current cell

Insert image in selected cells

Insert Cells

Add new cell above the current one



Add new cell below the current one

Working with Different Programming Languages


Kernels provide computation and communication with front-end interfaces like the notebooks. There are three main kernels:

Widgets

Notebook widgets provide the ability to visualize and control changes in your data, often as a control like a slider, textbox, etc.

You can use them to build interactive GUIs for your notebooks or to synchronize stateful and stateless information between Python and JavaScript.

Download serialized state of all widget models in use



- Save notebook with interactive widgets
- Embed current widgets

Command Mode:




Edit Mode:



Executing Cells

Run selected cell(s)



Run current cells down and create a new one below

Run all cells

Run current cells down and create a new one above

Run all cells below the current cell

Run all cells above the current cell

Run all cells below the current cell


Change the cell type of current cell

toggle, toggle scrolling and clear current outputs

toggle, toggle scrolling and clear all output

View Cells

Toggle display of Jupyter logo and filename



Toggle line numbers in cells

Toggle display of toolbar


Toggle display of cell action icons:

- None
- Edit metadata
- Raw cell format
- Slideshow
- Attachments
- Tags

- Save and checkpoint
- Insert cell below
- Cut cell
- Copy cell(s)
- Paste cell(s) below
- Move cell up
- Move cell down
- Run current cell
- Interrupt kernel
- Restart kernel
- Display characteristics
- Open command palette
- Current kernel
- Kernel status
- Log out from notebook server


Asking For Help

Walk through a UI tour




List of built-in keyboard shortcuts

Edit the built-in keyboard shortcuts




Notebook help topics

Description of markdown available in notebook




Information on unofficial Jupyter Notebook extensions

Python help topics




IPython help topics

NumPy help topics




SciPy help topics

Matplotlib help topics



Sympy help topics

Pandas help topics



About Jupyter Notebook



DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

NumPy Basics

Learn Python for Data Science Interactively at www.DataCamp.com



NumPy


The NumPy library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays.

Use the following import convention:

```
>>> import numpy as np
```



NumPy Arrays



Creating Arrays

```
>>> a = np.array([1,2,3])
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)]),
      dtype = float)
```

Initial Placeholders

```
>>> np.zeros((3,4))
>>> np.ones((2,3,4),dtype=np.int16)
>>> d = np.arange(10,25,5)

>>> np.linspace(0,2,9)

>>> e = np.full((2,2),7)
>>> f = np.eye(2)
>>> np.random.random((2,2))
>>> np.empty((3,2))
```

Create an array of zeros
Create an array of ones
Create an array of evenly spaced values (step value)
Create an array of evenly spaced values (number of samples)
Create a constant array
Create a 2X2 identity matrix
Create an array with random values
Create an empty array

I/O

Saving & Loading On Disk

```
>>> np.save('my_array', a)
>>> np.savetxt('array.npz', a, b)
>>> np.load('my_array.npy')
```

Saving & Loading Text Files

```
>>> np.loadtxt("myfile.txt")
>>> np.genfromtxt("my_file.csv", delimiter=',')
>>> np.savetxt("myarray.txt", a, delimiter=" ")
```

Data Types

```
>>> np.int64
>>> np.float32
>>> np.complex
>>> np.bool
>>> np.object
>>> np.string_
>>> np_unicode_
```

Signed 64-bit integer types
Standard double-precision floating point
Complex numbers represented by 128 floats
Boolean type storing TRUE and FALSE values
Python object type
Fixed-length string type
Fixed-length unicode type

Inspecting Your Array

```
>>> a.shape
>>> len(a)
>>> b.ndim
>>> e.size
>>> b.dtype
>>> b.dtype.name
>>> b.astype(int)
```

Array dimensions
Length of array
Number of array dimensions
Number of array elements
Data type of array elements
Name of data type
Convert an array to a different type

Asking For Help

```
>>> np.info(np.ndarray.dtype)
```

Array Mathematics

Arithmetic Operations

```
>>> g = a - b
      array([[-0.5,  0.,  0.],
             [-3., -3., -3.]])
>>> np.subtract(a,b)
>>> b + a
      array([[ 2.5,  4.,  6.],
             [ 5.,  7.,  9.]])
>>> np.add(b,a)
>>> a / b
      array([[ 0.66666667,  1.,
              [ 0.25,  0.4,  0.5],
              [ 1.5,  4.,  9.],
              [ 4.,  10.,  18.]])
>>> np.multiply(a,b)
>>> np.exp(b)
>>> np.sqrt(b)
>>> np.sin(a)
>>> np.cos(b)
>>> np.log(a)
>>> e.dot(f)
      array([[ 7.,  7.],
             [ 7.,  7.]])]
```

Subtraction
Addition
Addition
Division
Division
Multiplication

Multiplication
Exponentiation
Square root
Print sines of an array
Element-wise cosine
Element-wise natural logarithm
Dot product

Comparison

```
>>> a == b
      array([[False,  True,  True],
             [False, False, False]], dtype=bool)
>>> a < 2
      array([True, False, False], dtype=bool)
>>> np.array_equal(a, b)
```

Element-wise comparison
Element-wise comparison
Array-wise comparison

Aggregate Functions

```
>>> a.sum()
>>> a.min()
>>> b.max(axis=0)
>>> b.cumsum(axis=1)
>>> a.mean()
>>> b.median()
>>> a.correlcoef()
>>> np.std(b)
```

Array-wise sum
Array-wise minimum value
Maximum value of an array row
Cumulative sum of the elements
Mean
Median
Correlation coefficient
Standard deviation

Copying Arrays

```
>>> h = a.view()
>>> np.copy(a)
>>> h = a.copy()
```

Create a view of the array with the same data
Create a copy of the array
Create a deep copy of the array

Sorting Arrays

```
>>> a.sort()
>>> c.sort(axis=0)
```

Sort an array
Sort the elements of an array's axis

Subsetting, Slicing, Indexing

Subsetting

```
>>> a[2]
      3
>>> b[1,2]
      6.0
```

1	2	3
1.5	2	3
4	5	6

Select the element at the 2nd index
Select the element at row 0 column 2 (equivalent to b[1][2])

Slicing

```
>>> a[0:2]
      array([1, 2])
>>> b[0:2,1]
      array([ 2.,  5.])
```

1	2	3
1.5	2	3
4	5	6

Select items at index 0 and 1
Select items at rows 0 and 1 in column 1
Select all items at row 0 (equivalent to b[0:1, :])
Same as [1, :, :]

Reversed array a

```
>>> a[ : :-1]
      array([3, 2, 1])
```

1	2	3
1.5	2	3
4	5	6

Reversed array a

Boolean Indexing

```
>>> a[a<2]
      array([1])
```

Select elements from a less than 2
Select elements (1,0),(0,1),(1,2) and (0,0)
Select a subset of the matrix's rows and columns

Array Manipulation

Transposing Array

```
>>> i = np.transpose(b)
>>> i.T
```

Permute array dimensions
Permute array dimensions

Changing Array Shape

```
>>> b.ravel()
>>> g.reshape(3,-2)
```

Flatten the array
Reshape, but don't change data

Adding/Removing Elements

```
>>> h.resize((2,6))
>>> np.append(h,g)
>>> np.insert(a, 1, 5)
>>> np.delete(a,[1])
```

Return a new array with shape (2,6)
Append items to an array
Insert items in an array
Delete items from an array

Combining Arrays

```
>>> np.concatenate((a,d),axis=0)
      array([ 1,  2,  3, 10, 15, 20])
>>> np.vstack((a,b))
      array([[ 1.,  2.,  3.],
             [ 1.5,  2.,  3.],
             [ 4.,  5.,  6.]])
>>> np.r_[e,f]
>>> np.hstack((e,f))
      array([[ 7.,  7.,  1.,  0.],
             [ 7.,  7.,  0.,  1.]])
>>> np.column_stack((a,d))
      array([[ 1, 10],
             [ 2, 15],
             [ 3, 20]])
>>> np.c_[a,d]
```

Concatenate arrays
Stack arrays vertically (row-wise)
Stack arrays vertically (row-wise)
Stack arrays horizontally (column-wise)

Create stacked column-wise arrays

Create stacked column-wise arrays

Splitting Arrays

```
>>> np.hsplit(a,3)
      [array([1]),array([2]),array([3])]
>>> np.vsplit(c,2)
      [array([[ 1.5,  2.,  3.],
              [ 4.,  5.,  6.]]),
       array([[ 3.,  2.,  3.],
              [ 4.,  5.,  6.]])]
```

Split the array horizontally at the 3rd index
Split the array vertically at the 2nd index



Python For Data Science Cheat Sheet

Also see NumPy

SciPy - Linear Algebra

Learn More Python for Data Science [Interactively](#) at www.datacamp.com



SciPy

The SciPy library is one of the core packages for scientific computing that provides mathematical algorithms and convenience functions built on the NumPy extension of Python.



Interacting With NumPy

[Also see NumPy](#)

```
>>> import numpy as np  
>>> a = np.array([1,2,3])  
>>> b = np.array([(1+5j),2j,3j], [4j,5j,6j])  
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)])
```

Index Tricks

```
>>> np.mgrid[0:5,0:5]  
>>> np.ogrid[0:2,0:2]  
>>> np.r_[3,[0]*5,-1:1:10j]  
>>> np.c_[b,c]
```

Create a dense meshgrid
Create an open meshgrid
Stack arrays vertically (row-wise)
Create stacked column-wise arrays

Shape Manipulation

```
>>> np.transpose(b)  
>>> b.flatten()  
>>> np.hstack((b,c))  
>>> np.vstack((a,b))  
>>> np.hsplit(c,2)  
>>> np.vsplit(d,2)
```

Polynomials

```
>>> from numpy import poly1d  
>>> p = poly1d([3,4,5])
```

Create a polynomial object

Vectorizing Functions

```
>>> def myfunc(a):  
    if a < 0:  
        return a**2  
    else:  
        return a/2  
>>> np.vectorize(myfunc)
```

Vectorize functions

Type Handling

```
>>> np.real(c)  
>>> np.imag(c)  
>>> np.real_if_close(c,tol=1000)  
>>> np.cast['f'](np.pi)
```

Return the real part of the array elements
Return the imaginary part of the array elements
Return a real array if complex parts close to 0
Cast object to a data type

Other Useful Functions

```
>>> np.angle(b,deg=True)  
>>> g = np.linspace(0,np.pi,num=5)  
>>> g[3:] += np.pi  
>>> np.unwrap(g)  
>>> np.logspace(0,10,3)  
>>> np.select([c<4],[c*2])  
  
>>> misc.factorial(a)  
>>> misc.comb(10,3,exact=True)  
>>> misc.central_diff_weights(3)  
>>> misc.derivative(myfunc,1.0)
```

Return the angle of the complex argument
Create an array of evenly spaced values
(number of samples)
Unwrap
Create an array of evenly spaced values (log scale)
Return values from a list of arrays depending on conditions
Factorial
Combine N things taken at k time
Weights for N-point central derivative
Find the n-th derivative of a function at a point

Linear Algebra

You'll use the linalg and sparse modules. Note that `scipy.linalg` contains and expands on `numpy.linalg`.

```
>>> from scipy import linalg, sparse
```

Creating Matrices

```
>>> A = np.matrix(np.random.random((2,2)))  
>>> B = np.asmatrix(b)  
>>> C = np.mat(np.random.random((10,5)))  
>>> D = np.mat([[3,4], [5,6]])
```

Basic Matrix Routines

Inverse

```
>>> A.I  
>>> linalg.inv(A)  
>>> A.T  
>>> A.H  
>>> np.trace(A)
```

Norm

```
>>> linalg.norm(A)  
>>> linalg.norm(A,1)  
>>> linalg.norm(A,np.inf)
```

Rank

```
>>> np.linalg.matrix_rank(C)
```

Determinant

```
>>> linalg.det(A)
```

Solving linear problems

```
>>> linalg.solve(A,b)  
>>> E = np.mat(a).T  
>>> linalg.lstsq(D,E)
```

Generalized inverse

```
>>> linalg.pinv(C)  
>>> linalg.pinv2(C)
```

Creating Sparse Matrices

```
>>> F = np.eye(3, k=1)  
>>> G = np.mat(np.identity(2))  
>>> C[C > 0.5] = 0  
>>> H = sparse.csr_matrix(C)  
>>> I = sparse.csc_matrix(D)  
>>> J = sparse.dok_matrix(A)  
>>> E.todense()  
>>> sparse.isspmatrix_csc(A)
```

Inverse
Inverse
Transpose matrix
Conjugate transposition
Trace

Frobenius norm
L1 norm (max column sum)
L inf norm (max row sum)

Matrix rank

Determinant

Solver for dense matrices
Solver for dense matrices
Least-squares solution to linear matrix equation

Compute the pseudo-inverse of a matrix
(least-squares solver)
Compute the pseudo-inverse of a matrix
(SVD)

Create a 2x2 identity matrix
Create a 2x2 identity matrix

Compressed Sparse Row matrix
Compressed Sparse Column matrix
Dictionary Of Keys matrix
Sparse matrix to full matrix
Identify sparse matrix

Sparse Matrix Routines

Inverse

```
>>> sparse.linalg.inv(I)
```

Norm

```
>>> sparse.linalg.norm(I)
```

Solving linear problems

```
>>> sparse.linalg.spsolve(H,I)
```

Inverse

Norm

Solver for sparse matrices

Sparse Matrix Functions

```
>>> sparse.linalg.expm(I)
```

Sparse matrix exponential

Matrix Functions

Addition

```
>>> np.add(A,D)
```

Subtraction

```
>>> np.subtract(A,D)
```

Division

```
>>> np.divide(A,D)
```

Multiplication

```
>>> np.multiply(D,A)  
>>> np.dot(A,D)  
>>> np.vdot(A,D)  
>>> np.inner(A,D)  
>>> np.outer(A,D)  
>>> np.tensordot(A,D)  
>>> np.kron(A,D)
```

Exponential Functions

```
>>> linalg.expm(A)  
>>> linalg.expm2(A)  
>>> linalg.expm3(D)
```

Logarithm Function

```
>>> linalg.logm(A)
```

Trigonometric Functions

```
>>> linalg.sinm(D)  
>>> linalg.cosm(D)  
>>> linalg.tanm(A)
```

Hyperbolic Trigonometric Functions

```
>>> linalg.sinhm(D)  
>>> linalg.coshm(D)  
>>> linalg.tanhm(A)
```

Matrix Sign Function

```
>>> np.signm(A)
```

Matrix Square Root

```
>>> linalg.sqrtm(A)
```

Arbitrary Functions

```
>>> linalg.funm(A, lambda x: x*x)
```

Addition

Subtraction

Division

Multiplication

Dot product

Vector dot product

Inner product

Outer product

Tensor dot product

Kronecker product

Matrix exponential
Matrix exponential (Taylor Series)
Matrix exponential (eigenvalue decomposition)

Matrix logarithm

Matrix sine

Matrix cosine

Matrix tangent

Hypberbolic matrix sine

Hyperbolic matrix cosine

Hyperbolic matrix tangent

Matrix sign function

Matrix square root

Evaluate matrix function

Decompositions

Eigenvalues and Eigenvectors

```
>>> la, v = linalg.eig(A)  
  
>>> l1, l2 = la  
>>> v[:,0]  
>>> v[:,1]  
>>> linalg.eigvals(A)
```

Singular Value Decomposition

```
>>> U,s,Vh = linalg.svd(B)  
>>> M,N = B.shape  
>>> Sig = linalg.diagsvd(s,M,N)
```

LU Decomposition

```
>>> P,L,U = linalg.lu(C)
```

Solve ordinary or generalized eigenvalue problem for square matrix
Unpack eigenvalues
First eigenvector
Second eigenvector
Unpack eigenvalues

Singular Value Decomposition (SVD)

Construct sigma matrix in SVD

LU Decomposition

Sparse Matrix Decompositions

```
>>> la, v = sparse.linalg.eigs(F,1)  
>>> sparse.linalg.svds(H, 2)
```

Eigenvalues and eigenvectors
SVD

Asking For Help

```
>>> help(scipy.linalg.diagsvd)  
>>> np.info(np.matrix)
```

DataCamp

Learn Python for Data Science [Interactively](#)



Python For Data Science Cheat Sheet

Pandas Basics

Learn Python for Data Science Interactively at www.DataCamp.com



Pandas

The Pandas library is built on NumPy and provides easy-to-use data structures and data analysis tools for the Python programming language.



Use the following import convention:

```
>>> import pandas as pd
```

Pandas Data Structures

Series

A one-dimensional labeled array capable of holding any data type

a	3
b	-5
c	7
d	4

```
>>> s = pd.Series([3, -5, 7, 4], index=['a', 'b', 'c', 'd'])
```

DataFrame

Columns

	Country	Capital	Population
0	Belgium	Brussels	11190846
1	India	New Delhi	1303171035
2	Brazil	Brasilia	207847528

```
>>> data = {'Country': ['Belgium', 'India', 'Brazil'],
   >>>          'Capital': ['Brussels', 'New Delhi', 'Brasilia'],
   >>>          'Population': [11190846, 1303171035, 207847528]}
>>> df = pd.DataFrame(data,
   >>>          columns=['Country', 'Capital', 'Population'])
```

I/O

Read and Write to CSV

```
>>> pd.read_csv('file.csv', header=None, nrows=5)
>>> df.to_csv('myDataFrame.csv')
```

Read and Write to Excel

```
>>> pd.read_excel('file.xlsx')
>>> pd.to_excel('dir/myDataFrame.xlsx', sheet_name='Sheet1')
Read multiple sheets from the same file
>>> xlsx = pd.ExcelFile('file.xls')
>>> df = pd.read_excel(xlsx, 'Sheet1')
```

Asking For Help

```
>>> help(pd.Series.loc)
```

Selection

Getting

```
>>> s['b']
-5
>>> df[1:]
   Country    Capital  Population
1  India      New Delhi     1303171035
2  Brazil     Brasilia     207847528
```

Also see NumPy Arrays

Get one element

Get subset of a DataFrame

Selecting, Boolean Indexing & Setting

By Position

```
>>> df.iloc[[0], [0]]
'Belgium'
>>> df.iat[[0], [0]]
'Belgium'
```

By Label

```
>>> df.loc[[0], ['Country']]
'Belgium'
>>> df.at[[0], ['Country']]
'Belgium'
```

By Label/Position

```
>>> df.ix[2]
   Country      Brazil
   Capital    Brasilia
   Population  207847528
```

```
>>> df.ix[:, 'Capital']
0    Brussels
1   New Delhi
2    Brasilia
```

```
>>> df.ix[1, 'Capital']
'New Delhi'
```

Boolean Indexing

```
>>> s[~(s > 1)]
>>> s[(s < -1) | (s > 2)]
>>> df[df['Population'] > 1200000000]
```

Setting

```
>>> s['a'] = 6
```

Select single value by row & column

Select single value by row & column labels

Select single row of subset of rows

Select a single column of subset of columns

Select rows and columns

Series s where value is not >1
s where value is <-1 or >2

Use filter to adjust DataFrame

Set index a of Series s to 6

Dropping

```
>>> s.drop(['a', 'c'])
>>> df.drop('Country', axis=1)
```

Drop values from rows (axis=0)

Drop values from columns (axis=1)

Sort & Rank

```
>>> df.sort_index()
>>> df.sort_values(by='Country')
>>> df.rank()
```

Sort by labels along an axis

Sort by the values along an axis

Assign ranks to entries

Retrieving Series/DataFrame Information

Basic Information

```
>>> df.shape
>>> df.index
>>> df.columns
>>> df.info()
>>> df.count()
```

(rows,columns)
Describe index
Describe DataFrame columns
Info on DataFrame
Number of non-NA values

Summary

```
>>> df.sum()
>>> df.cumsum()
>>> df.min() / df.max()
>>> df.idxmin() / df.idxmax()
>>> df.describe()
>>> df.mean()
>>> df.median()
```

Sum of values
Cummulative sum of values
Minimum/maximum values
Minimum/Maximum index value
Summary statistics
Mean of values
Median of values

Applying Functions

```
>>> f = lambda x: x**2
>>> df.apply(f)
>>> df.applymap(f)
```

Apply function
Apply function element-wise

Data Alignment

Internal Data Alignment

NA values are introduced in the indices that don't overlap:

```
>>> s3 = pd.Series([7, -2, 3], index=['a', 'c', 'd'])
>>> s + s3
a    10.0
b    NaN
c     5.0
d     7.0
```

Arithmetic Operations with Fill Methods

You can also do the internal data alignment yourself with the help of the fill methods:

```
>>> s.add(s3, fill_value=0)
a    10.0
b    -5.0
c     5.0
d     7.0
>>> s.sub(s3, fill_value=2)
>>> s.div(s3, fill_value=4)
>>> s.mul(s3, fill_value=3)
```



Python For Data Science Cheat Sheet

Scikit-Learn

Learn Python for data science interactively at www.DataCamp.com



Scikit-learn

Scikit-learn is an open source Python library that implements a range of machine learning, preprocessing, cross-validation and visualization algorithms using a unified interface.



A Basic Example

```
>>> from sklearn import neighbors, datasets, preprocessing
>>> from sklearn.model_selection import train_test_split
>>> from sklearn.metrics import accuracy_score
>>> iris = datasets.load_iris()
>>> X, y = iris.data[:, :2], iris.target
>>> X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=33)
>>> scaler = preprocessing.StandardScaler().fit(X_train)
>>> X_train = scaler.transform(X_train)
>>> X_test = scaler.transform(X_test)
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
>>> knn.fit(X_train, y_train)
>>> y_pred = knn.predict(X_test)
>>> accuracy_score(y_test, y_pred)
```

Loading The Data

Also see NumPy & Pandas

Your data needs to be numeric and stored as NumPy arrays or SciPy sparse matrices. Other types that are convertible to numeric arrays, such as Pandas DataFrame, are also acceptable.

```
>>> import numpy as np
>>> X = np.random.random((10, 5))
>>> y = np.array(['M', 'M', 'F', 'F', 'M', 'F', 'M', 'F', 'F'])
>>> X[X < 0.7] = 0
```

Training And Test Data

```
>>> from sklearn.model_selection import train_test_split
>>> X_train, X_test, y_train, y_test = train_test_split(X,
...                                                     y,
...                                                     random_state=0)
```

Preprocessing The Data

Standardization

```
>>> from sklearn.preprocessing import StandardScaler
>>> scaler = StandardScaler().fit(X_train)
>>> standardized_X = scaler.transform(X_train)
>>> standardized_X_test = scaler.transform(X_test)
```

Normalization

```
>>> from sklearn.preprocessing import Normalizer
>>> scaler = Normalizer().fit(X_train)
>>> normalized_X = scaler.transform(X_train)
>>> normalized_X_test = scaler.transform(X_test)
```

Binarization

```
>>> from sklearn.preprocessing import Binarizer
>>> binarizer = Binarizer(threshold=0.0).fit(X)
>>> binary_X = binarizer.transform(X)
```

Create Your Model

Supervised Learning Estimators

Linear Regression

```
>>> from sklearn.linear_model import LinearRegression
>>> lr = LinearRegression(normalize=True)
```

Support Vector Machines (SVM)

```
>>> from sklearn.svm import SVC
>>> svc = SVC(kernel='linear')
```

Naive Bayes

```
>>> from sklearn.naive_bayes import GaussianNB
>>> gnb = GaussianNB()
```

KNN

```
>>> from sklearn import neighbors
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
```

Unsupervised Learning Estimators

Principal Component Analysis (PCA)

```
>>> from sklearn.decomposition import PCA
>>> pca = PCA(n_components=0.95)
```

K Means

```
>>> from sklearn.cluster import KMeans
>>> k_means = KMeans(n_clusters=3, random_state=0)
```

Model Fitting

Supervised learning

```
>>> lr.fit(X, y)
>>> knn.fit(X_train, y_train)
>>> svc.fit(X_train, y_train)
```

Unsupervised Learning

```
>>> k_means.fit(X_train)
>>> pca_model = pca.fit_transform(X_train)
```

Fit the model to the data

Fit the model to the data
Fit to data, then transform it

Prediction

Supervised Estimators

```
>>> y_pred = svc.predict(np.random.random((2,5)))
>>> y_pred = lr.predict(X_test)
>>> y_pred = knn.predict_proba(X_test)
```

Unsupervised Estimators

```
>>> y_pred = k_means.predict(X_test)
```

Predict labels
Predict labels
Estimate probability of a label
Predict labels in clustering algos

Encoding Categorical Features

```
>>> from sklearn.preprocessing import LabelEncoder
>>> enc = LabelEncoder()
>>> y = enc.fit_transform(y)
```

Imputing Missing Values

```
>>> from sklearn.preprocessing import Imputer
>>> imp = Imputer(missing_values=0, strategy='mean', axis=0)
>>> imp.fit_transform(X_train)
```

Generating Polynomial Features

```
>>> from sklearn.preprocessing import PolynomialFeatures
>>> poly = PolynomialFeatures(5)
>>> poly.fit_transform(X)
```

Evaluate Your Model's Performance

Classification Metrics

Accuracy Score

```
>>> knn.score(X_test, y_test)
>>> from sklearn.metrics import accuracy_score
>>> accuracy_score(y_test, y_pred)
```

Estimator score method

Metric scoring functions

Classification Report

```
>>> from sklearn.metrics import classification_report
>>> print(classification_report(y_test, y_pred))
```

Precision, recall, f1-score and support

Confusion Matrix

```
>>> from sklearn.metrics import confusion_matrix
>>> print(confusion_matrix(y_test, y_pred))
```

Regression Metrics

Mean Absolute Error

```
>>> from sklearn.metrics import mean_absolute_error
>>> y_true = [3, -0.5, 2]
>>> mean_absolute_error(y_true, y_pred)
```

Mean Squared Error

```
>>> from sklearn.metrics import mean_squared_error
>>> mean_squared_error(y_test, y_pred)
```

R² Score

```
>>> from sklearn.metrics import r2_score
>>> r2_score(y_true, y_pred)
```

Clustering Metrics

Adjusted Rand Index

```
>>> from sklearn.metrics import adjusted_rand_score
>>> adjusted_rand_score(y_true, y_pred)
```

Homogeneity

```
>>> from sklearn.metrics import homogeneity_score
>>> homogeneity_score(y_true, y_pred)
```

V-measure

```
>>> from sklearn.metrics import v_measure_score
>>> metrics.v_measure_score(y_true, y_pred)
```

Cross-Validation

```
>>> from sklearn.cross_validation import cross_val_score
>>> print(cross_val_score(knn, X_train, y_train, cv=4))
>>> print(cross_val_score(lr, X, y, cv=2))
```

Tune Your Model

Grid Search

```
>>> from sklearn.grid_search import GridSearchCV
>>> params = {"n_neighbors": np.arange(1,3),
...            "metric": ["euclidean", "cityblock"]}
>>> grid = GridSearchCV(estimator=knn,
...                      param_grid=params)
>>> grid.fit(X_train, y_train)
>>> print(grid.best_score_)
>>> print(grid.best_estimator_.n_neighbors)
```

Randomized Parameter Optimization

```
>>> from sklearn.grid_search import RandomizedSearchCV
>>> params = {"n_neighbors": range(1,5),
...            "weights": ["uniform", "distance"]}
>>> rsearch = RandomizedSearchCV(estimator=knk,
...                               param_distributions=params,
...                               cv=4,
...                               n_iter=8,
...                               random_state=5)
>>> rsearch.fit(X_train, y_train)
>>> print(rsearch.best_score_)
```



Python For Data Science Cheat Sheet

Matplotlib

Learn Python Interactively at www.DataCamp.com



Matplotlib

Matplotlib is a Python 2D plotting library which produces publication-quality figures in a variety of hardcopy formats and interactive environments across platforms.



1 Prepare The Data

Also see [Lists & NumPy](#)

1D Data

```
>>> import numpy as np  
>>> x = np.linspace(0, 10, 100)  
>>> y = np.cos(x)  
>>> z = np.sin(x)
```

2D Data or Images

```
>>> data = 2 * np.random.random((10, 10))  
>>> data2 = 3 * np.random.random((10, 10))  
>>> Y, X = np.mgrid[-3:3:100j, -3:3:100j]  
>>> U = -1 - X**2 + Y  
>>> V = 1 + X - Y**2  
>>> from matplotlib.cbook import get_sample_data  
>>> img = np.load(get_sample_data('axes_grid/bivariate_normal.npy'))
```

2 Create Plot

```
>>> import matplotlib.pyplot as plt
```

Figure

```
>>> fig = plt.figure()  
>>> fig2 = plt.figure(figsize=plt.figaspect(2.0))
```

Axes

All plotting is done with respect to an Axes. In most cases, a subplot will fit your needs. A subplot is an axes on a grid system.

```
>>> fig.add_axes()  
>>> ax1 = fig.add_subplot(221) # row-col-num  
>>> ax3 = fig.add_subplot(212)  
>>> fig3, axes = plt.subplots(nrows=2, ncols=2)  
>>> fig4, axes2 = plt.subplots(ncols=3)
```

3 Plotting Routines

1D Data


```
>>> fig, ax = plt.subplots()  
>>> lines = ax.plot(x, y)  
>>> ax.scatter(x, y)  
>>> axes[0,0].bar([1,2,3],[3,4,5])  
>>> axes[1,0].barh([0.5,1,2.5],[0,1,2])  
>>> axes[1,1].axhline(0.45)  
>>> axes[0,1].axvline(0.65)  
>>> ax.fill(x,y,color='blue')  
>>> ax.fill_between(x,y,color='yellow')
```

2D Data or Images

```
>>> fig, ax = plt.subplots()  
>>> im = ax.imshow(img,  
                  cmap='gist_earth',  
                  interpolation='nearest',  
                  vmin=-2,  
                  vmax=2)
```

Plot Anatomy & Workflow

Plot Anatomy



Workflow

The basic steps to creating plots with matplotlib are:

- 1 Prepare data
- 2 Create plot
- 3 Plot
- 4 Customize plot
- 5 Save plot
- 6 Show plot

```
>>> import matplotlib.pyplot as plt  
>>> x = [1,2,3,4]  
>>> y = [10,20,25,30] Step 1  
>>> fig = plt.figure() Step 2  
>>> ax = fig.add_subplot(111) Step 3  
>>> ax.plot(x, y, color='lightblue', linewidth=3) Step 3.4  
>>> ax.scatter([2,4,6],  
             [5,15,25],  
             color='darkgreen',  
             marker='^')  
>>> ax.set_xlim(1, 6.5)  
>>> plt.savefig('foo.png')  
>>> plt.show() Step 6
```

4 Customize Plot

Colors, Color Bars & Color Maps

```
>>> plt.plot(x, x, x, x**2, x, x**3)  
>>> ax.plot(x, y, alpha = 0.4)  
>>> ax.plot(x, y, c='k')  
>>> fig.colorbar(im, orientation='horizontal')  
>>> im = ax.imshow(img,  
                  cmap='seismic')
```

Markers

```
>>> fig, ax = plt.subplots()  
>>> ax.scatter(x,y,marker=".")  
>>> ax.plot(x,y,marker="o")
```

Linestyles

```
>>> plt.plot(x,y,linewidth=4.0)  
>>> plt.plot(x,y,ls='solid')  
>>> plt.plot(x,y,ls='--')  
>>> plt.plot(x,y,'-.',x**2,y**2,'-.')  
>>> plt.setp(lines,color='r',linewidth=4.0)
```

Text & Annotations

```
>>> ax.text(1,-2.1,  
           'Example Graph',  
           style='italic')  
>>> ax.annotate("Sine",  
               xy=(8, 0),  
               xycoords='data',  
               xytext=(10.5, 0),  
               textcoords='data',  
               arrowprops=dict(arrowstyle="->",  
                               connectionstyle="arc3"),)
```

Vector Fields

```
>>> axes[0,1].arrow(0,0,0.5,0.5)  
>>> axes[1,1].quiver(y,z)  
>>> axes[0,1].streamplot(X,Y,U,V)
```

Mathtext

```
>>> plt.title(r'$\sigma_i=15$', fontsize=20)
```

Limits, Legends & Layouts

```
>>> ax.margins(x=0.0,y=0.1)  
>>> ax.axis('equal')  
>>> ax.set(xlim=[0,10.5],ylim=[-1.5,1.5])  
>>> ax.set_xlim(0,10.5)
```

Legends

```
>>> ax.set(title='An Example Axes',  
           ylabel='Y-Axis',  
           xlabel='X-Axis')  
>>> ax.legend(loc='best')
```

Ticks

```
>>> ax.xaxis.set(ticks=range(1,5),  
                  ticklabels=[3,100,-12,"foo"])  
>>> ax.tick_params(axis='y',  
                           direction='inout',  
                           length=10)
```

Subplot Spacing

```
>>> fig3.subplots_adjust(wspace=0.5,  
                           hspace=0.3,  
                           left=0.125,  
                           right=0.9,  
                           top=0.9,  
                           bottom=0.1)  
>>> fig.tight_layout()
```

Axis Spines

```
>>> ax1.spines['top'].set_visible(False)  
>>> ax1.spines['bottom'].set_position(('outward',10))
```

Add padding to a plot
Set the aspect ratio of the plot to 1
Set limits for x-and y-axis
Set limits for x-axis

Set a title and x-and y-axis labels

No overlapping plot elements

Manually set x-ticks

Make y-ticks longer and go in and out

Adjust the spacing between subplots

Fit subplot(s) in to the figure area

Make the top axis line for a plot invisible

Move the bottom axis line outward

5 Save Plot

Save figures

```
>>> plt.savefig('foo.png')
```

Save transparent figures

```
>>> plt.savefig('foo.png', transparent=True)
```

6 Show Plot

```
>>> plt.show()
```

Close & Clear

```
>>> plt.cla()
```

```
>>> plt.clf()
```

```
>>> plt.close()
```

Clear an axis
Clear the entire figure
Close a window



Python For Data Science Cheat Sheet

Seaborn

Learn Data Science interactively at www.DataCamp.com



Statistical Data Visualization With Seaborn

The Python visualization library **Seaborn** is based on `matplotlib` and provides a high-level interface for drawing attractive statistical graphics.

Make use of the following aliases to import the libraries:

```
>>> import matplotlib.pyplot as plt  
>>> import seaborn as sns
```

The basic steps to creating plots with Seaborn are:

1. Prepare some data
2. Control figure aesthetics
3. Plot with Seaborn
4. Further customize your plot

```
>>> import matplotlib.pyplot as plt  
>>> import seaborn as sns  
>>> tips = sns.load_dataset("tips")  
>>> sns.set_style("whitegrid")  
Step 1  
>>> g = sns.lmplot(x="tip",  
y="total_bill",  
data=tips,  
aspect=2)  
Step 2  
>>> g.set_axis_labels("Tip", "Total bill(USD)")  
set(xlim=(0,10), ylim=(0,100))  
Step 3  
>>> plt.title("title")  
Step 4  
>>> plt.show(g)  
Step 5
```

1) Data

Also see [Lists, NumPy & Pandas](#)

```
>>> import pandas as pd  
>>> import numpy as np  
>>> uniform_data = np.random.rand(10, 12)  
>>> data = pd.DataFrame({'x':np.arange(1,101),  
'y':np.random.normal(0,4,100)})
```

Seaborn also offers built-in data sets:

```
>>> titanic = sns.load_dataset("titanic")  
>>> iris = sns.load_dataset("iris")
```

2) Figure Aesthetics

Seaborn styles

```
>>> sns.set()  
>>> sns.set_style("whitegrid")  
>>> sns.set_style("ticks",  
{"xtick.major.size":8,  
"ytick.major.size":8})  
>>> sns.axes_style("whitegrid")
```

(Re)set the seaborn default
Set the matplotlib parameters
Set the matplotlib parameters
Return a dict of params or use with
with to temporarily set the style

Context Functions

```
>>> sns.set_context("talk")  
>>> sns.set_context("notebook",  
font_scale=1.5,  
rc={"lines.linewidth":2.5})
```

Color Palette

```
>>> sns.set_palette("husl",3)  
>>> sns.color_palette("husl")  
>>> flatui = ["#9b59b6","#3498db","#95a5e6","#e74c3c","#34495e","#2ecc71"]  
>>> sns.set_palette(flatui)
```

Also see [Matplotlib](#)

3) Plotting With Seaborn

Axis Grids

```
>>> g = sns.FacetGrid(titanic,  
col="survived",  
row="sex")  
>>> g.map(plt.hist,"age")  
>>> sns.factorplot(x="pclass",  
y="survived",  
hue="sex",  
data=titanic)  
>>> sns.lmplot(x="sepal_width",  
y="sepal_length",  
hue="species",  
data=iris)
```

Subplot grid for plotting conditional relationships

Draw a categorical plot onto a Facetgrid

Plot data and regression model fits across a FacetGrid

```
>>> h = sns.PairGrid(iris)  
>>> h = h.map(plt.scatter)  
>>> sns.pairplot(iris)  
>>> i = sns.JointGrid(x="x",  
y="y",  
data=data)  
>>> i = i.plot(sns.regplot,  
sns.distplot)  
>>> sns.jointplot("sepal_length",  
"sepal_width",  
data=iris,  
kind='kde')
```

Subplot grid for plotting pairwise relationships
Plot pairwise bivariate distributions
Grid for bivariate plot with marginal univariate plots

Plot bivariate distribution

Categorical Plots

Scatterplot
`>>> sns.stripplot(x="species",
y="petal_length",
data=iris)
>>> sns.swarmplot(x="species",
y="petal_length",
data=iris)`

Bar Chart

```
>>> sns.barplot(x="sex",  
y="survived",  
hue="class",  
data=titanic)
```

Count Plot

```
>>> sns.countplot(x="deck",  
data=titanic,  
palette="Greens_d")
```

Point Plot

```
>>> sns.pointplot(x="class",  
y="survived",  
hue="sex",  
data=titanic,  
palette={"male":"g",  
"female":"m"},  
markers=["^","o"],  
linestyles=["-","--"])
```

Boxplot

```
>>> sns.boxplot(x="alive",  
y="age",  
hue="adult_male",  
data=titanic)
```

Violinplot

```
>>> sns.violinplot(x="age",  
y="sex",  
hue="survived",  
data=titanic)
```

Scatterplot with one categorical variable

Categorical scatterplot with non-overlapping points

Show point estimates and confidence intervals with scatterplot glyphs

Show count of observations

Show point estimates and confidence intervals as rectangular bars

Boxplot

Boxplot with wide-form data

Violin plot

Regression Plots

```
>>> sns.regplot(x="sepal_width",  
y="sepal_length",  
data=iris,  
ax=ax)
```

Plot data and a linear regression model fit

Distribution Plots

```
>>> plot = sns.distplot(data.y,  
kde=False,  
color="b")
```

Plot univariate distribution

Matrix Plots

```
>>> sns.heatmap(uniform_data,vmin=0,vmax=1)
```

Heatmap

4) Further Customizations

Also see [Matplotlib](#)

Axisgrid Objects

```
>>> g.despine(left=True)  
>>> g.set_ylabels("Survived")  
>>> g.set_xticklabels(rotation=45)  
>>> g.set_axis_labels("Survived",  
"Sex")  
>>> h.set(xlim=(0,5),  
ylim=(0,5),  
xticks=[0,2.5,5],  
yticks=[0,2.5,5])
```

Remove left spine
Set the labels of the y-axis
Set the tick labels for x
Set the axis labels

Set the limit and ticks of the x-and y-axis

Plot

```
>>> plt.title("A Title")  
>>> plt.ylabel("Survived")  
>>> plt.xlabel("Sex")  
>>> plt.ylim(0,100)  
>>> plt.xlim(0,10)  
>>> plt.setp(ax,yticks=[0,5])  
>>> plt.tight_layout()
```

Add plot title
Adjust the label of the y-axis
Adjust the label of the x-axis
Adjust the limits of the y-axis
Adjust the limits of the x-axis
Adjust a plot property
Adjust subplot params

5) Show or Save Plot

Also see [Matplotlib](#)

```
>>> plt.show()  
>>> plt.savefig("foo.png")  
>>> plt.savefig("foo.png",  
transparent=True)
```

Show the plot
Save the plot as a figure
Save transparent figure

Close & Clear

```
>>> plt.cla()  
>>> plt.clf()  
>>> plt.close()
```

Clear an axis
Clear an entire figure
Close a window



Python For Data Science Cheat Sheet

Bokeh

Learn Bokeh [Interactively](#) at www.DataCamp.com, taught by Bryan Van de Ven, core contributor




Plotting With Bokeh

The Python interactive visualization library **Bokeh** enables high-performance visual presentation of large datasets in modern web browsers.



Bokeh's mid-level general purpose `bokeh.plotting` interface is centered around two main components: data and glyphs.



The basic steps to creating plots with the `bokeh.plotting` interface are:

1. Prepare some data:
Python lists, NumPy arrays, Pandas DataFrames and other sequences of values
2. Create a new plot
3. Add renderers for your data, with visual customizations
4. Specify where to generate the output
5. Show or save the results

```
>>> from bokeh.plotting import figure
>>> from bokeh.io import output_file, show
>>> x = [1, 2, 3, 4, 5]           Step 1
>>> y = [6, 7, 2, 4, 5]
>>> p = figure(title="simple line example",   Step 2
              x_axis_label='x',
              y_axis_label='y')
>>> p.line(x, y, legend="Temp.", line_width=2)  Step 3
>>> output_file("lines.html")      Step 4
>>> show(p)                      Step 5
```

1) Data

[Also see Lists, NumPy & Pandas](#)

Under the hood, your data is converted to Column Data Sources. You can also do this manually:

```
>>> import numpy as np
>>> import pandas as pd
>>> df = pd.DataFrame(np.array([[33.9, 4, 65, 'US'],
                               [32.4, 4, 66, 'Asia'],
                               [21.4, 4, 109, 'Europe']]),
                     columns=['mpg', 'cyl', 'hp', 'origin'],
                     index=['Toyota', 'Fiat', 'Volvo'])
```

```
>>> from bokeh.models import ColumnDataSource
>>> cds_df = ColumnDataSource(df)
```

2) Plotting

```
>>> from bokeh.plotting import figure
>>> p1 = figure(plot_width=300, tools='pan,box_zoom')
>>> p2 = figure(plot_width=300, plot_height=300,
               x_range=(0, 8), y_range=(0, 8))
>>> p3 = figure()
```

3) Renderers & Visual Customizations

Glyphs



Scatter Markers

```
>>> p1.circle(np.array([1,2,3]), np.array([3,2,1]),
             fill_color='white')
>>> p2.square(np.array([1.5,3.5,5.5]), [1,4,3],
             color='blue', size=1)
```



Line Glyphs

```
>>> p1.line([1,2,3,4], [3,4,5,6], line_width=2)
>>> p2.multi_line(pd.DataFrame([[1,2,3],[5,6,7]]),
                  pd.DataFrame([[3,4,5],[3,2,1]]),
                  color="blue")
```

Customized Glyphs

[Also see Data](#)



Selection and Non-Selection Glyphs

```
>>> p = figure(tools='box_select')
>>> p.circle('mpg', 'cyl', source=cds_df,
             selection_color='red',
             nonselection_alpha=0.1)
```



Hover Glyphs

```
>>> from bokeh.models import HoverTool
>>> hover = HoverTool(tooltips=None, mode='vline')
>>> p3.add_tools(hover)
```



Colormapping

```
>>> from bokeh.models import CategoricalColorMapper
>>> color_mapper = CategoricalColorMapper(
             factors=['US', 'Asia', 'Europe'],
             palette=['blue', 'red', 'green'])
>>> p3.circle('mpg', 'cyl', source=cds_df,
             color=dict(field='origin',
                        transform=color_mapper),
             legend='Origin')
```

Legend Location

Inside Plot Area

```
>>> p.legend.location = 'bottom_left'
```

Outside Plot Area

```
>>> from bokeh.models import Legend
>>> r1 = p2.asterisk(np.array([1,2,3]), np.array([3,2,1]))
>>> r2 = p2.line([1,2,3,4], [3,4,5,6])
>>> legend = Legend(items=[("One", [p1, r1]), ("Two", [r2])],
                    location=(0, -30))
>>> p.add_layout(legend, 'right')
```

Legend Orientation

```
>>> p.legend.orientation = "horizontal"
>>> p.legend.orientation = "vertical"
```

Legend Background & Border

```
>>> p.legend.border_line_color = "navy"
>>> p.legend.background_fill_color = "white"
```

Rows & Columns Layout

Rows

```
>>> from bokeh.layouts import row
>>> layout = row(p1,p2,p3)
```

Columns

```
>>> from bokeh.layouts import column
>>> layout = column(p1,p2,p3)
```

Nesting Rows & Columns

```
>>> layout = row(column(p1,p2), p3)
```

Grid Layout

```
>>> from bokeh.layouts import gridplot
>>> row1 = [p1,p2]
>>> row2 = [p3]
>>> layout = gridplot([[p1,p2], [p3]])
```

Tabbed Layout

```
>>> from bokeh.models.widgets import Panel, Tabs
>>> tab1 = Panel(child=p1, title="tab1")
>>> tab2 = Panel(child=p2, title="tab2")
>>> layout = Tabs(tabs=[tab1, tab2])
```

Linked Plots

Linked Axes

```
>>> p2.x_range = p1.x_range
>>> p2.y_range = p1.y_range
```

Linked Brushing

```
>>> p4 = figure(plot_width = 100,
                tools='box_select,lasso_select')
>>> p4.circle('mpg', 'cyl', source=cds_df)
>>> p5 = figure(plot_width = 200,
                tools='box_select,lasso_select')
>>> p5.circle('mpg', 'hp', source=cds_df)
>>> layout = row(p4,p5)
```

4) Output & Export

Notebook

```
>>> from bokeh.io import output_notebook, show
>>> output_notebook()
```

HTML

Standalone HTML

```
>>> from bokeh.embed import file_html
>>> from bokeh.resources import CDN
>>> html = file_html(p, CDN, "my_plot")
```

```
>>> from bokeh.io import output_file, show
>>> output_file('my_bar_chart.html', mode='cdn')
```

Components

```
>>> from bokeh.embed import components
>>> script, div = components(p)
```

PNG

```
>>> from bokeh.io import export_png
>>> export_png(p, filename="plot.png")
```

SVG

```
>>> from bokeh.io import export_svgs
>>> p.output_backend = "svg"
>>> export_svgs(p, filename="plot.svg")
```

5) Show or Save Your Plots

```
>>> show(p1)
>>> save(p1)
```

```
>>> show(layout)
>>> save(layout)
```

