

23. At a fixed efficiency of 30% for converting beam power to microwave power, operating at a current that is 80% of the space-charge-limiting value, plot the microwave output power at 2 MV as a function of wall radius (assuming a 2-mm standoff between the thin annular beam and the wall). Take account of space-charge depression of the beam energy.
24. To get higher beam power at fixed voltage, one must raise the current. Given that the beam must have some separation from the wall, it seems that one must increase the radius of the drift tube. From the standpoint of basic klystron operating principles, what problem does this raise?
25. To continue to raise beam currents while maintaining cutoff between cavities, the triaxial klystron, with a center conductor in the drift tube, has been proposed. We want to know the cutoff frequencies for the triaxial waveguide configuration. To avoid the headaches of cylindrical geometry and Bessel functions, consider the case where the cylindrical geometry is almost planar, when the inner conductor is close to the outer. (a) Derive the normal modes and dispersion relation for the three classes of waves in a planar waveguide with infinite parallel-plate conductors separated by a distance d : transverse electromagnetic (TEM), transverse electric (TE), and transverse magnetic (TM). (b) Comment qualitatively on the difficulties posed by the TEM waves. If you can, offer a comment about the probability that these waves will couple to a beam and drive axial density perturbations.
26. In the reltron, the modulation cavity fill time delays microwave onset. We define this time as the period from the start of the electron beam to the time when the microwave signal reaches its full-power flattop. In Figure 9.29, estimate the cavity Q and the reduction in energy efficiency that this effect causes.
27. Derive the expression for the space-charge-limiting current in the triaxial klystron given in Equations 9.35 and 9.36.

References

In the following, many publications from the Stanford Linear Accelerator Center, which are available online through the SPIRES database, have SLAC publication numbers, even if they are also printed in the proceedings of the conference at which they were presented.

1. Varian, R. and Varian, S., A high frequency oscillator and amplifier, *J. Appl. Phys.*, 10, 321, 1939.

2. Staprans, A., McCune, E., and Reutz, J., High power linear-beam tubes, *Proc. IEEE*, 61, 299, 1973.
3. Konrad, G.T., High Power RF Klystrons for Linear Accelerators, paper presented at the Linear Accelerator Conference, Darmstadt, Germany, 1984 (SLAC-PUB-3324, 1984).
4. Lee, T.G., Lebacqz, J.V., and Konrad, G.T., A 50-MW Klystron for the Stanford Linear Accelerator Center, paper presented at the International Electron Devices Meeting, Washington, DC, 1983 (SLAC-PUB-3214, 1983).
5. Caryotakis, G., "High-power" microwave tubes: in the laboratory and on-line, *IEEE Trans. Plasma Sci.*, 22, 683, 1994.
6. Sprehn, D., Caryotakis, G., and Phelps, R.M., 150-MW S-Band Klystron Program at the Stanford Linear Accelerator Center, paper presented at the 3rd International Conference on RF Pulsed Power Sources for Linear Colliders, Hayama, Japan, 1996 (SLAC-PUB-7232, 1996).
7. Choroba, S., Hameister, J., and Jarylkapov, S., Performance of an S-Band Klystron at an Output Power of 200 MW, DESY Internal Report M 98-11 (1998), paper presented at the 19th International Linear Accelerator Conference (LINAC 98), Chicago, IL.
8. Sprehn, D. et al., X-band klystron development at the Stanford Linear Accelerator Center, *Proc. SPIE*, 4031, 137, 2000 (SLAC-PUB-8346).
9. See, for example, Lau, Y.Y., Some design considerations on using modulated intense annular electron beams for particle acceleration, *J. Appl. Phys.*, 62, 351, 1987.
10. Allen, M.A. et al., Relativistic Klystron Research for High Gradient Accelerators, paper presented at European Particle Accelerator Conference, Rome, 1988 (SLAC-PUB-4650, 1988; Lawrence Livermore National Laboratory, UCRL-98843).
11. Hamilton, D.R., Knipp, J.R., and Kuper, J.B.H., *Klystrons and Microwave Triodes*, McGraw-Hill, New York, 1948, pp. 81-82.
12. See Shintake, T., Nose-Cone Removed Pillbox Cavity for High-Power Klystron Amplifiers, KEK Preprint 90-53, Tsukuba, Japan, 1990, and references to earlier treatments there.
13. Hamilton, D.R., Knipp, J.R., and Kuper, J.B.H., *Klystrons and Microwave Triodes*, McGraw-Hill, New York, 1948, pp. 79-94.
14. Halbach, K. and Holsinger, R.F., SUPERFISH: a computer program for evaluation of RF cavities with cylindrical symmetry, *Part. Accel.*, 7, 213, 1976.
15. Gilmour, A.S., Jr., *Microwave Tubes*, Artech House, Dedham, MA, 1986, p. 229.
16. Gilmour, A.S., Jr., *Microwave Tubes*, Artech House, Dedham, MA, 1986, p. 216.
17. Branch, G.M., Jr., Electron beam coupling in interaction gaps of cylindrical symmetry, *IRE Trans. Electron Devices*, ED-8, 193, 1961.
18. Branch, G.M. and Mihran, T.G., Plasma frequency reduction factors in electron beams, *IRE Trans. Electron Devices*, ED-2, 3, 1955.
19. Branch, G.M., Jr. et al., Space-charge wavelengths in electron beams, *IEEE Trans. Electron Devices*, ED-14, 350, 1967.
20. Gilmour, A.S., Jr., *Microwave Tubes*, Artech House, Dedham, MA, 1986, p. 228.
21. Gilmour, A.S., Jr., *Microwave Tubes*, Artech House, Dedham, MA, 1986, p. 220.
22. Briggs, R.J., Space-charge waves on a relativistic, unneutralized electron beam and collective ion acceleration, *Phys. Fluids*, 19, 1257, 1976.

23. Friedman, M. et al., Externally modulated intense relativistic electron beams, *J. Appl. Phys.*, 64, 3353, 1988.
24. Lau, Y.Y. et al., Relativistic klystron amplifiers driven by modulated intense relativistic electron beams, *IEEE Trans. Plasma Sci.*, 18, 553, 1990.
25. Hamilton, D.R., Knipp, J.R., and Kuper, J.B.H., *Klystrons and Microwave Triodes*, McGraw-Hill, New York, 1948, pp. 77-80.
26. Lavine, T.L. et al., Transient Analysis of Multicavity Klystrons, paper presented at the Particle Accelerator Conference, Chicago, 1989 (SLAC-PUB-4719 [Rev], 1989).
27. Miller, R.B. et al., Super-reltron theory and experiments, *IEEE Trans. Plasma Sci.*, 20, 332, 1992.
28. Marder, B.M. et al., The split-cavity oscillator: a high-power e-beam modulator and microwave source, *IEEE Trans. Plasma Sci.*, 20, 312, 1992.
29. International Study Group, International Study Group Progress Report on Linear Collider Development (SLAC-Report-559, 2000).
30. Sprehn, D., Phillips, R.M., and Caryotakis, G., The Design and Performance of 150-MW S-Band Klystrons, paper presented at the IEEE International Electron Development Meeting, San Francisco, 1994 (SLAC-PUB-6677, 1994).
31. Sprehn, D. et al., PPM Focused X-Band Klystron Development at the Stanford Linear Accelerator Center, paper presented at the 3rd International Conference on RF Pulsed Power Sources for Linear Colliders, Hayama, Japan, 1996 (SLAC-PUB-7231, 1996).
32. Caryotakis, G., Development of X-Band Klystron Technology at SLAC, paper presented at the Particle Accelerator Conference, Vancouver, BC, 1997 (SLAC-PUB-7548, 1997).
33. From the SLAC Web site: <http://www.slac.stanford.edu/grp/kly/>.
34. Abdallah, C. et al., Beam transport and RF control, in *High-Power Microwave Sources and Technologies*, Barker, R.J. and Schamiloglu, E., Eds., IEEE Press, New York, 2001, p. 254.
35. Sessler, A. and Yu, S., Relativistic klystron two-beam accelerator, *Phys. Rev. Lett.*, 58, 2439, 1987.
36. Allen, M.A. et al., Relativistic Klystron Research for Linear Colliders, paper presented at the DPF Summer Study: Snowmass '88, High-Energy Physics in the 1990s, Snowmass, CO, 1988 (SLAC-PUB-4733, 1988).
37. Allen, M.A. et al., Relativistic Klystrons, paper presented at the Particle Accelerator Conference, Chicago, 1989 (SLAC-PUB-4861; Lawrence Livermore National Laboratory, UCRL-100634; Lawrence Berkeley National Laboratory, LBL-27147; all 1989).
38. Allen, M.A. et al., Recent Progress in Relativistic Klystron Research, paper presented at the 14th International Conference on High-Energy Particle Accelerators, Tsukuba, Japan, 1989 (SLAC-PUB-5070; Lawrence Livermore National Laboratory, UCRL-101688; Lawrence Berkeley National Laboratory, LBL-27760; all 1989).
39. Houck, T. et al., Prototype microwave source for a relativistic klystron two-beam accelerator, *IEEE Trans. Plasma Sci.*, 24, 938, 1996.
40. Haimson, J. and Mecklenburg, B., Design and construction of a chopper driven 11.4 GHz traveling wave RF generator, in *Proceedings of the 1989 IEEE Particle Accelerator Conference*, Chicago, IL, 1989, p. 243.
41. Dolbilov, G.V. et al., Experimental study of 100 MW wide-aperture X-band klystron with RF absorbing drift tubes, in *Proceedings of the European Accelerator Conference (EPAC-96)*, Bristol, UK, Vol. 3, 1996, p. 2143.
42. Dolbilov, G.V. et al., Design of 135 MW X-band relativistic klystron for linear collider, in *Proceedings of the 1997 IEEE Particle Accelerator Conference*, Vancouver, BC, 1997, p. 3126.
43. Friedman, M. et al., Relativistic klystron amplifier, *Proc. SPIE*, 873, 92, 1988.
44. Levine, J.S., High current relativistic klystron research at Physics International, *Proc. SPIE*, 2154, 19, 1994.
45. Fazio, M.V. et al., A 500 MW, 1 μ s pulse length, high current relativistic klystron, *IEEE Trans. Plasma Sci.*, 22, 740, 1994.
46. Hendricks, K.J. et al., Gigawatt-class sources, in *High-Power Microwave Sources and Technologies*, Barker, R.J. and Schamiloglu, E., Eds., IEEE Press, Piscataway, NJ, 2002, p. 66.
47. Serlin, V. and Friedman, M., Development and optimization of the relativistic klystron amplifier, *IEEE Trans. Plasma Sci.*, 22, 692, 1994.
48. Friedman, M. et al., Efficient generation of multigigawatt rf power by a klystronlike amplifier, *Rev. Sci. Instrum.*, 61, 171, 1990.
49. Colombant, D.G. et al., RF converter simulation: imposition of the radiation condition, *Proc. SPIE*, 1629, 15, 1992.
50. Serlin, V. et al., Relativistic klystron amplifier. II. High-frequency operation, *Proc. SPIE*, 1407, 8, 1991.
51. Friedman, M. et al., Relativistic klystron amplifier. I. High power operation, *Proc. SPIE*, 1407, 2, 1991.
52. Friedman, M. et al., Intense electron beam modulation by inductively loaded wide gaps for relativistic klystron amplifiers, *Phys. Rev. Lett.*, 74, 322, 1995.
53. Friedman, M. et al., Efficient conversion of the energy of intense relativistic electron beams into rf waves, *Phys. Rev. Lett.*, 75, 1214, 1995.
54. Miller, R.B. and Habiger, K.W., A review of recent progress in reltron tube design, in *Proceedings of the 12th International Conference on High-Power Particle Beams (BEAMS'98)*, Haifa, Israel, 1998, p. 740.
55. Miller, R.B. et al., Super-reltron theory and experiments, *IEEE Trans. Plasma Sci.*, 20, 332, 1992.
56. Caryotakis, G. et al., A 2-GW, 1- μ s microwave source, in *Proceedings of the 11th International Conference on High Power Particle Beams (BEAMS'96)*, Prague, Czech Republic, 1996, p. 406.
57. Caryotakis, G., A Sheet-Beam Klystron Paper Design, paper presented at the 5th Modulator-Klystron Workshop for Future Linear Colliders, CERN, Geneva, 2001 (SLAC-PUB-8967, 2001).
58. Pasour, J., Smithe, D., and Ludeking, L., An X-band triaxial klystron, in *High Energy Density and High Power RF, 6th Workshop*, Berkeley Springs, WV, 2003, p. 141.
59. Palmer, R., Herrmannsfeldt, W., and Eppley, K., An immersed field cluster klystron, *Part. Accel.*, 30, 197, 1990.
60. See, for example, Wright, E. et al., Test results for a 10-MW, L-band multiple beam klystron for TESLA, in *Proceedings of EPAC 2004*, Lucerne, Switzerland, 2004, p. 1117.

Viractors, Gyrotrons and Electron Cyclotron Masers, and Free-Electron Lasers

10.1 Introduction

This chapter is devoted to a somewhat briefer treatment of three classes of narrowband microwave sources that are unrelated in their underlying operating principles: virtual cathode oscillators, gyrotrons and electron cyclotron masers, and free-electron lasers. The reason for collecting these microwave sources in a single chapter is that at this time we regard these three classes of narrowband sources as somehow less significant in the field of high power microwaves (HPM) than the sources of Chapters 7 to 9. Let us consider each separately and state the reasons for our admittedly subjective judgment, which varies with the source, recognizing that the significance of any one of them could change with shifts in the technology or application needs.

Virtual cathode oscillators are enjoying something of a renaissance at this time, and developments with two variants in particular — tunable viractors and coaxial viractors — may yet overcome two problems that have plagued devices of this type: low efficiency and sensitivity to gap closure in the high-current, explosive emission diodes that are so often used with sources of this type. Nevertheless, despite their efficiency problems, these sources are attractive in applications requiring a simple source configuration — viractors many times employ no applied magnetic field and no slow-wave structure — and low device impedance, which permits high power operation at low voltage or optimizes coupling with low-impedance power sources such as explosive generators, which are a compact, energy-rich power source.

Gyrotrons are an extraordinarily mature source for high-average-power application at the several-megawatt level to the problem of heating magnetic fusion plasmas at electron cyclotron resonance frequencies of 100 GHz or more (see Chapter 3). In fact, gyrotrons join klystrons as the only sources that are produced to continuously generate power levels at 1 MW or above. Another variant of this class of *electron cyclotron masers*, the *gyroklystron*, has been investigated as an alternative to klystrons for power levels around 100 MW and frequencies in the X-band and above. Another variant, the *cyclotron*